NORTHWEST PIPE AND CASING CLACKAMAS, OREGON SITE ASSESSMENT REPORT

4.2.3



28103



ecology and environment, inc.

1500 FIRST INTERSTATE BUILDING, 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

July 2, 1993

Chris D. Field United States Environmental Protection Agency 1200 Sixth Avenue, HW-113 Seattle. WA 98101

REF: TDD T10-9210-031

Dear Chris:

Enclosed please find a copy of the final site assessment report and a Potential Hazardous Waste Site Identification form for the Northwest Pipe and Casing Site, located in Clackamas, Oregon. Field work was begun in early October with TAT visiting the site to perform an elevation survey and to establish current site conditions. Drilling and sampling activities were begun on October 26 and concluded on November 20, 1992. A total of seven monitoring wells were installed using newly developed field screening technology to assist in selection of monitoring zones.

Based on analytical data collected from the monitoring wells and from on-site locations, potential degradation of regional groundwater quality is of concern. Data indicate high concentrations and unknown quantities of uncontrolled hazardous materials are present on the site. Similar compounds at lower concentrations were detected in groundwater along the sites former perimeter. TCE was detected in field screening analysis of groundwater samples collected while drilling. Inorganics, such as chromium and lead, and semivolatile compounds, such as phthalates, were detected in groundwater samples from monitoring wells. Continued monitoring of groundwater quality is recommended to establish a database and determine trends.

Direct contact is also of concern due to lack of site security and evidence of transient occupancy. Repair or replacement of fencing is necessary to prevent exposure to on-site contaminants.

NWPC warrants further consideration for removal actiity to mitigate potential for environmental impact to groundwater and surface water. As a result of the variable on-site lithology, a general assessment of the feasibility of controlling groundwater while excavating cannot be made.

Mr. Chris Field July 2, 1993 Page 2

Based on geologic data, it appears that, at some locations, excavation will not pose any problem while at others, dewatering and on-site treatment will be necessary. Exploratory excavations at known and suspected disposal locations are required to establish the depth at which the wastes are buried and groundwater quality and quantity.

Sincerely,

William L. Carberry

Technical Assistance Team Leader

JJR/gam

Enclosure

Ecology and Environment, Inc. - Technical Assistance Team Document Circulation Request

TO:	William Carberry, TATL, E & E, Seattle							
FROM:	, osc							
SUBJ:	: Northwest Pipe and Casing Site Assessment Report Clackamas, Oregon							
REF:	TDD: T10-9210-031							
Ple parties:	lease mail copies of the above-noted report ts:	o the following						
Name	Address	Date Sent (TAT)						
		OSC						

1 1	REMOVAL	ACTION
<i>i</i> · /	110111	11011011

POTENTIAL HAZARDOUS WASTE SITE

I. IDENTIFICATION							
01 STATE	02 SITE NUMBER						
WA	ORO201						

SEPA	SITE IDENT	IFICA	TION		WA	ORO201
II. SITE NAME AND LOCATION						
31 SITE NAME (Legal, common, or describere name of see)		02 STREE	T, ROUTE NO	OR SPECI	FIG LOCATION IDENTIFIER	
Northwest Pipe and	Casing ·	946	0 S.E.	Law	nfield Road]
33 CITY		04 STATE	05 ZIP CODE	08 COL	YTNL	07COUNTY 08 CON
Clackamas		OR	97015	C1	ackamas	3.5
III. RESPONSIBLE PARTIES					<u> </u>	
O1 OWNER (# thouse)		02 STREE	T (Business, reside)	new. meang	,	
Wayne Hall Propert	y Owner					
03 CITY		04 STATE	05 ZIP CODE	1.	EPHONE NUMBER	
I					3654-6844	
07 OPERATOR (If known and different from owner)		OB STREE	T (Buemees, reade	neel means		
None		ļ	Y. T. L.			
09 CITY		10 STATE	1 1 ZIP CODE	12 TEL	EPHONE NUMBER	
13 TYPE OF OWNERSHIP (Check one) XOXA, PRIVATE B. FEDERAL			□ C STAT	ne n	D. COUNTY E. M	UNIÇIPAL
AA	(Agency name)				D. COOKITY (1) 2. M	ONICIPAL
☐ F. OTHER:	(Specify)	_	G. UNK	NOWN		
IV. HOW IDENTIFIED	· · · · · · · · · · · · · · · · · · ·					
O1 DATE IDENTIFIED O2 IDENTIFIED BY M A. CITIZEN C E. RCRA INS H. OTHER	COMPLAINT 8. INDUSTRY PECTION F. SURFACE IMP		ATE/LOCAL GO NT ASSESSME		_ · · · ·	ECONNAISANCE PAIDENTIFICATION
V. SITE CHARACTERIZATION						
01 TYPE OF SITE (Check at that abov)	E C DISCOCAL C D LINAUE	HORIZED	DI IMPING		nuco	
☐ A. STORAGE ☐ B. TREATMENT	☑ C. DISPOSAL ☐ D. UNAUT	MONIZED	DUMPING	U E. UI	(Specify)	
02 SUMMARY OF KNOWN PROBLEMS (Provide narral						•
On-site buried waste Northwest Pipe and C	e. Documented so Casing is Nationa	oil a al Pr	ind gro	undw es L	ater contar isted.	mination.
03 SUMMARY OF ALLEGED OR POTENTIAL PROB	RLEMS (Provide nerraive description)					
VI. INFORMATION AVAILABLE FROM						
01 CONTACT	02 OF (Agency/Organiz					03 TELEPHONE NUMBER
Mark Ader	Region	10 US	SEPA			206 553-16
JJ Roland	05 AGENCY		& E		07 TELEPHONE NUMBER (206624-95	

TECHNICAL ASSISTANCE TEAM SITE ASSESSMENT FINAL REPORT FOR:

NORTHWEST PIPE AND CASING CLACKAMAS, OREGON

TDD T10-9210-031

REPORT PREPARED BY: ECOLOGY AND ENVIRONMENT, INC. PROJECT MANAGER: DAWN HARTLEY

DATE: MAY 1993

SUBMITTED TO CHRIS D. FIELD, DEPUTY PROJECT OFFICER and JOHN SAINSBURY, ON-SCENE COORDINATOR SUPERFUND RESPONSE AND INVESTIGATIONS BRANCH U.S. ENVIRONMENTAL PROTECTION AGENCY REGION X SEATTLE, WASHINGTON

TABLE OF CONTENTS

Secti	on	Page
ABSTR	ACT	
1.0	INTRODUCTION	1
2.0	SITE CONDITIONS AND BACKGROUND. 2.1 Site Description. 2.1.1 Site Evaluation. 2.1.2 Site Location. 2.1.3 Site Characteristics. 2.1.4 Release Threat Posed By Site. 2.1.5 NPL Status.	2 2 2 2 2 5 6
	2.2 Actions to Date	6 6 6 7 7 10 13 14 17 20
	2.3 State and Local Authorities Role to Date	20
3.0	PUBLIC HEALTH AND ENVIRONMENTAL THREATS	20 23 23 23
4.0	ENDANGERMENT DETERMINATION	24
5.0	CONCLUSIONS	24
REFE	RENCES	
APPE	NDIX A: PHOTOGRAPHIC DOCUMENTATION	
APPEI	NDIX B: GEOLOGIC AND TRENCH LOGS	
APPE	NDIX C: FIELD SCREENING ANALYSIS	
APPE	NDIX D: QUALITY ASSURANCE REVIEW	

LIST OF FIGURES

F <u>igures</u>		Page
1	Location Map	3
2	Site Map	4
3	Preliminary Groundwater Contours	8
4	Monitoring Well Location Map	9
5	Generalized Monitoring Well Construction	11
6	Groundwater Elevations-Shallow Wells	15
7	Groundwater Elevations-Lower Gravel Aquifer	16
8	Trench Location Map	22

LIST OF TABLES

<u>Tables</u>		Page
1	Groundwater Monitoring Well Screened Intervals	12
2	Field Screening Results: Shallow Soils and Groundwater	18
3	Analytical Results of Groundwater Sampling	19
4	Analytical Results of Trench Water Samples	21

ABSTRACT

Technical Directive Document T10-9210-031 tasked Ecology and Environment, Inc. (E & E) Region 10 Technical Assistance Team (TAT) to conduct a site assessment at Northwest Pipe and Casing, a National Priorities List site located in Clackamas, Oregon.

The purpose of the site assessment was to evaluate off-site groundwater quality to determine the need for a removal action to address allegations of waste sources buried on-site. Solvents and pipe coatings high in PAHs are reportedly buried throughout the site and were observed at the site surface. A total of seven groundwater monitoring wells were installed and sampled as part of this site assessment. In addition, on-site trenches were excavated adjacent to previously identified geophysical anomalies to evaluate groundwater quality associated with alleged burials.

Analytical data indicate the presence of tetrachloroethelene at a low concentration in one of the wells constructed on former Northwest Pipe and Casing property and downgradient of alleged sources. Semi-volatile and inorganic contaminants were also detected in monitoring wells along the downgradient border of current and former site boundaries. Groundwater collected from on-site trenches showed elevated concentrations of inorganics, VOCs, and PAHs and buried debris was observed. These data support the possible need for removal of on-site sources to mitigate potential threat to local groundwater and surface water resources.

SITE ASSESSMENT REPORT FOR Northwest Pipe and Casing Clackamas, Oregon T10-9210-031

Site Name/Address:

Northwest Pipe and Casing Between Lawnfield and Mather Roads Clackamas, Oregon

Investigation Participants:

Dawn A. Hartley, TAT, Project Manager
Jeffrey Fowlow, TAT, Geologist
John J. Roland, TAT, Geologist
Michael Szerlog, TAT, Chemist
Mark Woodke, TAT, Chemist
Ecology and Environment, Inc., Seattle, WA, (206) 624-9537

Dates of Site Assessment:

October 26 to November 20, 1993

1.0 INTRODUCTION

The U. S. Environmental Protection Agency (EPA) Region X Superfund Response and Investigations Branch (SRIB) tasked the Ecology and Environment, Inc., (E & E) Region 10 Technical Assistance Team (TAT) to conduct an assessment at the Northwest Pipe and Casing (NWPC) site, located in Clackamas, Oregon under contract No. 68-W0-0037.

NWPC is listed on the National Priorities List (NPL) for hazardous waste sites requiring assessment and remediation by the EPA. On-site groundwater contamination was documented in a Listing Site Inspection (LSI) conducted by the E & E Region 10 Field Investigation Team (FIT) in 1990. Polychlorinated biphenyls (PCBs), inorganics, polycyclic aromatic hydrocarbons (PAHs), tetrachloroethene and other volatile organic compounds (VOCs) were detected by FIT in on-site groundwater and soils.

The EPA tasked the TAT to conduct a site assessment to evaluate groundwater quality downgradient of the site. Evaluation of the migration potential, and subsequent impact to local groundwater resources, would determine the need for a removal action to address allegations of buried waste.

2.0 SITE CONDITIONS AND BACKGROUND

2.1 Site Description

2.1.1 Site Evaluation

NWPC is the site of a former pipe manufacturing and coating facility in an industrialized section of Clackamas, Clackamas County, Oregon (Figure 1). The NWPC site was operated by various parties from 1956 to 1986 (E & E 1990). The site has been inactive since 1986, and although several buildings have been removed, numerous dilapidated structures remain. The site is fenced but holes have been cut along the Mather Road boundary and evidence of trespassing, vagrancy, and vandalism is apparent throughout the site.

2.1.2 Site Location


The NWPC site is located in Clackamas, approximately 20 miles southeast of Portland, Oregon. During operation, the facility occupied 55 acres in sections 4 and 9 of Township 2 South, Range 2 East of the United States Geological Survey (USGS) 7.5 Minute Series, Gladstone Quadrangle. Subsequently, the property has been divided into three separate lots. The primary NWPC site is the most significantly impacted and also the largest lot occupying 36 acres and designated Parcel B. The other two lots (each approximately 10 acres), designated Parcel A are currently occupied by the Oregon Department of Transportation (ODOT) and Northwest Development Company (NWDC) respectively (Figure 2). NWPC is located between Lawnfield and Mather Roads, and bordered to the west by the Southern Pacific Railroad. To the east lies Camp Withycombe, an Oregon National Guard facility and Mount Talbert.


2.1.3 Site Characteristics

The E & E Region 10 FIT conducted a Screening Site Inspection (SSI) at NWPC in April 1988 and subsequently a LSI that was completed in June 1990 (E & E 1990). The site was assigned to the NPL on October 14, 1992.

The investigations conducted under the FIT contract identified and documented surface soil contamination, subsurface soil contamination, and groundwater contamination within the primary NWPC site. Additionally, FIT documented geophysical anomalies indicative of buried metallic and non-metallic sources throughout the site. Suspicions that the anomalies were buried drums and sludge lagoons was never confirmed by the FIT.

The NWPC site is level, except for several manmade mounds, and is prone to flooding. The northwest half of the site is particularly susceptible and is commonly covered by standing water during winter months. A series of manmade ditches drain the site north to Mount Scott Creek.





Clackamas River, located one mile south of the site. The Clackamas River is used as a potable water resource in the Clackamas area (E & E 1990).

The site is heavily vegetated with blackberry brambles and small trees or bushes that severely limit line of sight. Paved and gravel roads connect the standing buildings and debris left in the footprints of demolished buildings. The system of roads connects with Mather Road to the south and Industrial Way on the north. Prior to installation of the fence, the NWPC road system was utilized as a short cut between Mather and Lawnfield roads. Solidified coal tar product is evident and abundant throughout the site, particularly in the vicinity of the former Plant 3 building.

2.1.4 Release Threat Posed By Site

Off-site migration of contaminants by the groundwater pathway represents the highest threat of release posed by the site. VOCs, PAHs, and PCBs were detected in shallow on-site wells and similar compounds were detected at lower concentrations in wells located along the downgradient border of the present and former site boundaries. Characteristics of the contaminant source have not been determined and therefore the associated release threat can not be fully evaluated. The source is potentially attributable to leaking buried drums, allegedly buried on site, that may be contributing limited, and possible seasonal, influxes of contaminants. With time and continued deterioration of the rumored drums there may be future container failure that results in a greater pulse of contaminants. Groundwater characteristics of the underlying gravel aquifer may not be sufficient to provide mitigating effects to such a release. Since the quantity and concentration of contaminants in allegedly on-site buried containers is unknown it is not possible to estimate the subsequent effect on groundwater quality. Municipal supply wells are located within one mile of the site.

The surface water pathway also poses a threat of release from the site overland flow of precipitation across the site to the system of site drainage ditches. The tendency of water to pond on the site is indicative of an inability to infiltrate the soils and a shallow depth to the top of the water table. Heavy rainfall events that are common in the Pacific Northwest will, in the absence of infiltration, result in runoff across the site to the ditch system. As the water flows across the site it can erode and carry sediments contaminated with high levels of PAHs. Release of contaminated sediments from the site from surface water runoff is a potential concern.

Direct contact with surface soils poses a release threat to both humans and animals. Contaminated soils and product are prevalent and easily accessible. Past sampling of surface soils have detected VOCs such as TCE and xylene, PCB Aroclor 1254, and a variety of semivolatile heterocyclic and polycyclic aromatic compounds in on-site soils (E & E 1988,90). The fence that surrounds the site is an ineffective security measure. Numerous gaps are present in the fence and holes have been cut to gain access.

Release threat posed by the air pathway is limited to dry summer months. The site has several areas of exposed soils that may dry out and become airborne during the summer months. Concentrations of PAHs in the surface soils are high enough to pose a threat but the majority of the site is well vegetated minimizing the release potential.

2.1.5 NPL Status

As previously discussed, the LSI for the Northwest Pipe and Casing site was completed in June 1990. The LSI resulted in a sufficient Hazard Ranking System (HRS) score for the site to be assigned NPL status on October 14, 1992.

2.2 Actions to Date

2.2.1 Previous Actions and Investigations

NWPC has been the subject of numerous previous actions and investigations. In accordance with the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) of 1980, NWPC has been the subject of a Preliminary Assessment (PA), an SSI, and an LSI. The PA, SSI, and LSI were used to collect information necessary to generate and substantiate HRS scoring for the site.

Information collected for the HRS scoring package included waste types, waste quantities, and waste releases to the environment. The types of materials handled at this facility included coal tar, coal tar epoxies, pipe primer (bitumastic jet primer containing 70 percent volatile organic compounds in a chlorinated paraffin and rubber base), asphalt, cement mortar, and steel pipe. It is believed that waste products were placed in lagoons or buried on site in drums, the quantity of waste and amount released to the environment is unknown.

On-site soils contained PAHs at concentrations up to 5,800 parts per million (ppm), tetrachloroethene to 3.2 ppm, and PCBs to 1,000 ppm. Groundwater samples from on-site wells contained low concentrations of volatile organic compounds that in concentrated, or pure form are dense non-aqueous phase liquids (DNAPLs), including tetrachloroethene up to 4.2 ppm, and PAHs up to 5.0 ppm. These dilute concentrations indicate the potential presence of immiscible phase DNAPLs. Aroclor 1254 was detected at 15 parts per billion (ppb) in one on-site monitoring well. Lead, chromium, barium, and other heavy metals were also detected at elevated concentrations in groundwater samples from on-site monitoring wells (E & E 1988, 90).

2.2.2 Current Action

2.2.2.1 Sampling Rationale

The TAT was tasked by EPA to determine the need for a removal action at NWPC based on the release threat posed by the site. To determine if contaminants released from the source have migrated

downgradient and pose a threat to the regional groundwater resource, public health and/or the environment, TAT identified four primary objectives.

To confirm groundwater flow direction(s) and determine placement of proposed downgradient wells, the TAT surveyed existing wells, collected groundwater elevations, and constructed a groundwater contour map. Downgradient well placement was determined from this map and drill rig accessibility. To determine the magnitude and extent of downgradient groundwater contamination attributable to the site, TAT installed a total of seven monitoring wells. One in an assumed background location and 6 downgradient of the primary NWPC site. To determine if previously identified geophysical anomalies are attributable to buried sources, TAT excavated on-site test trenches. Finally, to determine the feasibility of on-site excavation of alleged buried waste, TAT conducted a pump test to determine the hydraulic characteristics of the shallow aquifer. Photodocumentation of these activities is included in Appendix A.


2.2.2.2 Elevation Survey


TAT conducted a vertical control survey to evaluate the reliability of existing water level data and groundwater contour maps. Water level elevation data collected during the LSI is presented in Figure 3 (E&E 90). Relative casing elevations of the seven on-site wells, two Oregon National Guard (ONG) Camp Withycombe wells, and four ODOT wells were obtained. Results of the survey, in conjunction with water lever measurements taken concurrently at each well, confirmed the general groundwater flow direction illustrated in Figure 3 and dictated monitoring well placement shown in Figure 4.

Following completion and development of TAT monitoring wells, an additional vertical control and water level elevation survey was conducted. The new wells were incorporated into the existing monitoring well network for refinement of groundwater contours. All water level measurements, accurate to 0.01 feet, were collected with an electronic sounder and tape measure in accordance with the established E & E Standard Operating Procedure (E & E 1990a SOP).

2.2.2.3 Monitoring Well Installation

A total of 5 EPA and 2 ODOT monitoring wells were constructed. The EPA wells were designated MW-8 through MW-12 as a continuation of wells MW-1 through MW-7 constructed on-site during the LSI. The ODOT wells are numbered ODOT-5 and ODOT-6 to compliment well designations ODOT-1 through ODOT-4 assigned to existing tank pit wells (Figure 4). As each well was drilled, soil and groundwater samples were collected at 5-foot intervals and screened in the field for the VOCs tetrachloroethene (PCE) and trichloroethene (TCE). Screening was accomplished using a field portable gas chromatograph (GC) operated by TAT chemists. Well screens were placed to monitor at intervals selected based on the analytical data obtained from screening soil and water samples and from interpretation of lithologic conditions encountered while drilling.





The deep wells were installed at depths of approximately 95 to 100 feet below ground surface (bgs), no VOCs were detected in the lower portions of these boreholes. Screen intervals were selected based on lithology and contaminant characteristics. Zones just above the deepest transition from gravel to fine-grained lithology were selected for monitoring in an effort to intercept the DNAPL contaminants as they move downward toward the base of the gravel aquifer. The more shallow installations were constructed at depths corresponding to detection of contaminants by field screening.

The monitoring wells were constructed of clean, 4-inch inside diameter (I.D.), type 304 stainless steel casing with matching sump, screen, and casing. All casing segments include flush threaded joints with 0-rings. The well screens are a manufactured 10-slot (0.010-inch) wire wound type screen, 5 feet in length. Stainless steel centralizers were installed at the bottom and top of the screened intervals and an additional centralizer was installed 50 feet above the top of the screen in the deeper wells. The sand pack consists of clean, 10-20 mesh graded silica sand from one foot below the bottom of the screened interval to 2 feet above the top of the screen. A 2-foot thick bentonite plug was set on top of the sand pack. High solids bentonite grout (PureGold) was then tremied from the top of the bentonite plug to ground surface. A PureGold mixer was used to hydrate to a 30% solids slurry. Each batch of grout was weighed with a mud balance prior to placement to ensure recommended density was achieved.

Below grade monitoring well boxes were used to complete all the wells except MW-8, which was completed with a 6-inch steel protective casing. All below grade installations were cemented in place, appropriately designated and the well casings fitted with locking caps. MW-8 was completed using a cement pad and locking cover for the 6-inch protective casing. A generalized monitoring well construction diagram is shown in Figure 5 and screened intervals are given in Table 1.

2.2.2.4 Geology

NWPC is located on a relatively level alluvial flood plain north of the Clackamas River. The site is underlain by Quartenary Age alluvial sediments. These sediments consist of silty sands, silts, clays, and gravels (E & E 1988, 90). Regionally, these deposits unconformably overlie fluvial terrace deposits consisting of poorly sorted gravels with minor sand and silt lenses. Underlying the terrace deposits are discontinuous lava flows (Boring Lavas), well-indurated sandstones and conglomerates of the Troutdale Formation, and older clays and silts of the Sandy River Mudstone unit. In the vicinity of the site these units are mapped as unconformably overlying Tertiary age Columbia River Basalts (USGS 1983, 1989).

Geologic logs compiled by E & E during field activities at NWPC indicate that in the vicinity of the site the shallow subsurface consists of interbedded silts, clays, sands, and gravels. These interbeds extend to a depth of about 10 feet bgs in the northern wells (MW-9, -10, -11, and -12) and about 8 feet bgs in the southernmost well




TABLE 1

GROUNDWATER MONITORING WELL SCREENED INTERVAL
BELOW GROUND SURFACE
NORTHWEST PIPE AND CASING
CLACKAMAS, OREGON

MONITORING WELL	SCREENED INTERVAL (FEET BGS)
MW-8	66.0 - 71.0
MW-9	79.5 - 84.5
MW-10	28.5 - 33.5
MW-11	60.0 - 65.0
MW-12	33.0 - 38.0
ODOT-5	95.0 - 100.0
ODOT-6	14.0 - 19.0

(MW-8). The lithology grades to an increasingly gravel rich deposit for approximately 5 to 7 feet below the interbeds. Detailed Geologic Logs are presented in Appendix B.

Underlying these shallow deposits are well graded, fine— to coarse gravels that extend to depths of at least 95 to 100 feet. Minor sand/silt zones, or lenses, were occasionally noted within the gravel. The lenses were generally one or two feet thick with gravel remaining the dominant feature of the sample, at greater than 50 percent.

2.2.2.5 Hydrology

The shallow interbedded sequence of silts, clays, sands, and gravels contain both saturated and unsaturated zones that may, depending on the screened material, yield small quantities of groundwater. These conditions are substantiated by geologic logs and groundwater yields of on-site shallow wells constructed to depths of 7 to 15 bgs for the LSI.

The presence of the underlying gravel aquifer at shallow depths may impact the ability to easily excavate on-site to investigate the areas of geophysical anomalies. Excavation is necessary to confirm the allegations of buried waste and to subsequently remove the sources. Excavation is limited by the high yield of the aquifer, pump capacity required to maintain a relatively dry excavation, and the ability to treat recovered water. To estimate the production capacity of the aquifer, TAT conducted a pump test utilizing an on-site well. Transmissivity was estimated at 3,000 gallons per day per foot (gpd/ft) from a specific capacity test conducted on MW-3. This well was selected based on historic data and TAT field screening that indicated it was the least contaminated of the on-site wells. It is also screened within a zone of increasing gravel content, 11 to 16 feet bgs, and as a result is presumably one of the more productive on-site wells.

No aquifer test data was collected at the deeper off-site wells due to the significant amount of purge water that would have to be contained and treated as investigation derived waste. However, during drilling of these wells the observed groundwater production capacity indicates that this is a high yield aquifer. The relatively low transmissivity noted at mw-3 is most likely not indicative of conditions in the gravel aquifer nor of conditions within the shallow aquifer across the site. The inferred high yield of this lower gravel aquifer is likely providing dilution and dispersion effects that may significantly reduce contaminant concentrations within the aquifer.

The relationship between the shallow and deeper gravel aquifers has not been determined, but analytical data indicates that contaminants associated with NWPC are also present in wells at the downgradient boundary of the site. Wells MW-10 and -12 are constructed within the upper portion of the gravel aquifer at depths of 35 and 40 feet bgs respectively. Field screening analytical results indicate these wells are contaminated with low concentrations of contaminants associated with NWPC.


After all monitoring wells were installed, developed, and completed the TAT conducted a vertical control survey to tie the new wells into the existing network of surveyed wells. TAT then collected a final round of groundwater elevation data from MW-1 through MW-12, ODOT-1 through ODOT-6, and ONG-1 and ONG-2 on November 19, 1992. This data was used to generate the contoured groundwater elevation maps illustrated in Figures 6 and 7. These maps indicate that groundwater flows to the northwest within the gravel aquifer although the gradient apparently varies with depth indicating a vertical componant of flow.


2.2.2.6 Field Screening

Field analysis of soil and groundwater samples collected during drilling operations was determined to be the most efficient and effective means of identifying optimal zones for groundwater monitoring. After review of available site information, TAT determined that dilution and dispersion effects would result in downgradient contaminant concentrations below the detection limits of conventional field screening instrumentation.

TAT identified and procured instrumentation capable of meeting the needs of the project. TAT selected the field portable Sentex Systems Scentograph GC with an argon ionization detector coupled with a purge and trap unit. TAT modified Region 10 Field Analytical Support Project (FASP) method F080.001 to the Sentex operating parameters. All FASP method quality control were met for initial calibration, continuing calibration, final calibration, and quantitation limits. The compounds TCE and PCE were selected as target analytes. Detection limits of 5 ppb were obtained with a sample preparation and run time of approximately 5 minutes. Initial field calibration was verified using samples collected from MW-2, MW-4, and MW-6 which previous sampling had documented PCE and TCE. Approximately 10 percent of the field analyzed samples were submitted for laboratory confirmation with acceptable correlation. A detailed description of the field screening methodology, results, and correlation to laboratory results is provided as Appendix C.

A total of 52 borehole soil samples and 68 groundwater samples were analyzed by the portable GC to optimize well screen placement. Low levels of TCE, ranging from 3 ppb to 9 ppb, were detected in groundwater samples collected from 30 to 45 feet below ground surface while boring MW-9. To capture this zone of contamination the shallow well MW-10 was screened from approximately 30 to 35 feet bgs. Tetrachloroethene (PCE) contamination was identified in well ODOT-5 by the field GC. At 15 feet bgs the PCE concentration in groundwater was an estimated 2 ppb. PCE was detected in the soil and groundwater 35 feet bgs at estimated concentrations of less than 1 ppb. An estimated concentration of 3 ppb PCE was identified in groundwater obtained from 45 feet bgs while drilling ODOT-5. Monitoring well ODOT-6 was constructed and screened at an approximate depth of 15 to 20 feet bgs to capture this zone of contamination in the upper aquifer. No contaminants were detected during installation of MW-8, MW-11, and MW-12.





These field screening analysis indicate low concentrations of TCE were detected in groundwater samples from 15 to 45 feet bgs along the downgradient border of former site operations. Field screening results for TCE are given in Table 2, and complete field screening results and procedures are presented in Appendix C.

2.2.2.7 Sampling Results

Following installation, completion, and development each well was sampled and submitted for laboratory analysis. Groundwater samples were collected, handled, and analyzed, and results were reported per the TAT Sampling Plan/Quality Assurance Project Plan for NWPC. A quality assurance review of the analytical results performed by E & E TAT chemists is presented in Appendix D along with a key that identifies TAT sample numbers and their corresponding sample location numbers. In general, the data were judged to be acceptable, except where flagged with qualifiers which modify the usefulness of individual values.

Groundwater samples were collected from all seven monitoring wells and from three on-site trenches. All samples were analyzed for volatile organic compounds, semivolatile organic compounds, pesticides/PCBs, and inorganic compounds. A summary of laboratory analytical results is presented in Table 3 for groundwater monitoring wells and Table 4 for on-site trench samples.

Monitoring Well Sample Results

The single volatile organic analyte detected in laboratory analysis of groundwater samples was trichloroethene (TCE) at 3.0 ppb in ODOT-6. This shallow well is located on Parcel A, formerly land used as part of NWPC operations, near the fence that delineates the present site boundary. Tetrachloroethene (PCE) was not detected in any of the off-site groundwater samples either by laboratory or field screening analysis. Semivolatile organic compounds were detected at low concentrations in all the monitoring wells including the background well MW-8. Phthalates and PAHs are the predominant contaminants detected. A summary of groundwater analytical results is presented in Table 3.

Soil samples collected while drilling at the screen interval in MW-8, MW-9, MW-11 and 0D0T-5 and submitted for laboratory analysis indicate the presence of phthalates. Complete analytical results are given in Appendix D.

Phthalates are common compounds associated with degradation of plastic materials. Their presence in the background well suggests the potential of an upgradient source of this contaminant in addition to NWPC. The PAHs identified in the groundwater are common constituents of coal tar and likely associated with the NWPC site. No pesticides/PCBs were detected in any of the groundwater samples. Elevated concentrations of the inorganic compounds chromium, copper, lead, nickel, and zinc were detected in five of the seven wells. The nickel concentration in ODOT-6 exceeds the Maximum Contaminant Level (MCL) established by the EPA.

TABLE 2

FIELD SCREENING RESULTS FOR TCE
SHALLOW SOILS AND GROUNDWATER
NORTHWEST PIPE AND CASING
CLACKAMAS, OREGON
(ppb)

Sample Depth (bgs)	MW-8	MW-9/10	MW-11/12	ODOT-5/6
10' - Soil	ND	ND	ND	ND
- Water	NA	ND	ND	ND
15' - Soil	ND	NA	ND	2 F
- Water	NA	ND	ND	ND
20' - Soil	ND	ND	ND	ND
- Water	NA	ND	ND	ND
25' - Soil	ND	NA	ND	ND
- Water	NA	NA	ND	ND
30' - Soil	ND	ND	NA	ND
- Water	NA	7 F	ND	NA
35' – Soil	ND	ND	ND	<1 F
– Water	NA	ND	ND	<1 F
0' - Soil	ND	ND	NA	ND
- Water	NA	3 F	ND	ND
45' - Soil	ND	NA	NA	ND
- Water	NA	9 F	ND	3 F
30' - Soil	ND	NA	NA	ND
- Water	NA	ND	ND	ND

ND - Not detected

NA - Not analyzed

F - Data have been generated using FASP methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

TABLE 3

ANALYTICAL RESULTS OF OFF SITE GROUNDWATER SAMPLING NORTHWEST PIPE AND CASING CLACKAMAS, OREGON NOVEMBER 1992 (ppb)

Analyte	8 ~1:714	<i>PTVI</i> = 9	MV-10	MW-11	MW-12	ODOT-5	ODOT-5 (Duplica	ODOT-6. te)
Volatile Organics								
Tetrachloroethene	ND	ND	ND	ND	(ID	ND	ND	ND
Trichloroethene	ND	· ND	ND	ND	ND	ND	ND	3.0 J
Semi-Volatile Organics								
Di-n-butylphthalate	2	ND	ND	ND	ND	ND	ND	ND
Bis(2-ethylhexyl)phthal	37 J	8 J	11	53 J	36 J	31 J	ND	10
Acenaphthene	ND	NO	10	ND	ND	2 J	ND	40
Di-n-octylphthalate	ND	ND	ND	ND	3 J	ND	ND	ND
Dibenzofuran	ND	ND	ND	ND	ND	ND	ND	16
Fluorene	ND	ND	ND	ND	ND	ND	ND	13
Phenanthrene	t1D	. 11D	ND	ИD	ND	ND	ND	9 J
Fluoranthene	11D	ИD	ND	ND	ND	ND	ИD	8 J
Pyrene	11D	ND	ND	ND	ND	ND	ИО	7 Ј
Pesticides/PCBs								
None detected	MD	ti D	ND	NE	ND	ND	ИD	ИD
Inorganics								
Arsenic	iID	:10	11.1	ND	IID	ND	ND	ИD
Chromium	69.4	₽D.	41.0	ND	80.1	ND	11.6	980
Copper	:ID	ND	71.8	. ND	ND	29.0	ND	46.6
Lead	3.1	ND	23.2	ND	ND	5.8	ND	4.7
Nickel	₽D	ND	44.8	ND	72.6	ND	ИD	597
Zinc	ND	ND	110	กด	106	43.2	ИD	25.9

J - The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.

19

ND - Not detected

Trench Sample Results

Groundwater samples collected from shallow trenches excavated during this project indicate a significant variation in on-site groundwater quality (Table 4). A total of 4 trenches, designated T-1 through T-4, were excavated from 6.5 to 8.5 feet bgs. Trench locations are illustrated in Figure 8 and soil profiles are included in Appendix B. No contaminants were detected in the sample collected from T-1 and no sample was collected from T-3 due to insufficient groundwater and lack of visible contamination.

Trench sample T-2 contained a wide range of high concentration semivolatile and low concentration inorganic contaminants. Semivolatile contaminants are primarily PAHs consistent with products know to have been used on-site. Napthalene was detected at 4,000 ppb, Acenaphthene at 6,200 ppb, Dibenzofuran at 3,500 ppb, Phenanthrene at 6,700 ppb, and Fluoranthene at 4,500 ppb. Nine of the thirteen priority pollutant metals are present at elevated concentrations in sample T-2. Trench sample T-4 contained similar contaminants at much lower concentrations. These trench sample results and the debris and oily sheen observed in two of the trenches may indicate the presence of buried waste at the NWPC site.

2.2.2.8 Investigation Derived Waste

Groundwater and drill cuttings generated during drilling operations, monitoring well construction, and groundwater sampling at NWPC were contained and stored on site. Analysis of samples collected from the Investigation Derived Wastes (IDW) did not indicate the presence of hazardous materials. The drill cuttings were removed from the drums, the drums cleaned, and then removed from the site. Two tanks used to store the water portion of the IDW were drained to a low section of the site, cleaned out and removed from the site.

2.3 State and Local Authorities Role to Date

The State of Oregon Department of Environmental Quality (DEQ) has demonstrated an active interest in the NWPC site. DEQ has monitored groundwater elevations since NWPC was assigned NPL status. DEQ has demonstrated cooperation with the TAT investigation by providing groundwater elevations and other requested information. TAT provided DEQ with a debriefing of activities completed during the investigation. Preliminary copies of TAT drilling and sampling logs were provided to DEQ at their request and under the direction of the On-Scene Coordinator (OSC).

3.0 PUBLIC HEALTH AND ENVIRONMENTAL THREATS

3.1 Threats to Public Health and Welfare

The NWPC site presents a potential threat to public health and welfare through several mechanisms. There is a high potential for direct contact with contaminated on-site soils. This threat is

TABLE 4

ANALYTICAL RESULTS OF TRENCH WATER SAMPLES
NORTHWEST PIPE AND CASING
CLACKAMAS, OREGON
NOVEMBER 1992
(ppb)

Analyte	T-1	T-2	T-3	T-4
Volatile Organics			1-	
Vinyl Chloride	ND	ND	*	37
Semi-Volatile Organics				
Napthalene	ND	4,000		2 J
2-Methylnapthalene	ND	1,100		ND
Acenaphthene	ND	6,200		25
Dibenzofuran	ND	3,500		10
Fluorene	ND	2,900		37
Phenanthrene	ND	6,700		68
Anthracene	ND	500 J		84
Fluoranthene	ND	4,500		16
Pyrene	ND	3,200		17
Benzo(a)anthracene	ND	460 J		ND
Chrysene	ND	470 J		5 J
Benzo(b)fluranthene	ND	200 J		ND
Pesticides/ PCBs				
None detected	ND	ND		ND
Inorganics				
Antimony	ND	ND		81.3
Arsenic	ND	14.7		ND
Cadmium	ND	5.0		ND
Chromium	ND	76.4		29.4
Copper	ND	141		46.4
Lead Lead	ND	23.4		9.4
Mercury	ND	0.26		ND
Nickel	ND	60.6		ND
Zinc	21.3	352		277

J - The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.

ND - Not detected

^{*} No visable contamination, no sample collected.

Southern Pacific Railroad

22

particularly high among vagrants, teenagers, and children that are attracted to the abandoned buildings and have little difficulty gaining access through the vandalized fence.

Public health and welfare could be threatened by the potential contamination of potable groundwater resources. Analytical data indicates the presence of multiple on-site sources and that releases from those sources have occurred. The transmissive nature of the aquifer complicates interpretation of the source release mechanism and the magnitude of potential groundwater quality impact. A steady state release condition may exist or deteriorating conditions may result in a significant release within a finite time frame. Such a release, although physically unlikely has the potential to exceed the dilution capacity of the aquifer and threaten downgradient drinking water resources.

Surface water and associated mechanisms may also threaten public health. Surface water runoff may result in the transportation of contaminated soils to previously unaffected locations presenting an unknown and unanticipated threat to those that may come in contact with the soil. Site runoff also poses a public threat through potential contamination of surface waters used for recreational resources.

3.2 Threats to the Environment

On-site contamination presents a potential threat to the environment through direct contact and ingestion of soils and coal tar by animals that may forage on the easily accessible property. Water fowl was observed to congregate on the ponds of standing water located through out the site. Surface water runoff from the site is likely to occur due to the low rate of infiltration apparent at the site. As a result contaminants can be transported off-site as part of the suspended sediment load or as dissolved constituents of the runoff. This potential poses a threat to the quality of the water in downgradient rivers such as the Clackamas. The sensitive riverine environment and associated plants and animals are also threaten by this potential runoff.

The most significant environmental threat posed by the NWPC site is the potential impact to a large regional groundwater resource. If the source of dilute DNAPL compounds documented in on-site wells were to undergo a large scale release, remediation efforts and costs would increase significantly. Characteristics of DNAPLs decrease the potential for recovery from groundwater once released. Source identification and removal is essential to reduce environmental impact.

3.3 Status and Regulatory Authorities

The NWPC site was assigned NPL status on October 14, 1992. EPA has authority under CERCLA to investigate, and remediate if necessary, hazardous waste sites that pose a threat to public health and environmental quality. Past and present site owners have been identified as Potentially Liable Parties as part of the LSI.

4.0 ENDANGERMENT DETERMINATION

Allegations of buried waste were substantiated by the TAT investigation. Trench excavation conducted on site was exploratory and not invasive, and as a result avoided geophysical anomalies indicative of buried metal drums or debris. Excavation did establish that migration of semivolatile and inorganic contaminants away from the source has occurred. Additionally, the low concentrations of VOCs detected in downgradient wells suggests that migration has occurred away from the source as well as substantial dilution.

Although a release has apparently occurred, the impact to down-gradient receptors is diminished by dilution and dispersion effects. Continued confidence and reliance on dilution and dispersion to mitigate the threat the public health or welfare and the environment is dependent on identification of the source and release mechanism.

The potential degradation of alleged buried containers pose the threat of release of hazardous substances in sufficient quantity to exceed the dilution effects of the aquifer. Such a release may present and imminent and substantial endangerment to public health, or welfare, and the environment. Identification, characterization, and removal of sources to the extent practicable is recommended for further consideration in order to reduce potential for environmental impact.

5.0 CONCLUSIONS

NWPC, a Superfund NPL site, is a former pipe coating and manufacturing facility located in Clackamas, Oregon. The site was active for approximately thirty years until closed in 1986.

Seven groundwater-monitoring wells were installed using recently developed field analysis equipment and techniques to determine the optimal depths for screen placement.

Groundwater flow at NWPC is to the northwest. The site is underlain by a gravel aquifer used as a potable water resource. Contaminants were detected in groundwater monitoring wells along the present and former border of site operations. Potential for degradation of local groundwater quality exists as a result of the elevated concentrations and uncertain quantities of on-site contaminants.

The shallow lithology at NWPC is variable in thickness and transmissivity across the site. The underlying gravel aquifer has, apparently, a sufficient capacity to impact excavation efforts below the depth at which it is encountered

Quarterly monitoring of water level elevations should be conducted and a data base established to determine if data collected during this assessment is representative of conditions throughout the year.

On-site excavation indicated the presence of buried wastes and contaminated groundwater.

Direct contact is of concern due to lack of site security and evidence of transient occupancy.

REFERENCES

- Ecology and Environment, Inc. (E & E) 1990, Listing Site Inspection Final Report for Northwest Pipe and Casing, Clackamas, Oregan, Field Investigation Team, USEPA Contract 68-01-7347.
- Ecology and Environment, Inc. (E & E) 1988, Site Inspection Report for Northwest Pipe and Casing, Clackamas, Oregon, Field Investigation Team, USEPA Contract 68-01-7347.
- Ecology and Environment, Inc. (E & E), 1990, Region Ten Technical Assistance Team Quality Assurance Project Plan, TDD No. T10-9010-001, Superfund Response and Investigations Section, U.S. Environmental Protection Agency.
- Ecology and Environment, Inc. (E & E), 1990a, Standard Operating Procedures, Volume 5, Geotechnical Practices.
- United States Environmental Protection Agency (USEPA), 1990, Technical Assistance Team (TAT) Contract for Emergency Response, Removal and Prevention (Zone II), Contract No. 68-WO-0037, Superfund Branch Washington DC.
- United States Geologic Society (USGS), 1983, Groundwater in the Northern Part of Clackamas County, Oregon, Open File Report 80-1049.
- United States Geologic Society(USGS), 1989, Lithology, Thickness and Extent of Hydrologic Units Underlying the East Portland Area, Oregon Water Resources Investigation Report 88-4110.


APPENDIX A PHOTOGRAPHIC DOCUMENTATION


PHOTOGRAPH IDENTIFICATION SHEET

Camera Serial No.: EPA 645491 TDD No.: T10-9210-031


Lens Type: 50mm Site Name: Northwest Pipe and Casing

Pho No.	to Date	Taken By	Description
1	10/26/92	D. Hartley	Looking northwest from outside gate on Mather Rd.
2	10/26/92	D. Hartley	
3	10/31/92	D. Hartley	
4	11/03/92	D. Hartley	
5	11/03/92	D. Hartley	
6	11/05/92	D. Hartley	Field Chromatograph laboratory.
7	10/31/92	D. Hartley	Rig set up and ready to begin drilling at MW-9.
8	10/27/92	D. Hartley	Drilling at MW-8.
9	11/09/92	D. Hartley	Drilling at MW-10.
10	11/09/92	D. Hartley	Jacking out 8 inch working casing, at MW-9, note gravel in discharge.
11	11/18/92	D. Hartley	Backhoe at trench 3. Looking north.
12	11/18/92	D. Hartley	Looking down into trench 3.
13	11/09/92	D. Hartley	Looking east across MW-11 location.
14	11/10/92	D. Hartley	Cleaning up after constructing wellhead protection at MW-11.
15	11/10/92	D. Hartley	
16	11/09/92	D. Hartley	• •
17	03/25/93	J. Kolb	Emptied drums, cuttings in foreground. Looking north.
18	03/25/93	J. Kolb	Looking west, draining storage tank
19	03/26/93	J. Kolb	Loading empty drums to remove from site.
20	03/26/93	J. Kolb	Removing drums from NWPC.




























































APPENDIX B

GEOLOGIC AND TRENCH LOGS

Project: Northwest Pipe and Casing
Boring Contractor: Staco Well Services

Boring Method: <u>Downhole hammer</u> Logged By: <u>Fowlow</u>

Date Completed: 10-29-92

Job No.: EORO201SCA

Location: Clackamas, Oregon
Surface Elevation: ~197 Feet

Casing Elevation: 200.59 Feet
Total Depth: 100 Feet

Groundwater: ~7 Feet

Boring No.: MW-8

Datum: ONG-1 (200)

Datum: ONG-1
Datum: BGS

Datum: BGS

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0-		Begin drilling: 0900		Conc. HNu Conc. GC-Soil Conc. GC-Water
- - 5-	SM	From cuttings: Silty sand: Sand (50%), very fine grained, moderate brown, moist, with silt (40%), clay 10%).		
-		Increasing gravel.		
10-	GW	Well graded gravel: Gravel (100%), fine to coarse, moderate gray, subangular, dense, wet. Insufficient sample soil recovery for sampling.	MW-8-1 0935 10-28-92	6/10/22 0.6' rec 0 ppm HNu 0 ppb GC-S
15-	GW	Well graded gravel: Gravel (90%), fine to coarse, moderate gray, subrounded, very dense, wet, with sand (10%).	MW-8-2 1005 10-28-92	5/30/37 0.8' rec 0 ppm HNu 0 ppb GC-S
-				

Depth (feet)	Symbol	Lith	nological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
- - -	GV		vel: Gravel (90%), fine to coarse, subrounded, very dense, wet, with	MW-8-3 1030 10-28-92	15/50/70 1.0' rec 0 ppm HNu 0 ppb GC-S
- 25— - -	GV	coarse, modera	vel with sand: Gravel (85%), fine to te gray and moderate brown, subrount, with sand (15%).	MW-8-4 1055 10-28-92	7/7/41 .0.5' rec 0 ppm HNu 0 ppb GC-S
30-	G ¹	coarse, modera	evel with sand: Gravel (85%), fine to te gray and moderate brown, subrounce, wet, with sand (15%).	MW-8-5 1125 10-28-92	8/26/64 0.8' rec 0 ppm HNu 0 ppb GC-S
- 35- - -	G		gvel with sand: Gravel (85%), fine to stee brown, subrounded, very dense, (15%).	MW-8-6 1200 10-28-92	11/100/R 0.7' rec 0 ppm HNu
-					

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
40-	GW	Well graced gravel with sand: Gravel (60%), fine to coarse, moderate brown to moderate gray, subrounded to rounded, very dense, wet, with sand (35%), subangular, medium to coarse, gray to grayish red, and fines (5%).	MW-8-7 1315 10-28-92	17/100/R 0.8' rec 0 ppm HNu 0 ppb GC-S
- 45- - -	GW	Well graded gravel with sand: Gravel (70%), fine to coarse, moderate gray, subrounded, very dense, wet, with sand (30%), medium to coarse, moderate brown.	MW-8-8 1340 10-28-92	15/75/R 0.7' rec 0 ppm HNu 0 ppb GC-S
50— -	GW	Well graded gravel with sand: Gravel (75%), fine to coarse, moderate gray, rounded to subrounded, very dense, wet, with sand (25%), medium to very coarse, reddish brown.	MW-8-9 1415 10-28-92	10/95/R 1.3' rec 0 ppm HNu 0 ppb GC-S
- 55 — - -	GW	Well graded gravel with sand: Gravel (75%), fine to coarse, rounded, varied colors, dense, wet, with sand (25%), medium to very coarse, reddish brown.	MW-8-10 1445 10-28-92	5/12/27 1.0' rec 0 ppm HNu 0 ppb GC-S
-				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
60 — - - -	GW	Well graded gravel with sand: Gravel (70%), fine to coarse, varied colors, rounded, very dense, wet, with sand (30%), fine to very coarse, moderate brown, and trace fines.	MW-8-11 1545 10-28-92	12/70/R 0.9' rec 0 ppm HNu 0 ppb GC-S
- 65 — - -	GW	Well graded gravel with sand: Gravel (60%), fine to coarse, varied colors, rounded, dense, wet, with sand (40%), medium to very coarse, moderate brown, and trace fines.	MW-8-12 1615 10-28-92	10/25/30 0.7' rec 0 ppm HNu
- 70-		Insufficient sample; cuttings indicate gravel as above.	1650 10-28-92	1/2/5 rec HNu
-	SM	From cuttings: 73 - 75' Very fine sand/silt layer ~2 feet thick; lower water transmissivity.	0830 10-29-92	
75— - -	GW	Well graded gravel with sand: Gravel (75%), fine to coarse, varied colors, rounded, medium dense, wet, with sand (25%), medium to very coarse, moderate brown, and trace fines.	0850 10-29-92	3/5/7 0.6' rec 0 ppm HNu
-		Additional sample same as above: From cuttings: 78 - 80' semilithified sandstone and shale, rounded to very angular cuttings, very low transmissivity.	MW-8-14 0910 10-29-92	5/8/15 0.7' rec 0 ppm HNu 0 ppb GC-S

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
80— - -	GM	Silty (clayey) gravel with sand: Gravel (60%), mostly fine, various colors, rounded, very dense, moist to wet, with sand (25%), and fines (15%), green, cohesive.	MW-8-15 0950 10-29-92	30/50/80(4) 0.8' rec 0 ppm HNu 0 ppb GC-S
-		80 - 85' drilled open borehole.		
85 — - -	GW	Well graded gravel: Gravel (100%), fine to coarse, igneous rock fragments, black with some green phenocrysts, mineral decomposition along fracture planes, angular, dense, wet.	MW-8-16 1045 10-29-92	7/27/100 0.5' rec 0 ppm HNu 0 ppb GC-S
90-	GW	Well graded gravel: Gravel (90%), fine to coarse, igneous rock fragments, angular to rounded, dense, wet, with sand (10%).	MW-8-17 1145 10-29-92	5/7/30 0.7' rec 0 ppm HNu 0 ppb GC-S
95 — -	GN	Silty (clavey) gravel with sand: Gravel (60%), fine to coarse, mostly dark gray to black, subrounded to subangular fragments, very dense, wet, with sand (20%), and fines (20%), moderate brown, wet.	MW-8-18 1330 10-29-92	27/100/R 0.7' rec 0 ppm HNu
-				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
100-	GW	Well graded gravel with sand: Gravel (80%), fine to coarse, dark gray, subangular, dense, wet, with sand (20%).	MW-8-19 1410 10-29-92	15/19/30 0.6' rec 0 ppm HNu
-		Total Depth: 100 feet below ground surface.		
105—				
-				
-			• .	
110— -				
-				
115—		·		
- 611		·		
-				
-				

Project: Northwest Pipe and Casing
Boring Contractor: Staco Well Services
Boring Method: Downhole hammer

Logged By: Fowlow

Date Completed: 11-3-92

Job No.: EORO201SCA Boring

Location: Clackamas, Oregon

Surface Elevation: ~191 Feet

Casing Elevation: 189.92 Feet

Total Depth: 92 Feet

Groundwater: ~5 Feet

Boring No.: MW-9

Datum: <u>ONG-1 (200)</u>

Datum: QNG-1
Datum: BGS
Datum: BGS

Depth (feet)	Symb	ool	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0-			Began drilling: 0830	==	Conc. HNU Conc. GC-Soil Conc. GC-Water
-					
5 <i>-</i>			From cuttings: Gravel with sand and silt.		·
					·
10-		GW- GM	Well graded gravel with silt and sand: Gravel (60%), fine to coarse, moderate brown, subangular to subrounded, very dense, wet, with sand (30%), and fines (10%).	MW-9-1 0845 11-2-92	5/27/45 0.7' rec 0 ppm HNu 0 ppb GC-soil
			From cuttings: Increase silt ~13 - 14'.		0 ppb GC-water
15-		GW	Well graded gravel: Gravel (90%), fine to coarse, varied colors, subangular to rounded, medium dense, wet, with sand (5%), and fines (5%). Insufficient soil recovery for sampling.	MW-9-2 0905 11-2-92	5/8/10 0.5' rec 0 ppm HNu NA ppb GC-S
-			recovery for sampling.		C ppb GC-W
-			·		

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
20-	SM	Silty sand: Sand (60%), fine to coarse grained, light brown, subrounded, very dense, moist, with silt (20%), and gravel (10%). Decreasing water production.	MW-9-3 0930 11-2-92	10/27/55 0.9' rec 0 ppm HNu 0 ppb GC-S 0 ppb GC-W
- 25— - -	GW	Well graded gravel: Gravel (90%), fine to coarse, dark gray to grayish black, subangular, medium dense, wet, with sand (10%). Insufficient water and soil recovery for sampling.	MW-9-4 0950 11-2-92	4/6/19 0.5' rec 0 ppm HNu NA GC-S NA GC-W
30- - -	GW	Well graded gravel with sand: Gravel (75%), fine to coarse, dark gray, subangular to rounded, very dense, wet, with sand (25%), and trace of fines.	MW-9-5 1005 11-2-92	7/20/52 1.1' rec 0 ppm HNu 0 ppb GC-S 9 ppb GC-W
- 35— - -	GW	Well graded gravel with sand: Gravel (80%), fine to coarse, dark gray, subangular to rounded, dense, wet, with sand (15%), and fines (5%).	MW-9-6 1030 11-2-92	8/15/28 1.0' rec 0 ppm OVA 0 ppb GC-S 0 ppb GC-W
_				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
40-	GW	Well graded gravel with sand: Gravel (75%), fine to coarse, dark gray, subangular to subrounded, medium dense, wet, with sand (20%), and fines (15%).	MW-9-7 1050 11-2-92	5/10/15 0.7' rec 0 ppm OVA 0 ppb GC-S 2 ppb GC-W
- 45 - - -	GW	Well graded gravel: Gravel (90%), fine to coarse, dark gray, subangular to rounded, medium dense, wet, with sand (10%), and trace fines. Insufficient soil recovery for sampling.	MW-9-8 1110 11-2-92	3/5/12 0.3' rec 0 ppm OVA NA ppb GC-S 5 ppb GC-W
- 50— - -	GW	Well graded gravel: Gravel (90%), fine to coarse, dark gray, subangular to rounded, medium dense, wet, with sand (10%) and trace fines. Insufficient soil recovery for sampling.	MW-9-9 1135 11-2-92	6/7/13 0.8' rec 1 ppm OVA NA ppb GC-S 0 ppb GC-W
- 55 — - -	sw	Well graded sand with gravel: Sand (65%), medium to very coarse, moderate brown, subrounded to rounded, very dense, wet, with gravel (30%), and fines (5%).	MW-9-10 1210 11-2-92	7/70/R 1.0' rec 0.8 ppm OVA 0 ppb GC-S 0 ppb GC-W
_				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
60-	SM	Silty sand with gravel: Sand (60%), very fine to coarse, medium dark gray, subrounded, very dense, wet, with gravel (25%), and silt (15%).	MW-9-11 1320 11-2-92	14/60/75 1.0' rec 0 ppm OVA 0 ppb GC-S 0 ppb GC-W
-		From cuttings: Wood fragments; semi-lithified sandy pellets.		
65 —	SW- SM	Well graded sand with silt and gravel: Sand (75%), very fine to coarse, subrounded, dense, wet, with gravel (15%), and silt (10%). Possibly slough.	MW-9-12 1500 11-2-92	3/12/27 0.6' rec 0 ppm OVA 0 ppb GC-S 0 ppb GC-W
-				
70— -	GW	Well graded gravel: Gravel (95%), fine to coarse, grayish black, subrounded to subangular, medium dense, wet with sand (5%) and trace fines.	MW-9-13 1530 11-2-92	3/6/12 0.4' rec 0 ppm OVA 0 ppb GC-S 0 ppb GC-W
-				
75— - -	GW	Well graded gravel: Gravel (95%), fine to coarse, medium gray to grayish black, subrounded to rounded, medium dense, wet, with sand (5%), and trace fines.	MW-9-14 1600 11-2-92	3/8/9 0.3' rec 0 ppm OVA 0 ppb GC-S 0 ppb GC-W
-				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
80-	GW	Well graded gravel: Gravel (90%), fine to coarse, medium gray to grayish black, subrounded to rounded, medium dense, wet, with sand (10%) and trace fines.	MW-9-15 1430 11-2-92	5/8/13 0.5' rec 0 ppm OVA 0 ppb GC-S 0 ppb GC-W
85— - -	GW	Well graded gravel: Gravel (95%), fine to coarse, medium gray to grayish black, rounded, medium dense, wet, with sand (5%), and trace fines.	MW-9-16 0920 11-3-92	3/7/10 0.3' rec 0 ppm OVA 0 ppb GC-S 0 ppb GC-W
90— -	SM ML	From cuttings: Decrease water production @ 87' Silty sand with trace clay. Sandy silt: Silt (60%), medium gray, very stiff to hard, moist to dry, with sand (30%), and clay (10%).	MW-9-17 1010 11-3-92	4/7/15/60(8") 1.5' rec 0 ppm OVA 0 ppb GC-S 0 ppb GC-W
- 95 - -		Total depth: 92 feet below ground surface. Boring MW-9 was terminated when a layer of fine sand, then silt, was encountered at ~87 ' bgs. Water flow through this formation was greatly reduced compared to formation above. Soil sampler was overdriven because ~8" of slough was detected by		
-		driller. The moisture level of the sample recovered also indicated a comfining layer was encountered.		

Project: Northwest Pipe and Casing Boring Contractor: Staco Well Services Boring Method: Downhole Hammer

Logged By: Fowlow Date Completed: 11-5-92 Job No.: EOR0201SCA Boring No.: MW-10 Location: Clackamas, Oregon Surface Elevation: ~191 Feet

Casing Elevation: 189.92 Feet Total Depth: 35 Feet

Groundwater: ~5 Feet

Datum: ONG-1 (200) Datum: ONG-1 Datum: BGS Datum: BGS

Depth (feet)	Sym	bol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0-			MW-10 was installed within approximately 10 feet of MW-9. An insignificant geologic variation is assumed and therefore, no samples were collected.		Conc. HNU Conc. GC-Soil Conc. GC-Water
-		:			
5-	⊒		From cuttings: Gravel with sand and silt.		
-					
10-		GW- GM	Well graded gravel with silt and sand: Gravel (60%), fine to coarse, moderate brown, subangular to subrounded, very dense, wet, with sand (30%), and fines (10%).		5/27/45 0.7' rec 0 ppm HNu 0 ppb GC-soil 0 ppb GC-water
-			From cuttings: Increase silt ~13 - 14'.		
15-		GW	Well graded gravel: Gravel (90%), fine to coarse, varied colors, Subangular to rounded, medium dense, wet, with sand (5%), and fines (5%). Insufficient soil recovery for sampling.	·	5/8/10 0.5' rec 0 ppm HNu NA ppb GC-S
- -					0 ppb GC-W
	<u> </u>	<u> </u>			<u></u>

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
20-	SM	Silty sand: Sand (60%), fine to coarse grained, light brown, subrounded, very dense, moist, with silt (20%), and gravel (10%). Decreasing water production.		10/27/55 0.9' rec 0 ppm HNu 0 ppb GC-S 0 ppb GC-W
- 25 — - -	GW	Well graded gravel: Gravel (90%), fine to coarse, dark gray to grayish black, subangular, medium dense, wet, with sand (10%). Insufficient water and soil recovery for sampling.		4/6/19 0.5' rec 0 ppm HNu NA GC-S NA GC-W
30-	GW	Well graded gravel with sand: Gravel (75%), fine to coarse, dark gray, subangular to rounded, very dense, wet, with sand (25%), and trace of fines.		7/20/52 1.1' rec 0 ppm HNu 0 ppb GC-S 9 ppb GC-W
35-	GW	Well graded gravel with sand: Gravel (80%), fine to coarse, dark gray, subangular to rounded, dense, wet, with sand (15%), and fines (5%). Total depth: 35 feet below ground surface.		8/15/28 1.0' rec O ppm OVA O ppb GC-S O ppb GC-W

Project: Northwest Pipe and Casing
Boring Contractor: Staco
Boring Method: Downhole Hammer

Logged By: Fowlow
Date Completed: 11-7-92

Job No.: EORO201SCA
Location: Clackamas, Oregon
Surface Elevation: ~192 Feet C

Casing Elevation: 191.26 Feet
Total Depth: 76 Feet

Groundwater: ~5 Feet

Boring No.: MW-11

Datum: ONG-1 (200)
Datum: ONG-1
Datum: BGS
Datum: BGS

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0-		Began drilling: 1500		Conc. HNu Conc. GC-Soil Conc. GC-Water
-				
5 <i>-</i>		From cuttings: Fine to coarse, subrounded, moderate brown, well graded gravel with sand and silt.		
-		·		·
- 10- - -	GW- GM	Well graded gravel with silt: Gravel (80%), fine to coarse, subrounded, moderate brown, very dense, wet, with sand (10%), and fines (10%).	MW-11-1 1520 11-6-92	15/31/41(R) 0.5'-rec 0 ppb GC-S 0 ppb GC-W
-				
15-	GW	Well graded gravel with sand: Gravel (80%), fine to coarse, subrounded to subangular, moderate brown to medium gray, very dense, wet, with sand (15%), and fines (5%).	MW-11-2 1600 11-6-92	26/75(R)/- 0.5' rec 0 ppb GC-S 0 ppb GC-W
-		Decrease water production at 19' bgs, increase sand and fines.		

Depth (feet)	Syn	nbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
20-		GW- GM	Well graded gravel with silt and sand: Gravel (70%), fine to coarse, subangular to subrounded, medium dark gray to dark gray, very dense, wet to moist, with sand (20%), and fines (10%).	MW-11-3 1635 11-6-92	25/75(R)/- 0.7' rec 0 ppb GC-S 0 ppb GC-W
25 -		GW- GM	Well graded gravel with silt and sand: Gravel (70%), fine to coarse, angular to subrounded, medium dark gray to dark gray, very dense, wet, with sand (20%), and fines (10%).	MW-11-4 . 0800 11-7-92	28/80(5)/- 0.7' rec 0 ppb GC-S C ppb GC-W
	-	GW	Well graded gravel: Gravel (95%), fine to coarse, angular to subrounded, dark gray, medium dense, wet, with sand (5%).	MW-11-5 0835 11-7-92	5/5/9 O.4' rec NA ppb GC-S O ppb GC-W
35-	-	GW- GM	Well graded gravel with sand: Gravel (75%), fine to coarse, angular to subrounded, dark gray, very dense, wet, with sand (20%), and fines (5%).	MW-11-6 0900 11-7-92	9/22/70 0.8' rec 0 ppb GC-S 0 ppb GC-W
	-				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
40 <i>-</i> - -	GW	Well graded gravel: Gravel (95%), coarse to fine, rounded to angular, various colors, medium dense, wet, with sand (<5%).	MW-11-7 0930 11-7-92	5/5/10 0.7' rec NA ppb GC-S 0 ppb GC-W
- 45 — - -	GW	Well graded gravel: Gravel (95%), coarse to fine, rounded to angular (broken), dark gray with various colors, medium dense, wet with sand (<5%).	MW-11-9 1000 11-7-92	6/7/11 0.7' rec NA ppb GC-S 0 ppb GC-W
50— - -	GW	Well graded gravel: As above.	MW-11-9 1030 11-7-92	5/8/15 0.5' rec NA ppb GC-S 0 ppb GC-W
55— - - -	GW	Well graded gravel: Gravel (90%), coarse to fine, rounded to angular (broken), various colors, very dense, wet with sand (10%).	MW-11-10 1055 11-7-92	5/15/70(5) 0.8' rec NA ppb GC-S 0 ppb GC-W
_				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
60-	GW	Well graded gravel: Gravel (90%), coarse to fine, rounded to angular (broken), various colors, medium dense, wet, with sand (10%).	MW-11-11 1140 11-7-92	8/12/16 0.7' rec NA ppb GC-S 0 ppb GC-W
- 65 <i>-</i> -	GW	Well graded gravel: As above.	MW-11-12 1300 11-7-92	8/11/16 O.7' rec NA ppb GC-S O ppb GC-W
-		Increasing sand/silt in cuttings; decreasing water production.		
70-	SM	Silty sand with clay: Sand (60%), very fine to medium, dark gray, medium dense, moist, with silt (25%), and clay (15%).	MW-11-13 1400 11-7-92	7/7/21 O.8' rec O ppb GC-S O ppb GC-W
-				
75— - -	ML	Clayey silt with sand: Silt (50%), medium dark gray, hard, moist to dry, with clay (30%), and sand (20%). Total depth: 76 feet below ground surface.	MW-11-14 1450 11-7-92	14/35/56 1.2' rec 0 ppb GC-S NA ppb GC-W
-				

Date Completed: 11-9-92

DRILLING AND SAMPLING LOG

Groundwater: ~5 Feet

Project: Northwest Pipe and Casing
Boring Contractor: Staco
Boring Method: Downhole Hammer
Logged By: Fowlow

Job No.: EORO201SCA
Location: Clackamas, Oregon
Surface Elevation: ~192 Feet
Casing Elevation: 191.55 Feet
Total Depth: 40 Feet

Datum: ONG-1
Datum: BGS
Datum: BGS

Datum: ONG-1 (200)

Boring No.: MW-12

Depth (feet)	Symbol	Lithological Description	Sample Number	Remarks Total blows/ Recovery
0-		MW-12 was installed within approximately 10 feet of MW-11. An insignificant geologic variation is assumed and therefore, no samples were collected.		Conc. HNu Conc. GC-Soil Conc. GC-Water
-				
5 <i>-</i> -		From cuttings: Fine to coarse, subrounded, moderate brown, well graded gravel with sand and silt.		
-				
10-	GW- GM	Well graded gravel with silt: Gravel (80%), fine to coarse, subrounded, moderate brown, very dense, wet, with sand (10%), and fines (10%).		15/31/41(R) 0.5' rec 0 ppb GC-S 0 ppb GC-W
15				26/75(R)/-
-	GW	Well graded gravel with sand: Gravel (80%), fine to coarse, subrounded to subangular, moderate brown to medium gray, very dense, wet, with sand (15%), and fines (5%).		0.5' rec 0 ppb GC-S 0 ppb GC-W
-		Decreased water production at 19' bgs, increase sand and fines.		

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
20-	GW- GM	Well graded gravel with silt and sand: Gravel (70%), fine to coarse, subangular to subrounded, medium dark gray to dark gray, very dense, wet to moist, with sand (20%), and fines (10%).		25/75(R)/- 0.7' rec 0 ppb GC-S 0 ppb GC-W
- 25 — - -	GW- GM	Well graded gravel with silt and sand: Gravel (70%), fine to coarse, angular to subrounded, medium dark gray to dark gray, very dense, wet, with sand (20%), and fines (10%).		28/80(5)/- 0.7' rec 0 ppb GC-S 0 ppb GC-W
30-	GW	Well graded gravel: Gravel (95%), fine to coarse, angular to subrounded, dark gray, medium dense, wet, with sand (5%).		5/5/9 0.4' rec NA ppb GC-S 0 ppb GC-W
- 35 — - -	GW- GM	Well graded gravel with sand: Gravel (75%), fine to coarse, angular to subrounded, dark gray, very dense, wet, with sand (20%), and fines (5%).		9/22/70 0.8' rec 0 ppb GC-S 0 ppb GC-W
_				

Depth (feet)	Sym	nbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
· 40- -		GW	Well graded gravel: Gravel (95%), coarse to fine, rounded to angular, various colors, medium dense, wet, with sand (<5%).		5/5/10 0.7' rec NA ppb GC-S 0 ppb GC-W
-			Total depth: 40 feet below ground surface.		
45—					
-					
-					
-					
50 <i>-</i>					
-					
-					
-					
- 5 5 -					
-					
_					
-					
~					

Project: Northwest Pipe and Casing Boring Contractor: Staco Well Services Boring Method: Downhole Hammer

Logged By: Fowlow

Date Completed: 11-13-92

Job No.: EORO201SCA Boring No.: DOT 5

Location: Clackamas, Oregon Surface Elevation: ~197 Feet

Casing Elevation: 195.97 Feet

Total Depth: 112 Feet Groundwater: ~5 Feet

Datum: ONG-1 (200) Datum: ONG-1_ Datum: BGS

Datum: BGS

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0— - -		Begin drilling: 1110		Conc. GC-Soil Conc. GC-Water
- - 5—		From cuttings: Silty, sandy soil 0 - 5' bgs; sandy gravel 5' - 10' bgs.		
10-	GW- GM	Well graded gravel with silt and sand: Gravel (60%), fine to coarse, subangular to subrounded, grayish brown, very dense, wet, with sand (30%), and silt (10%).	DOT-5-1 1130 11-11-92	9/70(5)/- 0.5' rec 0 ppb GC-S 0 ppb GC-W
15—	GW- GM	Well graded gravel with silt and sand: Gravel (60%), fine to coarse, subrounded, varied colors, very dense, wet, with sand (30%), and silt (10%).	DOT-5-2 1220 11-11-92	14/31/70(5) 0.6' rec 0 ppb GC-S 2.5 ppb GC-W
-				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
20-	GM	Silty gravel with sand: Gravel (50%), fine to coarse, subangular to subrounded, grayish brown to dark gray, very dense, wet, with sand (30%), and silt (20%).	DOT-5-3 1245 11-11-92	70(5)/-/- 0.5' rec 0 ppb GC-S 0 ppb GC-W
25 — - -	GM	Silty gravel with sand: Gravel (45%), fine to coarse, subangular to subrounded, grayish brown, very dense, wet, with sand (40%), and fines (15%).	DOT-5-4 1340 11-11-92	18/28/32 1.0'rec 0 ppb GC-S 0 ppb GC-W
30-	GW- GM	Well graded gravel with silt and sand: Gravel (70%), fine to coarse, subrounded, grayish brown, very dense, wet, with sand (20%), and fines (10%).	DOT-5-5 1410 11-11-92	13/26/70(5) 0.7' rec 0 ppb GC-S NA ppb GC-W
35-	GW- GM	Well graded gravel with silt and sand: Gravel (60%), fine to coarse, subrounded, grayish brown, very dense, wet, with sand (30%), and fines (10%).	DOT-5-6 1445 11-11-92	30/70(4)/- 0.5' rec <1 ppb GC-S <1 ppb GC-W
_				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
40-	GW- GM	Well graded gravel with silt and sand: Gravel (70%), fine to coarse, subrounded, grayish brown, very dense, wet, with sand (20%), and fines (10%).	DOT-5-7 1515 11-11-92	13/70(5)/- 0.5′ rec 0 ppb GC-S 0 ppb GC-W
- 45— - -	GW- GM	Well graded gravel with silt and sand: As above.	DOT-5-8 1645 11-11-92	10/70(5)/- 0.5' rec 0 ppb GC-S 2 ppb GC-W
- 50- - -	SM	Silty sand with gravel: Sand (65%), fine to very coarse, moderate brown, medium dense, wet, with gravel (20%), and fines (15%).	DOT-5-9 0815 11-12-92	7/5/13 0.6' rec 0 ppb GC-S 0 ppb GC-W
55 — - - -	SM	Silty sand with gravel: As above.	DOT-5-10 0910 11-12-92	17/70(1)/- 0.8' rec 0 ppb GC-S 0 ppb GC-W
-				

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
60-	ML GW- GM	Gravel and ~0.3' of cemented medium to coarse sand. Silt with sand: Silt (50%), dark yellowish orange, hard, moist to dry, with sand (25%), very fine, and clay (25%). Decreased transmissivity. Silt and cemented sand ~60.5' to 61.5' bgs. Gravel (wet) with sand and fines resume: ~61.5 bgs.	DOT-5-11 0950 12-12-92	8/60/70(1) 1.1' rec 0 ppb GC-S 0 ppb GC-W
65-	SM GW- GM	Silty sand with gravel: Sand (60%), well graded but mostly coarse, dark gray, subrounded, very dense, wet to moist, with fines (25%), and gravel (15%). Gravel with sand and fines.	DOT-5-12 1030 11-12-92	11/27/40 1.0' rec 0 ppb GC-S 0 ppb GC-W
70-	SM	Silty sand with gravel: Sand (70%), well graded but mostly coarse, dark gray, very dense, wet, with fines (15%), and gravel (15%). Increasing gravel in cuttings.	DOT-5-13 1110 11-12-92	70(3)/-/- 0.9' rec 0 ppb GC-S 0 ppb GC-W
75-	SM	Silty sand with gravel: Sand (50%), very fine to medium, grayish black, very dense, moist, with fines (25%), and gravel (25%).	DOT-5-14 1320 11-12-92	18/48/70(3) 1.0' rec 0 ppb GC-S 0 ppb GC-W
_		Increasing gravel in cuttings.		

Depth (feet)	Symbol	Well graded gravel with sand: Gravel (65%), fine to coarse, subrounded to rounded, grayish black, very Number (date/time) DOT-5-15	Sample Number (date/time)	Remarks Total blows/ Recovery 23/70(5)/- 1.1' rec 0 ppb GC-S 0 ppb GC-W
80-	GW		DOT-5-15 1400 11-12-92	
- 85— - -	GW	Well graded gravel with sand: As above.	DOT-5-16 1450 11-12-92	6/18/70 1.3' rec O ppb GC-S O ppb CC-W
90	GW	Well graded gravel with sand: Gravel (80%), fine to coarse, subrounded, grayish black, very dense, wet, with sand (20%), and trace fines.	DOT-5-17 1520 11-12-92	5/18/40 1.0' rec NA ppb GC-S 0 ppb GC-W
- 95 -	GW	Well graded gravel with sand: As above.	DOT-5-18 1615 11-12-92	3/3/80 0.8' rec NA ppb GC-S 0 ppb GC-W
-				

Depth (feet)	Symbol	Symbol Lithological Description		Remarks Total blows/ Recovery
100-	O— GM From cuttings: Well graded gravel with sand.	From cuttings: Well graded gravel with sand.		
-]				
-	CL	From cuttings @ 103': Silty clay with sand and gravel.		
-				
- 105—	,	Driving 10' casing - sampling not possible at 105'.		
-	CL	From cuttings to 110' bgs: Silty clay with progres-		
-		sively decreasing gravel and sand.		
-				
110-	CL			8/18/36
-		(30%), and sand (10%).	1000 11-13-92	1.5' rec 0 ppb GC-S 0 ppb GC-W
-		Total depth: 112 feet below ground surface.		3 222 33 11
-				
-				
115—				
-			,	
-				
-				
-				

Date Completed: 11-17-92

DRILLING AND SAMPLING LOG

Project: Northwest Pipe and Casing
Boring Contractor: Staco Well Services
Boring Method: Downhole Hammer
Logged By: Fowlow

Job No.: EORO201SCA

Location: Clackamas, Oregon

Surface Elevation: ~197 Feet

Casing Elevation: 196.14 Feet

Total Depth: 20 Feet
Groundwater: ~5 Feet

Datum: ONG-1 (200)
Datum: ONG-1
Datum: BGS
Datum: BGS

Boring No.: <u>DOT-6</u>

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0-		DOT-6 was installed within approximately 10 feet of DOT-5. An insignificant geologic variation is assumed and therefore, no samples were collected.		Conc. GC-Soil Conc. GC-Water
-				
5-	₹	From cuttings: Silty, sandy soil 0 - 5' bgs; sandy gravel 5' - 10' bgs.		
-			·	
10-	GW- GM	Well graded gravel with silt and sand: Gravel (60%), fine to coarse, subangular to subrounded, grayish brown, very dense, wet, with sand (30%), and silt (10%).		9/70(5)/- 0.5' rec 0 ppb GC-S 0 ppb GC-W
- - 15-	GW-		·	14/31/70(5) 0.6′ rec
-	GM	Well graded gravel with silt and sand: Gravel (60%), fine to coarse, subrounded, varied colors, very dense, wet, with sand (30%), and silt (10%).		O ppb GC-S 2.5 ppb GC-W
-				

Depth Symb		ool	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
20-		GM	Silty gravel with sand: Gravel (50%), fine to coarse, subangular to subrounded, grayish brown to dark gray, very dense, wet, with sand (30%), and silt (20%).		70(5)/-/- 0.5' rec 0 ppb GC-S 0 ppb GC-W
· -			Total depth: 20 feet below ground surface.		
25-					
- -					
-					
30-					
_ :					
-					
- 35 <i>-</i>					
-					
-					
-		_			

Boring No.: T-1

Datum: NA

Datum: NA

DRILLING AND SAMPLING LOG

Project: Northwest Pipe and Casing Boring Contractor: Staco Well Services Boring Method: Backhoe Logged By: Fowlow Date Completed: 11-18-92

Job No.: EORO201SCA Location: Clackamas, Oregon Surface Elevation: NA

Casing Elevation: NA Total Depth: 6 Feet

Datum: BGS Datum: NA Groundwater: NA

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0-	SM	Silty sand with gravel, brown, dry, roots in top foot.		
-	OL	Moisture seeps. Clayey silt, black, high organic content.	Groundwater sample collected at moisture seep.	,
5-	CL	Gravelly clay, gray, lean.		
-		Total depth: 6 feet below ground surface.		
_				·
10-				
_				
-				
15—				
-				
-				
_				

DRILLING AND SAMPLING LOG

Project: Northwest Pipe and Casing Job No.: EORO201SCA Boring No.: T-2 Boring Contractor: Staco Well Services Location: Clackamas, Oregon Surface Elevation: NA Datum: NA Boring Method: Backhoe Datum: NA Logged By: Fowlow_ Casing Elevation: NA_ Date Completed: 11-18-92 Total Depth: 8.5 Feet Datum: BGS Groundwater: NA Datum: NA

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0-				
_	sw	Well-graded sand with gravel, dry, brown.		
- 1		Moisture seeps: oily, odorous. Buried material: cloth, etc.	Groundwater sample collected	
5-	СН	Fat clay with silt, black to gray, organic, plastic.	at moisture seep.	·
-	GM	Silty gravel with sand, gray, moist.		
. 10-		Total depth: 8.5 feet below ground surface.		
-				
-				
-				
15—				
-				
_				

DRILLING AND SAMPLING LOG

Project: Northwest Pipe and Casing
Boring Contractor: Staco Well Services
Boring Method: Backhoe

Logged By: Fowlow

Date Completed: 11-18-92

Job No.: EORO201SCA
Location: Clackamas, Oregon

Surface Elevation: NA
Casing Elevation: NA
Total Depth: 6.5 Feet

Groundwater: NA

Boring No.: T-3

Datum: NA

Datum: NA

Datum: BGS Datum: NA

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0-				
-	sw	Well-graded sand with gravel, dry, brown.		
-	мн	Elastic silt with sand and clay, moist, plastic.		
-	GW- SW	Well graded gravel and sand, moist, brown.	No sample collected.	
5— -	GW-	Moisture seeps: no odor or sheen. Well graded gravel and sand, moist to wet, gray.		
-	sw			
-		Total depth: 6.5 feet below ground surface.		
-				·
10-				
_ }				
-				
-				
_				
15—				
_				
_				
_				
-				

Date Completed: 11-18-92

DRILLING AND SAMPLING LOG

Project: Northwest Pipe and Casing
Boring Contractor: Staco Well Services
Boring Method: Backhoe
Logged By: Fowlow

__ Surface Elevation: NA ____ Casing Elevation: NA ____

Job No.: EOR0201SCA
Location: Clackamas, Oregon
Surface Elevation: NA

_

Datum: NA Datum: NA

Boring No.: <u>T-4</u>

Total Depth: 8 Feet
Groundwater: NA

Datum: BGS Datum: NA

Depth (feet)	Symbol	Lithological Description	Sample Number (date/time)	Remarks Total blows/ Recovery
0- - - - 5- - 10- - - 15-	ML SM	Lean clay with silt and trace gravel, gray to yellowish gray, moist. Silt with sand and trace clay, unstratified, brown. Large (4 ft. diameter) buried metallic object (crushed drum?). Moisture seep: hydrocarbon sheen and odor. Silty sand with organic clays, brown to black. Large amount of buried debris (plastic, rubber, metal, rags, coal tar, and slag, etc.). Total depth: 8 feet below ground surface.	Groundwater sample collected at moisture seep.	

STATE OF OREGON MONITORING WELL REPORT

Name of supervising Goologies Buginess D. A. HARTLEY

MUNITURING WELL REPURI (as required by ORS 537.765 & OAR 690-240-695)		Sta	rt Card #				
) OWNER/PROJECT: WELL NO. MW-8	(6) L	OCATION	OF WEI	L By lega	l descrip	tion	
N- ENVIRONMENTAL PROTECTION AGENCY		Location: Cou					
NEW 1200 GTH AVE	Tow	nship 2	_N 🖎	Range 2	Br V	•	9
ON SEATTLE SON WA TO		S W1/ treet address of					
(2) TYPE OF WORK:		ATHER.		AND			WAY
New construction. Repair Recondition	3. 1	ax lot member					
Conversion: Deepening Abandonment	4. /	TTACH MAI	WITH LO	CATION ID	ENTIFIED		·
(3) DRILLING METHOD Rotary Mad Cable	8.	TATIC WA <u>OY</u> P. be Artesian Pressu	low lend sur	face.	Date !!	17/12	<u>-</u>
(4) BORE HOLE CONSTRUCTION	J					•	<u> </u>
Yes No Depth of completed well 72 A.		WATER BE Depth at which			7 '		
U Interior		From	То	Est. Flo	w Rate	S	WL
Ventt A		7'	100	15 G	PM	8	<u>, </u>
Locky A PT Warming							
2 y 2 Concerto de							
Locking cap							
Casing Clarester 4 Jr.		WELL LO	G:	Ground elevi	ttion		
material STAINLES	<u>. </u>	Mate	riel		From	To	SV
Welded Threaded Gluec	1	SILTY S	AND		0	8	+
		WELL GI		RAVEL	8	25	 ~ ;
Seal Liner diameter MA in material		^		w/sano	25	7.3	
		511.74	SAND	MO SHO	73	75	+-
70 - Welded Threaded Glue	4	wen Ge		1 1/5000	75	78	+
61 n.		SEMILITI			78	80	+-
Well seal: Material Public (nout)	· ·	SILTY GR			80	85	+
Amount 12.50 LBS		WELL G		_	85	95	
NI DEATED- / O. 2 LB / FT Borehole dismeter	> .				95	100	+
Sovenide districted		SILTY G	KANGE W	JAND	75_	100	
		<u></u>		-1 /		+	+-
Bentonite plug at least 2 f	t. thick	1.0TA	L DEP	TH - 100			
						 	+-
Filter Screen Screen material 57 Annue 35	51061-						
interval(s):		i	·		 -		+-
From 12 To 66	<u>-</u>				 -		\dashv
73 ft Slot size 10 540T		<u> </u>				+	+
Filter pack:		- · · ·					_
Material Color 400	_	L	1/10	_	<u> </u>	12/2/	<u> </u>
Simim Sillic		Date started_	1927/4	<u> </u>	Completed_	10/30/	72
(E) THELL TESTA	(u	nbonded) Mons					
(5) WELL TEST: Pump	at	I certify that the candonsment of the	-				
		endards. Materi		information r	eported abo	ve are true to	the bes
Permeability Yield 15 GPM Conductivity 400 u.S PH 7.65	F	nowledge and b	cia.		1	MWC Numb	er .
Temperature of water 13.5 %C Depth artesian flow found	Si	grai				Date	
Was water analysis done? X Yes No	(b	onded) Monitor	Well Coasts	uctor Certific	ntion:		
By WHOMP COMMORCIAL LAB FOR EPA	·	I accept respon					
Dopth of strate to be enalysed. Proce 60 ft. to 72		ork performed o ork performed o					
Remarks:		mission. This s					

STATE OF OREGON MONITORING WELL REPORT

(a required by ORS 201165 & OAL BOTH 1999)		St	art Card #				
OWNER/PROJECT: WELL NO. MW-9	(6) L	OCATIO	OF WE	LL By legs	ıl descrip	tion	
N- ENVIRONMENTAL PROTECTION AGENCY	_ 1	Location: Co			_		
Man 1800 GTH AVE						W) Section	
ON SEATTLE SHE WA TO	15	5 W	1/4 of	92.00	sse evode که دری همک	NFIELD	>
(2) TYPE OF WORK:	<u> </u>						
New construction. Repair Recondition Conversion: Deepening Abandonment.		ux lot momber					
(3) DRILLING METHOD		TTACH MA			ENTURED	<u>. </u>	
Rotary Air Rotary Mad Cable		TATIC W •89 R. E			D 1/	19-92	
Hollow Stem Anger Other	Ā	rtesian Press	arelb	/sq. in.	Date	19-92	
(4) BORE HOLE CONSTRUCTION					ı,	,	
Pecial Standards Depth of completed well 8 P		VATER B			5 /		
Depth of completed well DP ft.	, , , , , , , , , , , , , , , , , , ,	epth at which	To		w Rate	72	WL.
Land surface		51	90'		GPM		891
Vault Water-tight cover	ŀ		170		G, PIVI	- 4.4	27_
TO - Surface flush vanit	-		 				
Locking cap	ŀ						-
Casing	(A) -		<u> </u>	<u> </u>			
diameter 4	n_	WELL LO	G:	Ground elev	100h		_
material STEAL ST		Mate			From	То	WE
	<u> </u>	WELL GRAD		1	0	15	12
Scal Liner	_		RADED (,	15	20	┼
A. diameter	in.		/ SANI		20	25	┼
Welded Threaded Glu	ed e	Well G	RADED (25	30	+
25 A	J }		-	W/Sand	30	45	+
Well scal; Material (VR5 GoL	_ [PADED G		4 5 5 5	55	+-
Amount 12 50 LBs	HORATED	WELL GRI	SAND W/		60	65	+
TO 10. 2 LB/pT-	3		W/SILT		65	70	+-
			RADED		70	90	+
			OILT - ME		90	92	1
Bentonite plug at least 2	i it. unck	1	<u> </u>		<u> </u>		
Filter Screen							
pack Pinkless	Siser	TOTAL	DEPTH	· -92	FOOT		
78 ft. From 80 To 8	5				<u> </u>		
From					ļ <u>-</u>		
Slot size // 3/6/		ļ			 		+
Material (augh 100)			1-1-1	0.5	<u> </u>	1	
Sizein. 5	40D	Date started_	101311	92_0	Completed_	11/04/9	12
(5) WELL TEST:	=	bonded) Moni				e, alteration, o	or .
Pump Bailer M Air Flowing Artesian	aba	ndonment of t	his well is in	compliance w	rich Oregon	well construct	tion
Permeability Yield 50 GPM		idards. Mater owledge and t		information r	eported abo	ve are true to (the best
Conductivity 350 MS PH 7-87		•				MWC Numbe	#
Temperature of water 13.9 WC Depth artesian flow found	n. Sign					Duto	
Was water analysis done? Yes No By whom? Whom FR CLAL LAB FOR EPA	•	nded) Monito Laccept respo				ı, or abanılmı	BONE P
Depth of strata to be analyzed. Prose	A. WOL	rk performed	on this well d	wing the cons	traction des	ne superiori ab	DVE. A
Remarks:						Oragon well or Age and belief.	
Dy Lagary	- .				1	MWC Number	
Name of supervising Goodsgiad Engineer D. A. HARTLEY	Sig					Dans	

STATE OF OREGON MONITORING WELL REPORT (as required by ORS \$37.765 & OAR 600-240-695)

(23 17	equired by ORS 537.765 & C	AR 694-248-695)			Sta	art Card #			-	
	OWNER/PROJECT:	WELL	NO. MW-10	(6) I	OCATION	OF WE	L By legs	descript	ion	
N	ENVIRONMENTAL	·	ON AGENCY		Location: Cou	_		-		
Adda	1200 GTH	AUE		Tow	matrip Z	N 630	Range Z	- B		
OR.	SEATTLE	sun WA		1	Street address of	4 d _ <u>\$</u>	<u>= 1/4 (</u>	of above sent		_
(2)	TYPE OF WORK:			2.5	itreet address of	well locatio	- 7.600	5 LAGO	<u> </u>	<u></u>
	New construction	Repair	Recondition	3. 7	Tax lot member (of well locati	on			
	Conversions	Decreasing	Abandonment	4. /	ATTACH MAI	WITH LO	CATION ID	entipied.		
(3)	DRILLING METHO	D_			STATIC W				_	
	Rotary Air Hollow Stem Auger	☐ Rotary Mad	Cable		<u>1.79 </u>		face. /sq. in.	Date 11-	19-92	
(<u>4</u>)	BORE HOLE CONS			<u> </u>	7,44,51,11,14,14					
(*)	Yes No		2 —		WATER BE			_ '		
	point Standards	Depth of comple	sted well 35n.	1	Depth at which			<u> </u>		
V	P		Land surface		From	To	Est. Flo	w Rate		ML_
	Vault	- 8	<u>'</u>		5	35				<u>. </u>
-	<u>O</u> ft]		Water-tight cover							
1-	70 - 1		Surface flush vault			ļ				
1	11. (B		Locking cap				<u> </u>			
		<i>11111</i>	Casing		WELL LO	G:	Ground elev	etion		_
			diameterin_ material <u>57 AIA (465) 5</u>		Mate	nel		From	To	SW
			Welded Threaded Glued	i	WELL GRAD	en Gul	SILT HO	0	15	12
					WELL GIR	ADED	GUL	15	20	1
	Scal 3		Linerin.	•		Y SA		20	25	1
	<u> </u>		material		WELL G			25	30	\top
	_ro ≺ ***********************************		Welded Threaded Glues	1	"	•	W/540	30	35	1
	22 n.		Weil seal:				7			
			Material PURE GOLD		TOTAL	DEPT	4 - 35	FEET		1
	- C		Amount 700 LB HYDR							
			Borehole diameter							
4			Bentonite plug at least 2 ft	t. thick						
•										
•	Filter		Screen							
•	pack 20		material STAINLESS ST	is r						
	A R		From 29 To 34	<u>_</u>		• .		<u> </u>		
	₹ ₩ \		From To Slot size /D **** T		<u> </u>			 		
	35 A ()		Filter pack:					 	+	-
			Material COLORADA SIL	LEA			_	<u> </u>		
			Sizein. 5/	ONP	Date started_	04 NOV	42_	Completed	06 40V	42
-) WELL TEST:			(u	nbonded) Moni					
(3	Pump B	ailer 🔼 A	ir Flowing Artesian	at	I certify that the certify that the certify that the certify that the certified in the cert	•				
		Yield	2 _		andards. Materi		information :	eported above	e are true to	the best
	Permeability 400	5 PH	B.OD GPM	k	d bna egboiwon	diet.			AWC Numbe	a
	Temperature of water	5 C Dept	artesian flow found	. Si	igned)ote	
	Was water analysis done?	Yes No	- •	(t	onded) Monito					
	By whom? OWM FY			_	i accept responsive ork performed o	•		•	_	MARIA.
	Depth of strate to be easily Remarks:	THE PROOF _ A. /_		L #	ork performed	Acring this tis	ne is in comp	iinnes with C	description of	
				e ' et	anderde. This r	opost is true	to the best of		AMC Massler AMC Massler	
	Name of supervising God	logis@igison- D	. A. HARTLEY		igand:			_)	

STATE OF OREGON MONITORING WELL REPORT

Manne of supervising Geologies Engineer D. A. HARTLEY

(as requires by OES 537.765 & OAR 699-249-973)	Start Card #
) OWNER/PROJECT: WELL NO. MW-//	(6) LOCATION OF WELL By legal description
HE ENVIRONMENTAL PROTECTION AGENCY	Well Location: County CLACK AMAS
NEW 1200 GTH AUE	Township 2 (N of Trange 2 (B) or W) Section 4
ON SEATTLE IN WA TO	1. <u>SE 1/4 of SE 1/4 of above section.</u>
(2) TYPE OF WORK:	2. Street address of well location LAWNFIELD NW DEVELOPMENT CO. PARKING LO
New construction Repair Recondition	3. Tax lot number of well location
Conversion: Deepening Abundonment	4. ATTACH MAP WITH LOCATION IDENTIFIED.
(3) DRILLING METHOD	
Rotary Air Rotary Mod Cable	(7) STATIC WATER LEVEL: 3.44 P. below land surface. Date 11-19-92
Hollow Stem Anger Other	Artesian Pressure fb/sq. in. Date
(4) BORE HOLE CONSTRUCTION	,
Van Va	(8) WATER BEARING ZONES:
Depth of completed welf 4.5 A.	Depth at which water was first found 5
Land surface	From To Est. Flow Rate SWL
Venit 3	5' 73 50 GPM 3.5'
On Mater-tight cover	
TO - Surface flush vanit	
fit. Locking cap	
Caring	(0) TIPLE 1.00: Complete size
diameterin_	(9) WELL LOG: Ground elevation
material STAINLESS	
Welded Threaded Glued	WELL GRADED GUL WISHT 0 30 ~3
	WELL GRADED GRAVEL 30 35
De Callette de la dispressa de la companya de la co	
n material	(100) (200) (10)
Welded Threaded Gluer	SILTY SAND WICLAY 68 73
So ft. Well seal:	CLAYEY SILT W/ SAND 73 76
Material RVL5 Group	CONTRACTOR TO TO
Amount 1100 LB HYDR	
TO 10. Z LB/FT &	TOTAL DATA TO ALST
Dorestone distriction	
Bemonite plug at least 2 ft	L thick
Filter Screen material MAIN LESS Sin	521
interval(a):	
58 ft. From 60.5 To 65.	5
FromTo	
Gle. S. Filter pack:	
Material CALPRADO S	yea
Simin. 54,	JD Date started 06 NOV 92 Completed 08 NOV 92
- CHARLES - CHAR	(unbonded) Monitor Well Constructor Certification:
(5) WELL TEST:	I certify that the work I performed on the construction, alteration, or
Pump Bailer Air Flowing Artesian	abandoment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to the bea
Permeability Yield 50 GPM	knowledge and belief.
Conductivity 250 µS PH 7-70	MWC Number Signed Date
Temperature of water 14 - 6 SPC Depth attestion flow found	
Was water analysis done? X Yes No	(bonded) Monitor Well Constructor Certification: I accept responsibility for the construction, shoration, or abandonment:
By whom? COM MA FIRCIAL LAB FOR EPA Depth of strata to be analyzed. Proce. 58 ft. to 64.5 ft	work performed on this well during the construction dates reported above.
Remarks:	work performed during this time is in compliance with Oregon well constru
	standards. This report is true to the best of my knowledge and belief. MWC Number:

STATE OF OREGON MONITORING WELL REPORT (as required by ORS 537.765 & OAR 690-240-95)

(as required by ORS 537.765 & OAR 690-240-495)		St	ert Card #			_	
OWNER/PROJECT: WELL NO. MW-12	(6)	LOCATION	OF WE	LL By leg	al descript	ion	
N- ENVIRONMENTAL PROTECTION AGENCY		l Location: Cor					
MAN 1200 GIH AUF		rnship 2	N or S	Range a	BW) Section	4
SGAMUS SIN WA TO		SE 1	4 of _50	=1/4	of above secti	OR.	
(2) TYPE OF WORK:	7 2.5	PARKIN	well location	= <u> </u>	WNFIE	20	77.
New construction. Repair Recondition	3. 3	Tax lot number				UF M G = 1	<u></u>
Conversion: Deepening Abandonment		ATTACH MA			ENTIFIED.		
(3) DRILLING METHOD	(7)	STATIC W	ATEDII	rvei.			
Rotary Air Rotary Mad Cable		3.70 P. b			Date 11-	19-92	_
Hollow Stem Asger Other		Artesian Pressu	re	√sq. in.	Date		
(4) BORE HOLE CONSTRUCTION					<u> </u>	•	
Yes No A pecial Standards Depth of completed well 39		WATER BI			< ¹		
Depth of completed well 31 h.	·	Depth at which From	To		ow Rate	1 62	WL.
Land surface							
Vault D. ft. Water-tight cover		5'	40	15	GPM	~	7
		ļ	 	 			
					· -· <u></u> -,		
Locking cap		L	<u> </u>	<u> </u>			
Casing	(9)	WELL LO	G:	Ground elev	ration		_
diameterin material 5 TAINLESS	S165L	Mate	rial	-	From	То	SV
Welded Threaded Glue		WELL GRA		/5AND+	0	30	+-
]				30	35	 ~ :
Seal Liner diameter in	n.	MELL G	*	. 4	35	40	+
At. dimeter material	····			" w/54m2	93	140	+-
Welded Threeded Glue	ed.					 	+-
21 ft. Welded I hreeded Glice	j			.=		 	+
Well seal: Material PURG Group	LD				 	 	+
Amount 600 LB HYDE		}			·	 	+
TO 10.2 LB1 F	73	-			<u> </u>	 	+
Borehole diameter					 	 	┼─
		Toma	7-	(10		 	+
Bentonite plug at least 2	ft. thick	TOTAL	DEPT	H - 40	FEET	 	┼
		 				 	┼
Filter pack Screen STAINLESS	SteeL				 	 	+
mterval(s):	-			<u> </u>	 	 	+
From 33 To 38	>_				 	╅━━━	+
39 R. Slot size 10 SLOT	-in.				 	 	+
Filter pack:					 	 	+-
Material O SIGICA	SAND	<u> </u>	-0	.02			
		Date started_	OT NOI	770	Completed_/	O NOV	74
(5) WELL TEST:	(u	nbonded) Monit				- h	
Pump Bailer Air Flowing Artesian	ab	I certify that the randomment of t	•				
Permeability Yield 15 GPM		endards. Materi		information	reported above	e are true to	the best
Conductivity 270 MS PH 7-60	, 18	nowledge and b	a xa.		м	WC Numbe	z_
Temperature of water 15,1 C Depth atterian flow found	Si	gnosi		 -		uec	
Was water analysis done? Yes No	(Ь	onded) Monitor					
By whom? OMM SECIAL LAB FOR EPA Dopth of streta to be enalyzed. Prost: 31 ft. to 39		l accept respon ork performed o	•		•		
Remarks:)L W	ork performed d	tering this tis	ne is in comp	Hence with O	region well o	onstruc
	- #1 -	endards. This re	port is trus	to the best of		p and belief. IWC Numbe	
Name of supervising Geological Regimes D. A. HARTLE 7	Si	gand			_	WC MEBOS	<u>'—</u>

STATE OF OREGON MONITORING WELL REPORT (se remired by ORS 57.765 & OAR 699.249-495)

(so required by ORS 537.765 & OAR 690-240-695)		Start Card #				
OWNER/PROJECT: WELL NO. DOT - 5	(6) LOCATION	ON OF WEI	LL By legs	ıl descript	ion	
N- OREGON DEPT OF TRANSPORTATION	Well Locations: County CLACKAMAS					
MAN 9200 LAWN FIELD	Township 2	N ac	Range Z			9
CLALKAMAS SE OR TO	1. NW			of above secti	Off.	
(2) TYPE OF WORK:	2. Street addres	AME A		R		
New construction. Repair Recondition	3. Tax lot mami	er of well locat	OR			
Conversion: Decpaning Abandonment	4. ATTACH N	LAP WITH LO	CATION ID	ENTIFIED.		·
(3) DRILLING METHOD Rotary Air Rotary Mind Cable Rollow Stern Auger Other		WATER LE	face.	Date//-	19-92	
(4) BORE HOLE CONSTRUCTION			<u> </u>		,	
Yes No Depth of completed well	(8) WATER Depth at who	BEARING		s'		
Land surface	From	То	Est. Flo	w Rate	SW	<i>r</i> L
Vault 3	5'	110	200	aPM	6	
O ft. Water-tight cover						
5urface flush vau			<u> </u>			
Locking cap						
Casing diameter 4	(9) WELL I	.OG:	Ground elev	ation		_
material STAIA		laterial		From	To	SV
Welded Threade	Glued	SHOY S	211	0	5	
Scal Liner		Y GRAI		5	10	26
diameter		EADED GUL		10	20	Ţ
Walded Theret	Gurd Sylty	GRAVEL	W/SAND	20	30	
	Uma G	RADED GUL	W SILTO	30	50	
Weit seal:	SILTY	SAND W/	PAVEL	50	61	
Material PURS		w/ 'S	and_	61	6a	↓
Amount <u>10 · Z L</u>	SULTY	SAND W/6	RAVEL	62	80	
Borehole diamete	WELL	SRADED GV	4 w/54no	80	103	↓
	SILTY 6	LAY w/ San	DIGUL	103	110	↓
Bentonite plug =	east 2 ft. thick	N CLA	7	110	112	-
	<u> </u>		· ···	 	 	
Filter Screen STA	LESS =	4. 5		<u> </u>		+
az interval(a):		AL DEF	7H -	112 F	EST	+
	100		-	 	 	+
LOL R. Slot size 10 50	27 id.			1	+	+
Filter pack:				 	+	+-
Material (1) A	ICANAND	· II vail (17		lla stast	<u> </u>
Sizein		M 11 NOV C		Completed	WNA	AL
(5) WELL TEST:		lonitor Well Cor nat the work I per			e elteration, o	OMF
Pump Bailer Air Flowing A	esian abandonment	of this well is in	compliance v	with Oregon v	reil construct	tion
Permeability Yield & D GPM	standards. M. knowledge s	sterials used and ad belief.	information	reported above	e are true to t	the bes
Conductivity 420 ALS PH 6-50					AWC Number	*
Temperature of water 14-0 PC Depth artesian flow found	n. Signed)etc	
Was water analysis done? XYes No	•	nitor Well Const				
By whom? ONLINE ERCLAL AB FOR EPA Depth of stress so be easilysed: Proce 93 ft. so 101	•	ed on this well (•		
Remarks:	work parform	ed during this ti	me is in comp	diance with C	yelen aeş e	
	——————————————————————————————————————	uis report is trus	च्च कड क्ला of	•	ge and belief. 4WC Numbe	

STATE OF OREGON MONITORING WELL REPORT (se required by ORS \$37.765 & OAR 690-240-995)

		Sun Care	'			
OWNER/PROJECT: WELL NO. DOT - 6	(6) LOCA	TION OF WE	LL By legs	d descript	ion	
N= OREGON DEPT OF TRANSPORTATION	1	e: County		_		
ME 9200 LAWNFIELD		2 No(5				9
ON CLAURAMAS SO OR TO	1. NW	1/4 ofN	E1/4 o	d above sect	ion.	
(2) TYPE OF WORK:	2. Street add	tress of well locati	ion	O. 11 F0	,	
New construction. Repair Recondition	3. Tax lot m	omber of well loca		-		
Conversion: Deepening Abundonment	4. ATTAC	H MAP WITH L	DCATION ID	ENTIFIED.		
(3) DRILLING METHOD	(7) STATI	C WATER L	EVEL.			
Rotary Air Rotary Med Cable		_R. below land s		Date 11	-19-93	2_
Hollow Stem Auger Other	Artesian	Pressure	b∕sq. m .	Date	<u> </u>	
(4) BORE HOLE CONSTRUCTION			- "		•	
A recial Standards Yes No. Depth of completed well 20 ft.		R BEARING		<u>_</u> 1		
Depth of completed well AU ft.	From	which water was t	Est. Flo	<u> </u>	SW	
Land surface	-					
Vault Oft. Water-tight cover	5	20	1-3	GPM	~ 5	
Surface State						
]		<u> </u>			
Locking cap			<u></u>			
Casing diameter 4 in	(9) WELI	L LOG:	Ground eleve	ntion	<u> </u>	-
diameter in material 51 An NL 65		Material	<u> </u>	From	To	SW
Welded Threaded Glue		TY SAND	, <	δ	5	-
		DANDY GR		5	10	ی-
Scal Liner diameter in		GRANED GUL		10	20	
ft		CIK HORD GAL	- W/ 4 AND	10	120	
TO Welded Threaded Glue		4. 2	20.00		 	-
	1 101	AL DEPTH	-20 566	<u> </u>	 	├
Well seal:	 	 ·				├─
Amount					 	\vdash
Borchole diameter						\vdash
10 in.					\ 	
					 	├─
Bentonite plug at least 2 f	t.thick ——					
Screen		 -			 	├─
Filter pack material STAINLE	35					
interval(s):	-				 	
From 19 To 19 From - To -	-			-		┼──
Slot size 10 supt					 	
Filter pack:						
Material CO SILICAS	4ND L	17 11	v C2	<u> </u>		<u> </u>
Sizein.	Date st	17 NO	<u> </u>	Completed	18 NOV	9 0
(5) WELL TEST:) Monitor Well Co that the work I pe				_
Pump Bailer Air Flowing Artesian	_	ant of this well is i				
Permeability Yield /-3 GPM		Materials used an	d information n	eported abov	e are true to ti	ne bent
Conductivity 150 MS PH 7-40	Tuowied	and belief.		N	(WC Number	
Temperature of water 15.0 MC Depth atterian flow found	Signed			0)etc	
Was water analysis done? Yes No		fanitor Well Cons				
By whom? LOWINGECIAL LAR FOR EPA	•	responsibility for remed on this well		-		
Depth of strata to be analyzed. From: 11 A. to 20	work perfe	count during this t	ime is in compl	ience with C	impos well co	
	standerds.	This report is true	s to the best of s		re and belief. FWC Number	
Name of supervising Geologist Engineer D.A. HARTLEY	Signed				WC Manager	

APPENDIX C

FIELD SCREENING

TECHNICAL ASSISTANCE TEAM FASP AND COMMERCIAL LABORATORY RESULTS COMPARISON FOR:

NORTHWEST PIPE AND CASING CLACKAMAS, OREGON

TDD T10-9210-031

REPORT PREPARED BY: ECOLOGY AND ENVIRONMENT, INC.
PROJECT CHEMISTS: MICHAEL SZERLOG, MARK WOODKE
DATE: MARCH 1993
SUBMITTED TO CHRIS D. FIELD, DEPUTY PROJECT OFFICER
and JOHN SAINSBURY, ON-SCENE COORDINATOR
SUPERFUND RESPONSE AND INVESTIGATIONS BRANCH
U.S. ENVIRONMENTAL PROTECTION AGENCY
REGION X
SEATTLE, WASHINGTON

TABLE OF CONTENTS

Sect	<u>ion</u>	Page
1.0	INTRODUCTION	1
2.0	FASP METHODOLOGY FOR VOLATILE ORGANIC COMPOUNDS IN SOIL/SEDIMENT BY PURGE AND TRAP	1
	2.1 Summary of Modified Fasp Method	1
3.0	FASP SAMPLE ANALYSES DATA	1
4.0	STATISTICAL ANALYSIS OF FASP RESULTS	4
5.0	FASP CALIBRATION DATA	5
	5.1 Initial Calibration	5
	5.2 Continuation Calibration	5
6.0	METHOD BLANK DATA	9
7.0	MATRIX SPIKE DATA	9
8.0	DUPLICATE SAMPLE DATA	9
9.0	INSTRUMENT OPERATING PARAMETERS	9
10.0	CONCLUSTON	12

LIST OF TABLES

TABL	<u>B</u>	PAGE
1	Summary of Analytical Results for Groundwater Samples	2
2	Summary of Analytical Results for Subsurface Soil Samples	3
3	Summary of Calibration Results for Fasp Analysis	6
4	Summary of Method Blank Results for Fasp Analysis	10
5	Summary of Duplicate Sample Results for Groundwater Samples	11
APPE	NDIX A SAMPLE CHROMATOGRAMS	

1.0 INTRODUCTION

As an integral part of the Site Assessment for Northwest Pipe and Casing, Clackamas, Oregon, groundwater and subsurface soil samples were analyzed by Ecology and Environment, Inc. (E & E) Technical Assistance Team (TAT) chemists utilizing Region 10 Field Analytical Support Project (FASP) methodologies. The samples were collected during the installation of 7 groundwater monitoring wells located on the perimeter of the site. A total of 52 subsurface soil samples and 68 groundwater samples were collected and analyzed for trichloroethene (TCE) and tetrachloroethene, also known as perchloroethylene (PERC), using a field portable Sentex Systems Scentograph gas chromatograph (GC) with an argon ionization detector coupled with a purge and trap unit. A total of 4 subsurface soil and 11 groundwater samples were submitted to a commercial laboratory. FASP analysis provided tentative identification and estimated concentrations of target analytes. Commercial laboratory confirmatory analysis provided positive identification of target analytes that were previously tentatively identified by FASP methodologies.

2.0 FASP METHODOLOGY FOR VOLATILE ORGANIC COMPOUNDS IN SOIL/SEDIMENT BY PURGE AND TRAP

The FASP method F080.001 was modified to adapt to the Sentex Systems Scentograph portable GC operating parameters. All FASP method quality control criteria were met for initial calibration, continuing calibration, final calibration, and quantitation limits. The target compounds analyzed for were TCE and PERC during the field analytical project.

2.1 Summary of Modified FASP Method

Five grams of soil/sediment, weighed to the nearest 0.01 gram, are placed into a volatile organic analysis (VOA) vial with 30 mls of deionized water. The sample was shaken for 1 minute and then transferred to the Teflon purge cup. The sample was then purged with argon to extract TCE and PERC onto a Tenax trap, or equivalent. The trapped sample is then desorbed with heat and moved along with the argon gas directly onto a packed glass column in a temperature-programmed GC. TCE and PERC were detected with an argon ionization detector. Quantitation and identification were based on sample peak areas and retention times compared to the calibration peak areas and retention times.

3.0 FASP SAMPLE ANALYSES DATA

Generally, there was a very good agreement of TCE and PERC results for the fifteen split groundwater and soil samples analyzed by TAT using FASP methodologies and the commercial laboratory using United States—Environmental Protection Agency (EPA) Method 8240 for volatile organic compounds (VOC) (Table 1 & Table 2). The TAT and commercial laboratories were consistent in the identification of results above and at the given detection limits for all samples analyzed.

TABLE 1
SUMMARY OF ANALYTICAL RESULTS
FOR GROUNDWATER SAMPLES
NORTHWEST PIPE AND CASING SITE ASSESSMENT
CLACKAMAS, OREGON
(µg/L)

Sample	Well	Analyte	Commercial Lab	TAT Lab	`
T2100121	MW-2	TCE	42.0	493.5	F
		PERC	33.0	22.7	F
T2100122	MW-4	TCE	1100.0	2188.0	F
		PERC	6200.0	2107.0	F
T2100123	MW-6	TCE	42.0	391.3	F
		PERC	5.8	17.1	F
T2100110	8-WM	TCE	10 ປ	5	UF
		PERC	10 U	5	UF
T2100111	MW-9	TCE	10 ປ	5	UF
•		PERC	10 U	5	UF
T2100112	MW-10	TCE	10 ប	5	UF
		PERC	10 U	5	UF
T2100113	MV-11	TCE	10 U	5	UF
		PERC	10 ປ	5	UF
T2100114	MV-12	TCE	10 U	5	UF
		PERC	10 U	5	UF
T2100115	DOT-5	TCE	10 U	5	UF
		PERC	10 บ	5	UF
T2100116	DOT-5 *	TCE	10 U	5	UF
		PERC	10 U	5	UF
T2100117	DOT-6	TCE	3.0 J	2.7	F
		PERC	10 U	5	UF

^{*-} Duplicate of sample T2100115.

- J- The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

DOT- Department of Transportation

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

TABLE 2 SUMMARY OF ANALYTICAL RESULTS FOR SUBSURFACE SOIL SAMPLES NORTHWEST PIPE AND CASING SITE ASSESSMENT CLACKAMAS, OREGON (µg/L)

Sample	Well	Analyte	Commercia	l Lab	TAT	Lab
T2100100	8-WM	TCE	200	U	10	UF
•		PERC	200	ប	10	UF
T2100101	MV-9	TCE	300	บ	10	UF
		PERC	300	U	10	UF
T2100102	MW-11	TCE	300	U	10	UF
		PERC	300	U	10	UF
T2100103	DOT-5	TCE	300	U	10	UF
		PERC	300	U	10	UF

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

DOT- Department of Transportation

- F- The data has been generated by the Technical Assistance Team using FASP methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.
- U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

FASP results were not confirmed by mass spectroscopy and, therefore, do not provide the same level of qualitative specificity as commercial or Contract Laboratory Program (CLP) data. While FASP data is not equivalent to or a replacement for commercial or CLP data, the results presented in this report correlate well between the two methods. The data generated by the TAT field laboratory for the Northwest Pipe and Casing Site Assessment were used to quantitate the extent of site contamination and to assist in the location of various monitoring wells.

4.0 STATISTICAL ANALYSIS OF FASP RESULTS

A statistical analysis was performed on the two sets of data using correlation coefficients. The correlation coefficient is defined by the equation below, and can be used to determine the correlation between two methods.

r=
$$\frac{i=1 (x_i - x)(y_i - y)}{n \frac{nS_xS_y}{}}$$

Where:

r = Correlation coefficient,

n = Number of data pairs,

x = TAT laboratory data point,

Y = Commercial laboratory data point,

 S_x = Standard deviation of x, and S_y = Standard deviation of y.

A correlation coefficient of 1.0 represents exact correlation. TAT and commercial laboratory data sets were compared for both analytes using eleven data pairs, including results above and at the method quantitation limits. A value of zero was used when calculating correlation coefficients for results below detection limits. The calculated correlation coefficients for groundwater sample results for Northwest Pipe and Casing are summarized below. Since only four soil samples were analyzed and the results were determined to be at the method detection limits, correlation coefficients were not calculated.

Analyte	Data Pairs Used	Correlation Coefficient (r)
Trichloroethene (water)	11	0.97489
Tetrachloroethene (wate	r) 11	0.99996

Based on commercial laboratory results and calculated correlation coefficients, TAT data for groundwater samples is acceptable for use in field screening applications to establish tentative identification and estimated quantities of target compounds for the Northwest Pipe and Casing Site Assessment.

5.0 FASP CALIBRATION DATA

5.1 Initial Calibration

A minimum of three concentrations of mixtures of TCE/PERC were used for the initial calibration. Concentrations of 50 ppb, 500 ppb and 1000 ppb TCE/PERC were used for initial calibration at the Northwest Pipe and Casing monitoring well drilling operation. Calibration factors (CF) were calculated based upon the total volume of sample, 30 milliliters, used in the purge and trap apparatus.

Using the calibration factors, the percent relative standard deviation (%RSD) was calculated for each peak (Table 3).

$$% XRSD = \frac{SD}{X} \times 100$$

where SD, the Standard Deviation, is given by

$$\frac{\left(X_{i}-X\right)^{2}}{N-1}$$

1=

where: X_i = individual calibration factor (per analyte) X^i = mean of initial three calibration factors N = number of calibration standards

The %RSD must be \leq 25.0 percent or the instrument needs to be re-calibrated with a complete initial calibration.

5.2 Continuation Calibration

The sample quantitation was based on analyte calibration factors calculated from continuing calibrations daily. Midrange standards, 500 ppb TCE/PERC, were analyzed at varied intervals during the analysis run or at the end of the day. Sample chromatograms from runs performed during the sampling event are presented in Appendix A.

The maximum allowable relative percent difference (RPD) calculated using the equation below for each analyte must be \leq 25 percent or an initial calibration must be rerun before analysis can continue.

$$RPD = \frac{|CF_{I} - CF_{C}|}{CF_{I} + CF_{C}} \times 100$$

TABLE 3
SUMMARY OF CALIBRATION RESULTS
FOR FASP ANALYSIS
NORTHWEST PIPE AND CASING SITE ASSESSMENT
CLACKAMAS, OREGON

INITIAL CALIBRATION: (50 ppb TCE/PERC) 10/27/92	Date	Retention Time (seconds)	Analytes	Peak Areas	% RSD
10/27/92 104 TCE 216633 15.8 17.5 (500 ppb TCE/PERC) 10/27/92 104 TCE 2481163 15.8 125 PERC 1198411 17.5 (1000 ppb TCE/PERC) 10/27/92 104 TCE 5926615 15.8 124 PERC 3421709 17.5 CONTINUING CALIBRATION: X RPD (500 ppb TCE/PERC) 10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA	INITIAL CALIB	RATION:			
10/27/92 104 TCE 216633 15.8 17.5 (500 ppb TCE/PERC) 10/27/92 104 TCE 2481163 15.8 125 PERC 1198411 17.5 (1000 ppb TCE/PERC) 10/27/92 104 TCE 5926615 15.8 124 PERC 3421709 17.5 CONTINUING CALIBRATION: X RPD (500 ppb TCE/PERC) 10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA	(50 ppb TCE/P	PERC)			
(500 ppb TCE/PERC) 10/27/92 104 TCE 2481163 15.8 125 PERC 1198411 17.5 (1000 ppb TCE/PERC) 10/27/92 104 TCE 5926615 15.8 124 PERC 3421709 17.5 CONTINUING CALIBRATION: X RPD (500 ppb TCE/PERC) 10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA			TCE		
10/27/92 104 TCE 2481163 15.8 125 PERC 1198411 17.5 (1000 ppb TCE/PERC) 10/27/92 104 TCE 5926615 15.8 124 PERC 3421709 17.5 CONTINUING CALIBRATION: % RPD (500 ppb TCE/PERC) 10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA		124	PERC	150536	17.5
10/27/92 104 TCE 2481163 15.8 125 PERC 1198411 17.5 (1000 ppb TCE/PERC) 10/27/92 104 TCE 5926615 15.8 124 PERC 3421709 17.5 CONTINUING CALIBRATION:	(500 ppb TCE/	PERC)			
(1000 ppb TCE/PERC) 10/27/92 104 TCE 5926615 15.8 124 PERC 3421709 17.5 CONTINUING CALIBRATION: % RPD (500 ppb TCE/PERC) 10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA			TCE	2481163	15.8
10/27/92 104 TCE 5926615 15.8 124 PERC 3421709 17.5 CONTINUING CALIBRATION: % RPD (500 ppb TCE/PERC) 10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA		125	PERC	1198411	17.5
10/27/92 104 TCE 5926615 15.8 124 PERC 3421709 17.5 CONTINUING CALIBRATION: % RPD (500 ppb TCE/PERC) 10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA	(1000 ppb TCF	Z/PERC)			
CONTINUING CALIBRATION: (500 ppb TCE/PERC) 10/27/92			TCE	5926615	15.8
(500 ppb TCE/PERC) 10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA		124	PERC	3421709	17.5
10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA	CONTINUING CA	ALIBRATION:			% RPD
10/27/92 105 TCE 2167151 13.5 126 PERC 1102559 8.3 10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA	(500 ppb TCE/	PERC)			
10/28/92 117 TCE 2763783 10.8 140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA			TCE	2167151	13.5
140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA		126	PERC	1102559	8.3
140 PERC 1319753 9.6 11/02/92* 109 TCE 856221 NA	10/28/92	117	TCE	2763783	10.8
	11 /02 /02*	100	TOP	056221	AT A
	11/02/92	109	PERC	2260640	NA NA

TCE- Trichloroethene

PERC- Tetrachloroethene

NA- Not applicable

RSD- Relative Standard Deviation

PPD- Relative Percent Difference

PPB- parts per billion

^{*-} Rerun of 500 ppb standard using new PCE/TCE stock solution prepared out in the field due to high RPD for daily final for previous three days. Insufficient amount of solvent to make 50 and 1000 ppb standards. RPD based upon 500 ppb standard.

TABLE 3 (cont.) SUMMARY OF CALIBRATION RESULTS FOR FASP ANALYSIS NORTHWEST PIPE AND CASING SITE ASSESSMENT CLACKAMAS, OREGON

Date	Retention Time (seconds)	Analytes	Peak Areas	% RPD
CONTINUING	CALIBRATION: (cont.)			
(500 ppb TC	E/PERC)			
11/03/92	115	TCE	1014298	16.9
	137	PERC	2509101	10.4
11/05/92	110	TCE	955611	11.0
	132	PERC	2224552	1.6
11/06/92	125	TCE	947784	10.2
	149	PERC	2420376	6.8
11/07/92	116	TCE	872412	1.9
	138	PERC	2078878	8.4
11/11/92	107	TCE	1177061	31.5
	128	PERC	3274259	36.6
11/12/92	107	TCE	956528	11.0
	129	PERC	2434356	7.4
11/13/92	102	TCE	849111	0.8
	122	PERC	2185887	3.4
11/16/92	98	TCE	1005920	16.1
	117	PERC	2456230	8.3
11/20/92	98	TCE	887586	3.6
,,	118	PERC	2557395	12.3

TCE- Trichloroethene

PERC- Tetrachloroethene NA- Not applicable

RPD- Relative Percent Difference

PPB- parts per billion

TABLE 3 (cont.) SUMMARY OF CALIBRATION RESULTS FOR FASP ANALYSIS NORTHWEST PIPE AND CASING SITE ASSESSMENT CLACKAMAS, OREGON

Date	Retention Time (seconds)	Analytes	Peak Areas	% RPD
DAILY/FINAL	CALIBRATION:			
(500 ppb TC	E/PERC)			
10/27/92	134 160	TCE PERC	3834564 2249746	42.9 61.0
10/28/92	133 159	TCE PERC	5453315 3201621	74.9 91.1
10/29/92	135 162	TCE PERC	1257794 4058686	65.4 108.8
10/31/92	NA			•
11/02/92*	130 156	TCE PERC	768573 2593310	10.8 13.7
11/03/92	NA			
11/05/92	109 130	TCE PERC	724044 1886119	16.7 18.1
11/06/92	NA			
11/07/92	NA			

TCE- Trichloroethene

PERC- Tetrachloroethene

NA- Not applicable/Not performed

RSD- Relative Percent Difference

PPB- parts per billion

^{*-} Rerun of 500 ppb standard using new PCE/TCE stock solution prepared out in the field due to high RPD for daily final for previous three days. Insufficient amount of solvent to make 50 and 1000 ppb standards. RPD based upon 500 ppb standard.

where: CF_I = mean CF from the initial calibration for each analyte CF_C = measured CF from the continuing calibration or daily calibration for the same analyte

6.0 METHOD BLANK DATA

Method blanks were analyzed each day using deionized water for sample analysis (Table 4). The method blank was analyzed immediately after and prior to sample analysis to insure that there was no sample carry-over after continuing calibration was verified. Two method blanks showed positive results for PERC, however, the results were below detection limits and may have been caused by contaminant carry-over during pre-site assessment activities.

7.0 MATRIX SPIKE DATA

Matrix spikes were done on two soil samples previously identified as nondetect at the given detection limits. One sample was spiked with 2 µg of PERC (41 µl/l diluent) and another with 10 µg of PERC (205 µl/l diluent). Both samples were analyzed using purge and trap. The results were 7.5 µl/l of PERC for the first sample, representing an 18% recovery, and 20.4 µl/l of PERC for the second sample, representing a 10% recovery. Possible explanations for the low recovery could be the low temperature of the sample resulting in ineffective purging or mobilization of contaminants, inefficient purging technique leading to loss of contaminant, or insolubility of the standard in the deionized water diluent. The use of a water bath in conjunction with a purge and trap unit that utilizes heated purge lines and needles capable of being directly injected into the septum of the sample vial may help to increase efficiency.

8.0 DUPLICATE SAMPLE DATA

Duplicate samples were run on approximately 10% of the positive and nondetected results during the sampling event. Only the positive duplicate results were listed in Table 5 to provide information on method precision.

9.0 INSTRUMENT OPERATING PARAMETERS

Instrument: Sentex Scentograph Calibrant: 500 ppb TCE/PERC Sample Time: 30 seconds Delay/Desorption Time: 4 seconds Inhibit Time: 65 seconds Oven Temperature: 55 degrees Celsius Chart Duration: 5 minutes Column Type: 3% Supelcoport-1000 packed column Detector Type: Argon Ionization Detector Final Temperature: 55 degrees Celsius Initial Gain: Column Pressure: 20 pounds per square inch Enable External Purge:

TABLE 4 SUMMARY OF METHOD BLANK RESULTS FOR FASP ANALYSIS NORTHWEST PIPE AND CASING SITE ASSESSMENT CLACKAMAS, OREGON (µg/L)

Sample	Well	Date	Analyte	TAT Lai	b
WATER BLK	MW-08	10/27/92	TCE	10	UF
			PERC	2	F
WATER BLK	MW-09	11/02/92	TCE	10	UF
			PERC	2	F
WATER BLK	MW-10	11/05/92	TCE -	10-	UF
			PERC	10	UF
WATER BLK	MW-11	11/06/92	TCE	10	UF
			PERC	10	UF
WATER BLK	DOT-5	11/11/92	TCE	10	UF
			PERC	10	UF
WATER BLK	DOT-6	11/16/92	TCE	10	UF
			PERC	10	UF
WATER BLK	MW-01	11/16/92	TCE	10	UF
			PERC	10	UF
WATER BLK	MW-02	11/16/92	TCE	10	UF
			PERC	10	UF
WATER BLK	MW-03	11/16/92	TCE	10	UF
		444440	PERC	10	UF
WATER BLK	MW-04	11/16/92	TCE	10	UF
WAMED DIE	WII 05	11/1//00	PERC	10	UF
WATER BLK	MW-05	11/16/92	TCE	10	UF
עוות משיינו	MIT OC	11/16/02	PERC	10	UF
WATER BLK	MW-06	11/16/92	TCE	10	UF
מות ממחת	MII 07	11/16/02	PERC	10	UF
WATER BLK	MW-07	11/16/92	TCE PERC	10 10	UF UF

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

DOT- Department of Transportation

BLK- Blank

F- The data has been generated by the Technical Assistance Team using FASP methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

TABLE 5
SUMMARY OF DUPLICATE SAMPLE RESULTS
FOR GROUNDWATER SAMPLES
NORTHWEST PIPE AND CASING SITE ASSESSMENT
CLACKAMAS, OREGON
(µg/L)

Sample	Well	Analyte Result		Date	Time	
MW-9-8W	MW-9	TCE	8.7	F	11/02/92	13:21
MW-9-8WD	MW-9	TCE	8.2	F	11/02/92	13:40
DOT-5-8W	DOT-5	PERC	1.5	F	11/12/92	11:11
DOT-5-8WD	DOT-5	PERC	1.8	F.	11/12/92	11:23
MW-2-W	MW-2	TCE	493.5	F	11/16/92	12:15
		PERC	22.7	F		
MW-2-WD	MW-2	TCE	407.4	F	11/16/92	17:33
		PERC	24.3	F		
DOT-6-W	DOT-6	TCE	2.7	F	11/20/92	11:41
DOT-6-WD	DOT-6	TCE	2.6	F	11/20/92	11:53

W- Water

WD- Water Duplicate

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

DOT- Department of Transportation

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

10.0 CONCLUSION

Subsurface Soil and groundwater samples were analyzed by the TAT FASP laboratory to acquire immediate analytical data as an integral part of the Northwest Pipe and Casing monitoring well drilling operation. The samples were analyzed for TCE and PERC using modified FASP methodologies. FASP data provided tentative identification of previously identified target analytes, at estimated concentrations. Confirmatory analysis was performed by a commercial laboratory on split samples at a frequency of 8 percent for soils and 16 percent. The purpose of confirmatory analysis was to provide positive identification of target analytes previously identified by the TAT laboratory. Correlation between the TAT and the commercial laboratory was excellent. TAT identification of TCE and PERC was confirmed by the commercial laboratory, and relative trends in analyte concentrations generally agreed.

Based on commercial laboratory confirmation results, TAT FASP data was determined to be acceptable for use in establishing tentative identification and estimated quantities of TCE and PERC for the Northwest Pipe and Casing Site.

APPENDIX A SAMPLE CHROMATOGRAMS

SCENTOGRAPH TRACE PRINOUT

TRACE #265 DATE: Wed Nov 11 14:25:54 1992

CHANNEL: 1

NAME: DOT-5-2W

COLUMN: 3%8P-1000

DETECTOR: AID

COLUMN PRESSURE: 20

TEMPERATURE: 55

INHIBIT TIME: 65 Seconds

PĚAK# NAME

RT AREA CONCENTRATION


1 TCE 106

5686

2.415 PPB

TOTAL AREA:

5686



SCENTOGRAPH TRACE PRINOUT

TRACE #370 DATE: Mon Nov 16 12:19:32 1992

CHANNEL: 1

NAME: MW-2-W

COLUMN: 3%SP-1000

DETECTOR: AID

COLUMN PRESSURE: 20

TEMPERATURE: 55

INHIBIT TIME: 65 Seconds

PEAK# NAME

RT AREA CONCENTRATION


1 TCE 100 1777949

883.743 PPB

2 PERC 121 244515

49.774 PPB

TOTAL AREA: 2022464



SCENTOGRAPH TRACE PRINOUT

TRACE #463

DATE: Fri Nov 20 11:53:45 1992

CHANNEL: 1

NAME: DOT-6-W DUP

COLUMN: 3%SP-1000

DETECTOR: AID

COLUMN PRESSURE: 20

TEMPERATURE: 55

INHIBIT TIME: 65 Seconds

4626

PEAK# NAME


CONCENTRATION AREA

1 TCE

98

2.606 PPB

TOTAL AREA: 4626



APPENDIX B

SUMMARY OF ANALYTICAL RESULTS

FOR

SUBSURFACE SOIL AND GROUNDWATER SAMPLES
NORTHWEST PIPE AND CASING SITE ASSESSMENT

 $(\mu g/L)$

Sample	Analyte	TAT La	TAT Lab	
MW-8-1S	TCE	10	UF	
5 _5	PERC	10	UF	
MW-8-2S	TCE	10	UF	
	PERC	10	UF	
MW-8-3S	TCE	10	UF	
	PERC	10	UF	
MW-8-4S	TCE	10	UF	
	PERC	10	UF	
MW-8-5S	TCE	10	UF	
	PERC	10	UF	
MW-8-6S	TCE	10	UF	
	PERC	10	UF	
MW-8-7S	TCE	10	UF	
0.00	PERC	10	UF	
MW-8-8S	TCE	10	UF	
WI 0 00	PERC	10	UF	
MW-8-9S	TCE	10	UF	
MW-8-10S	PERC TCE	10	UF	
WA-0-102	PERC	· 10 10	UF UF	
MW-8-11S	TCE	10	UF	
NW-0-113	PERC	10	UF	
MW-8-12S	TCE	10	UF	
114-0-125	PERC	10	UF	
MW-8-14S	TCE	10	UF	
0 2 10	PERC	10	UF	

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

S- Soil sample

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

(µg/L)

Sample	Analyte	TAT La	TAT Lab	
MW-8-15S	TCE	10	UF	
	PERC	10	UF	
MW-8-16S	TCE	10	UF	
	PERC	10	UF	
MW-8-17S	TCE	10	UF	
	PERC	10	UF	
MW-8-18S	TCE	NA		
	PERC	NA		
MW-8-19S	TCE	NA		
	PERC	NA		
MW-9-1W	TCE	5	UF	
	PERC	5	UF	
MW-9-1S	TCE	10	UF.	
	PERC	10	UF	
MW-9-2W	TCE	5	UF	
	PERC	5 5 5	UF	
MW-9-3W	TCE	5	UF	
	PERC	5	UF	
MW-9-35	TCE	10	UF	
	PERC	10	UF	
MW-9-5W	TCE	7	F	
	PERC	5	UF	
MW-9-5S	TCE	10	UF	
	PERC	10	UF	
MW-9-6W	TCE	5	UF	
	PERC	5	UF	

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

S- Soil

W- Water

NA- Not Analyzed or reported due to sample carryover problems

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

(µg/L)

Sample	Analyte	TAT Lab		,
MW-9-6S	TCE	10	UF	
	PERC	10	UF	
MW-9-7W	TCE	3	F	
	PERC	5	UF	
MW-9-7S	TCE	10	UF	•
	PERC	10	UF	•
MW-9-8W	TCE	9	F	
	PERC	5	UF	
MW-9-8WD	TCE	5 8 5 5	F	
	PERC	5	UF	
MW-9-9W	TCE	5	UF	
	PERC	5	UF	•
MW-9-10W	TCE	5	UF	
	PERC	5	UF	
MW-9-10S	TCE	10	UF	
0 1177	PERC	10	UF	
MW-9-11W	TCE	5 5	UF	
WI 0 11C	PERC		UF	
MW-9-11S	TCE	10	UF	
MW-9-12W	PERC	10 5	UF UF	
UM-J-ICM	TCE	5	UF	
MW-9-12S	PERC TCE	10	UF	
11#-7-123	PERC	10	UF	

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

S- Soil

W- Water

- F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.
- U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

 $(\mu g/L)$

Sample	Analyte	TAT Lab		
MW-9-13W	TCE	5	UF	
	PERC	5	UF	
MW-9-14W	TCE	5	UF	
	PERC	5 5 5 5	UF	
MW-9-15W	TCE	5	UF	
	PERC	5	UF	
MW-9-15S	TCE	10	UF	
	PERC	10	UF	
MW-9-16W	TCE	5	UF	
	PERC	5	UF	
MW-9-17W	TCE	5 5 5	UF	
	PERC		UF	
MW-9-17S	TCE	10	UF	
	PERC	10	UF	
MW-10-1W	TCE	1	F	
	PERC	5	UF	
MW-10-2W	TCE	2	F	
	PERC	. 5	UF	
MW-11-1W	TCE	5	UF	
	PERC	5	UF	
MW-11-1S	TCE	10	UF	•
	PERC	10	UF	
MW-11-2W	TCE	5	UF	
	PERC	5	UF	
MW-11-2S	TCE	10	UF	
	PERC	10	UF	

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

S- Soil

W- Water

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

(µg/L)

Sample	Analyte	TAT Lab		
MW-11-3W	TCE	5	UF	
	PERC	5	UF	
MW-11-3S	TCE	10	UF	
	PERC	10	UF	
MW-11-4W	TCE	5	UF	
	PERC	5	UF	
MW-11-5S	TCE	10	UF	
	PERC	10	UF	
MW-11-5W	TCE	5	UF	
	PERC	5 5 5 5	UF	
MW-11-6W	TCE	5	UF	
	PERC		UF	
MW-11-6S	TCE	10	UF	
	PERC	10	UF	
MW-11-7W	TCE	5	UF	
	PERC	5	UF	
MW-11-8W	TCE	5	UF	
	PERC	5	UF	
MW-11-9W	TCE	5 5	UF	
	PERC	5	UF	
MW-11-10W	TCE	5 5	UF	
MW-11-11W	PERC	5	UF	
	TCE	5	UF	
WI 11 1017	PERC	5 5	UF	
MW-11-12W	TCE	5 5	UF	
	PERC	2	UF	

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

S- Soil

W- Water

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

 $(\mu g/L)$

Sample	Analyte	TAT La	b
MW-11-13W	TCE	5	UF
	PERC	5	UF
MW-11-13S	TCE	10	UF
	PERC	10	UF
MW-11-14S	TCE	10	UF
	PERC	10	UF
DOT-5-1W	TCE	5	UF
	PERC	5	UF
DOT-5-1S	TCE	10	UF
	PERC	10	UF
DOT-5-2W	TCE	2	F
	PERC	5	UF
DOT-5-2S	TCE	10	UF
	PERC	10	UF
DOT -5-3W	TCE	5	UF
	PERC	5	UF
DOT-5-3S	TCE	10	UF
	PERC	10	UF
DOT-5-4W	TCE	5	UF
	PERC	5 5	UF
DOT-5-4S	TCE	10	UF
	PERC	10	UF

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

DOT- Department of Transportation

S- Soil

W- Water

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

 $(\mu g/L)$

Sample	Analyte	TAT La	ıb
DOT-5-5S	TCE	10	UF
	PERC	10	UF
DOT-5-6W	TCE	5 5	UF
	PERC	5	UF
DOT-5-6S	TCE	10	UF
	PERC	10	UF
DOT-5-7W	TCE	5	UF
	PERC	5	UF
DOT-5-7S	TCE	10	UF
	PERC	10	UF
DOT-5-8W	TCE	5	UF
	PERC	. 3	F
DOT-5-8S	TCE	10	UF
	PERC	10	UF
DOT-5-9W	TCE		UF
	PERC	5 5	UF
DOT-5-9S	TCE	10	UF
	PERC	10	UF
DOT-5-10W	TCE	5	UF
	PERC	5	UF
DOT-5-10S	TCE .	10	UF
	PERC	10	UF
DOT-5-11W	TCE	5	UF
	PERC	5	UF

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

DOT- Department of Transportation

S- Soil

W- Water

- F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.
- U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

 $(\mu g/L)$

	Analyte	TAT La	LD		
DOT-5-11S	TCE	10	UF		
	PERC	10	UF		
DOT-5-12W	TCE	5	UF		
	PERC	5	UF		
DOT-5-12S	TCE	10	UF		
	PERC	10	UF		
DOT-5-13W	TCE	5	UF		
	PERC	5	UF		
DOT-5-13S	TCE	. 10	UF		
	PERC	10	U F		
DOT-5-14W	TCE	5	UF		
	PERC	5	UF		
DOT-5-14S	TCE	10	UF		
	PERC	10	UF	-	
DOT-5-15W	TCE	5	UF		
	PERC	5	UF		
DOT-5-15S	TCE	10	UF		
	PERC	10	UF		
DOT-5-17W	TCE	5	UF		
5-5-5-45	PERC	5	UF		
DOT-5-18W	TCE	5	UF		
DOM 5 1011	PERC	5	UF		
DOT-5-19W	TCE	5	UF		
DOM 5 100	PERC	5	UF		
DOT-5-19S	TCE PERC	10 10	UF UF		

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

DOT- Department of Transportation

S- Soil

W- Water

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

 $(\mu g/L)$

Sample	Analyte	TAT La	.b		
MW-3-W	TCE	5	UF		
	PERC		UF		
MW-5-W	TCE	5 5 5	UF		
	PERC	5	UF		
MW-2-W	TCE	490	F		
	PERC	22	F		
MW-7-W	TCE	420	F		
	PERC	17	F		
MW-1-W	TCE	140	F		
	PERC	360	F		
MW-6-W	TCE	390	F		
	PERC	17	F		
MV-4-V	TCE	2200	F		
	PERC	2100	F		
DOT-1-W	TCE	. 5	UF		
	PERC	1	F		
DOT-2-W	UNKNOWN	44	F		
	TCE	5	UF		
	PERC	5	UF		
DOT-3-W	TCE	5	UF		
	PERC	5 5	UF		
DOT-4-W	TCE	5	UF		
	PERC	5	UF		
DOT-5-W	TCE	5 5 5 . 3	UF		
	PERC	5	UF		
DOT-6-W	TCE	. 3	F		
	PERC	5	UF		

TCE- Trichloroethene

PERC- Tetrachloroethene

MV- Monitoring Well

DOT- Department of Transportation

S- Soil

W- Water

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

 $(\mu g/L)$

Sample	Analyte	7	CAT Lab	
MW-9-W	TCE	5	UF	
	PERC	5	UF	
MW-12-W	TCE	5	UF	
	PERC	5	UF	
MW-11-W	TCE	5	UF	
	PERC	5	UF	

TCE- Trichloroethene

PERC- Tetrachloroethene

MW- Monitoring Well

DOT- Department of Transportation

S- Soil

W- Water

F- The data has been generated by the Technical Assistance Team using FASP Methodologies. Analytes are tentatively identified and concentrations are quantitative estimates.

U- The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit

APPENDIX D

QUALITY ASSURANCE REVIEW

KEY TO TAT SAMPLE NUMBERS

TAT Sample Numbers	Matrix	Sample Location (Well)
T2100121	Water	MW-2
T2100122	Water	MW-4
T2100123	Water	MW-6
T2100110	Water .	MW-8
T2100111	Water	MW-9
T2100112	Water	MW-10
T2100113	Water	MW-11.
T2100114	Water	MW-12
T2100115	Water	ODOT-5
T2100116	Water	ODOT-5 Dup.
T2100117	Water	ODOT-6
T2100124	Water	Trip Blank
T2100125	Water	Trip Blank
T2100104	Water	Trench-2
T2100105	Water	Trench-4
T2100106	Water	Trench-1
T2100120	Water	Purge Water
T2100100	Soil	MW-8
T2100101	Soil	MW-9 .
T2100102	Soil	MW-11
T2100103	Soil	O DOT -5
T2100118	Soil	Drill Cutting
T2100119	Soil	Drill Cutting

1500 FIRST INTERSTATE BUILDING, 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

HEMORANDUM

DATE: January 26, 1993

TO: Dawn Hartley, Project Manager, E & E, Seattle, WA

FROM: Mark Woodke, TAT-Chemist, E & E, Seattle, WA

THRU: David Byers, TAT-Chemist, E & E, Seattle, WA 72B

SUBJ: Organic Data Quality Assurance Review, Northwest Pipe and

Casing, Clackamas, Oregon

REF: Project TDD: T10-9210-031 Analytical TDD: T10-9210-058

Project PAN: EOR-0201-SC Analytical PAN: EOR-0202-AB

The data quality assurance review of 17 water and 2 soil samples collected from the Northwest Pipe and Casing site in Clackamas, Oregon, has been completed. Analysis for Volatile Organic Compounds (EPA method 8240) was performed by Sound Analytical Services, Tacoma, Washington.

The 19 samples were numbered:

T2100104	T2100105	T2100106	T2100110	T2100111
T2100112	T2100113	T2100114	T2100115	T2100116
T2100117	T2100118(soil)	T2100119(soil)	T2100120	T2100121
T2100122	T2100123	T2100124	T2100125	

Data Qualifications:

I Holding Time: Acceptable.

Samples T2100104, T2100105, and T2100106 were collected 11-18-92. Samples T2100110 through sample T2100117 were collected on 11-19-92. Samples T2100118, T2100119, T2100120, T2100124, and T2100125 were collected 11-20-92. Samples T2100121, T2100122, and T2100123 were collected 11-14-92. All samples were analyzed on or before 12-01-92. All samples were analyzed within QC criteria of 14 days from collection to analysis.

II GC/MS Tuning: Acceptable.

All tuning check compound mass abundances and ratios were within contract-required limits for volatile analysis.

III Calibration

A. Initial Calibration: Satisfactory.

All System Performance Check Compounds (SPCCs) were within contract-required limits for the initial calibration with average Relative Response Factors (RRFs) above 0.05 for volatiles, except:

Date	Compound	RRF	QC Limits	Associated Samples
11-11-9 2	Acetone	0.031	> 0.050	a
	2-Butanone	0.009	> 0.050	
12-01-92	Acetone	0.033	> 0.050	b
	2-Butanone	0.012	> 0.950	

a - T2100104 through T2100117

Positive results were flagged as estimated quantities (J) and sample quantitation limits for acetone and 2-butanone were rejected (R) in all samples.

All Calibration Check Compounds (CCCs) and non-CCCs were within contract-required limits for the initial calibration with Percent Relative Standard Deviations (RSDs) below 30 percent, except:

Date 11-11-92	Compound m&p-xylene	RSD 36.5%	QC Limits < 30%	Associated Samples a
12-01-92	Ethyl benzene	35.3%	< 30%	b
12-01-92	m&p-xylene	49.0%	< 30%	
12-01-92	o-xylene	32.0%	< 30%	

a - T2100104 through T2100117

No action was taken based on the continuing calibration QC outliers as none of the outliers were detected in any samples.

b - T2100118, T2100119, T2100120

b - T2100118, T2100119, T2100120

B. Continuing Calibration: Satisfactory.

T2100123, T2100124, T2100125

All System Performance Check Compounds (SPCCs) were within contract-required limits for the continuing calibration with average Relative Response Factors (RRFs) above 0.05 for volatiles, except:

Date	. (Compound	RRF	QC Limits	Associated Samples
11-24	-92 2	2-Butanone	0.039	> 0.050	<u>a</u>
11-25	-92	2-Butanone	0.020	> 0.050	Ъ
a - T	2100104	4, T2100105,	T2100106,	T2100111, T2100	112, T2100113,
T	2100114	4			
b - T	2100110	O. T2100115.	T2100116.	T2100117, T2100	121, T2100122.

Positive results for 2-butanone were flagged as estimated quantities (J) in all samples. Sample quantitation limits for 2-butanone were rejected (R) in all samples.

All Calibration Check Compounds (CCCs) and non-CCCs were within contract-required limits for the continuing calibration with Percent Relative Standard Deviations (RSDs) below 25 percent, except:

Date	Compound	RSD	QC I	Limits	Associated Samples
11-24-92	Acetone	42.8%		25%	a
11-24-92	Methylene Chloride	31.0%	<	25%	
11-24-92	1,1-Dichloroethane	42.8%	<	25%	
11-24-92	1,2-Dichloroethene	27.4%	<	25%	
11-24-92	1,2-Dichloroethane	70.0%	<	25%	
11-24-92	2-Butanone	343.8%	<	25%	
11-24-92	1,1,1-Trichloroethane	56.6%	<	25%	
11-24-92	Carbon tetrachloride	49.8%	<	25%	
11-24-92	Styrene	26.4%	<	25%	
11-24-92	Bromodichloromethane	47.0%	<	25%	
11-24-92	c-1,3-dichloropropane	26.6%	<	25%	
11-24-92	Dibromochloromethane	29.2%	<	25%	
11-24-92	Benzene	29.5%	<	25%	
11-24-92	t-1,3-dichloropropane	27.3%	<	25%	
11-24-92	4-Methyl-2-pentanone	40.5%	<	25%	
11-24-92	2-Hexanone	193.2%	<	25%	
11-24-92	1,1,2,2-Tetrachloroethane	36.4%	<	25%	
11-24-92	m&p-xylene	53.1%	<	25%	
11-24-92	o-xylene	40.3%	<	25%	

Date	Compound	RSD .	QC Limits	Associated Samples
11-25-92	Acetone	145.9%	< 25%	<u>b</u>
11-25-92	Methylene Chloride	66.5%	< 25%	
11-25-92	Chloromethane	25.9%	< 25%	
11-25-92	1,2-Dichloroethane	41.7%	< 25%	
11-25-92	2-Butanone	129.3%	< 25%	
11-25-92	1,1,1-Trichloroethane	32.3%	< 25%	•
11-25-92	Carbon tetrachloride	91.4%	< 25%	
11-25-92	Bromodichloromethane	33.4%	< 25%	
11-25-92	Dibromochloromethane	29.2%	< 25%	
11-25-92	2-Hexanone	61.0%	< 25%	
11-25-92	Bromoform	39.0%	< 25%	
11-25-92	m&p-xylene	33.1%	< 25%	

a - T2100104, T2100105, T2100106, T2100111, T2100112, T2100113, T2100114

Positive results and sample quantitation limits for the RRF QC outliers were flagged as estimated quantities (J) in samples.

IV Method Blank: Satisfactory.

The following compounds were detected in blanks:

Blank	Date	Compound	Concentration	Associated Samples
M. Blank	11-24-92	Methylene Chloride	3.3 ug/L	a
M. Blank	11-25-92	Methylene Chloride	6.0 ug/L	Ъ
		Toluene	1.3 ug/L	
		Ethylbenzene	1.3 ug/L	
		m&p-xylene	1.5 ug/L	
M. Blank	12-01-92	Methylene Chloride	3.8 ug/L	С
M. Blank	11-24-92	Methylene Chloride	240 ug/Kg	T2100118
M. Blank	11-25-92	Methylene Chloride	360 ug/Kg	T2100119

a - T2100105, T2100106, T2100112, T2100113, T2100114, T2100117

Results for the compound detected in the blanks were flagged as not detected (U) in the associated samples if the amount detected in the samples was less than 5 times the amount detected in the blank (10 times for common contaminants).

b - T2100110, T2100115, T2100116, T2100117, T2100121, T2100122, T2100123, T2100124, T2100125

b - T2100104, T2100110, T2100111, T2100115, T2100116, T2100120, T2100121, T2100125

c - T2100122, T2100123, T2100124

V Surrogate Recovery: Acceptable.

Recoveries for all surrogate compounds met QC criteria.

VI Matrix Spike/Matrix Spike Duplicates: Acceptable.

All matrix spike/matrix spike duplicate analyses met QC criteria.

VII Internal Standards: Acceptable.

All internal standard results were within QC limits.

VIII Field Duplicates: Not Applicable.

IX Overall Assessment of Data for Use

The overall usefulness of the data is based on the criteria outlined in the OSWER Directive "National Functional Guidelines for Organic Data Review" (June 1991).

Based upon the information provided, the data are acceptable for use with the above stated data qualifications.

Data Qualifiers and Definitions

- J The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.
- R Quality Control indicates that data are unusable for all purposes. The analyte was analyzed for, but the presence or absence of the analyte has not been verified. Resampling and reanalysis are necessary for verification to confirm or deny the presence of an analyte.

SPECIALIZING IN INDUSTRIAL & TOXIC WASTE ANALYSIS 4813 PACIFIC HTGHWAY EAST, TACOMA, WASHINGTON 98424 - TELEPHONE (206)922-2310 - FAX (206)922-5047

Report To: Ecology & Environment Date: December 21, 1992

Report On: Analysis of Water & Soil Lab No.: 28636

Page 1 of 94

IDENTIFICATION:

Samples Received on 11-23-92

Project: T109210031

ANALYSIS:

Lab No. 28636-1

Client ID: T2100114 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-24-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethane 1,1-Dichloroethane 1,2-Dichloroethane 1,2-Dichloroethane 2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethane Dibromochloromethane 1,1,2-Trichloroethane	22 <i>U</i>	20 V 20 V 20 V 100 V 10 10 10 10 10 10 10 10 10 10 10 10 10 1	

mr 1-26-93

Ecology & Environment Project: T109210031 Lab No. 28636 Page 2 of 94 December 21, 1992

Lab No. 28636-1

Client ID: T2100114 (water)

Compound	Concentration ug/l			
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 U 10 10 50 10 10 10 10 10	74 4 49 44	√ √

Ecology & Environment Project: T109210031

Lab No. 28636 Page 7 of 94 December 21, 1992

Lab No. 28636-2

Client ID: T2100112 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-24-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	20 V	20 V 20 20 V 100 V 10 10 10 10 10 10 10 10 10 10 10 10 10 1	R FT BT T T

ND = Not Detected

may 1-26-93

Ecology & Environment Project: T109210031 Lab No. 28636 Page 8 of 94 December 21, 1992

Lab No. 28636-2

Client ID: T2100112 (water)

Compound	Concentration ug/l	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 U D D D D D D D D D D D D D D D D D D

Ecology & Environment Project: T109210031

Lab No. 28636 Page 13 of 94 December 21, 1992

Lab No. 28636-3

Client ID: T2100113 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-24-92

Compound	Concentration ug/l		-
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	22 U 5.0	20 U 20 20 10 V 10 U 10 10 10 10 10 10 10 10 10 10 10 10 10 1	5 HHD ATH H

MW + 26-93

Ecology & Environment Project: T109210031 Lab No. 28636 Page 14 of 94 December 21, 1992

Lab No. 28636-3

Client ID: T2100113 (water)

Compound .	Concentration ug/l			
Benzene Trans-1,3-Dichloropropene		10 U 10 (7	
Bromoform 4-Methyl-2-Pentanone 2-Hexanone		10 50	44	
Tetrachloroethene 1,1,2,2-Tetrachloroethane		10 10 10	2	
Toluene Chlorobenzene		10 10		Whi
Ethyl Benzene Styrene Total Kylenes		10 10 10	7	1-24

Ecology & Environment Project: T109210031

Lab No. 28636 Page 19 of 94 December 21, 1992

Lab No. 28636-4

Client ID: T2100104 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-25-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-i,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	28 U 5.0	7	20 20 20 20 20 20 20 10 10 10 10 10 10 10 10 10 10 10 10 10

mr. 1-26-93

Ecology & Environment Project: T109210031

Lab No. 28636 Page 20 of 94 December 21, 1992

Salahara Military and Salahara

Lab No. 28636-4

Client ID: T2100104 (water)

8240 Continued .

Compound	Concentration ug/1	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 U J 10

Ecology & Environment Project: T109210031 Lab No. 28636 Page 25 of 94 December 21, 1992

Lab No. 28636-5

Client ID: T2100105 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-24-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane	37 22 U	20 U 20 U 20 U 100 U 10 10 10 10 10 10 10 10 10 10 10 10 10 10	R HAD RATH TO T

mm 1-21-93

Ecology & Environment Project: T109210031

Lab No. 28636 Page 26 of 94 December 21, 1992

Lab No. 28636-5

Client ID: T2100105 (water)

8240 Continued .

Compound .	Concentration ug/l	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 J 10 J 10 J 10 J 10 J 10 J 10 J 10 J

Ecology & Environment Project: T109210031 Lab No. 28636 Page 31 of 94 December 21, 1992

Lab No. 28636-6

Client ID: T2100106 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-24-92

Ccmpound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethane 1,2-Dichloroethane 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	22 V	20 U 20 V 20 V 20 V 100 U 10 10 10 10 10 10 10 10 10 10 10 10 10 1	R HAD ACH H H

1-26-93

Continued

Ecology & Environment Project: T109210031 Lab No. 28636

Page 32 of 94 December 21, 1992

Lab No. 28636-6

Client ID: T2100106 (water)

8240 Continued .

Compound	Concentration ug/l		
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Kylenes		10 V 10 10 10 10 10 10 10 10 10 10	55 bb 5 mm 26

Ecology & Environment Project: T109210031

Lab No. 28636 Page 37 of 94 December 21, 1992

Lab No. 28636-7

Client ID: T2100117 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-24-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene	24 U	20 U 20 V 20 V 100 V 10 10 10 10 10 10 10 50 10 10 10	5 R 5 R75 5
Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	3.0	10 <i>V</i>	J

M W - 26-93

Ecology & Environment Project: T109210031

Lab No. 28636 Page 38 of 94 December 21, 1992

Lab No. 28636-7

Client ID: T2100117 (water)

Compound	Concentration ug/l	PQL	Flag
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes	·	10 U 10 10 10 10 10 10 10 10	2 /-5p-

Ecology & Environment Project: T109210031 Lab No. 28636

Lab No. 28636 Page 43 of 94 December 21, 1992

Lab No. 28636-8

Client ID: T2100118 (soil)

Volatile Organics by Method 8240 Date Extracted: 11-24-92

Date Analyzed: 11-24-92

Compound	Concentration ug/kg			_
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethane 1,2-Dichloroethane 1,2-Dichloroethane 2-Butanone 1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,2-Trichloroethane	98Õ V	J	3,000 U 3,000	R J WHH J

mm +2693

Ecology & Environment Project: T109210031 Lab No. 28636

Lab No. 28636 Page 44 of 94 December 21, 1992

Lab No. 28636-8

Client ID: T2100118 (soil)

Compound Flag	Concentration ug/kg	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		300 U 300 U 30

Ecology & Environment Project: T109210031

Lab No. 28636 Page 49 of 94 December 21, 1992

Lab No. 28636-9

Client ID: T2100119 (soil)

Volatile Organics by Method 8240 Date Extracted: 11-25-92 Date Analyzed: 11-25-92

Compound	Concentration ug/kg			
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethane 1,2-Dichloroethane 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	510 V 95	5	500 500 500 500 250 250 250 250	J 448 4

MM 726-93

Continued

Ecology & Environment Project: T109210031

Lab No. 28636 Page 50 of 94 December 21, 1992

Lab No. 28635-9

Client ID: T2100119 (soil)

Compound Flag	Concentration ug/kg	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		250 U 250 250 1,250 250 250 250 250 250 250 250 250 250

Ecology & Environment Project: T109210031

Lab No. 28636 Page 55 of 94

December 21, 1992

Lab No. 28636-10

Client ID: T2100120 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-25-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethane 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	18 U	20 V 20 V 20 V 20 V 10 V 10 10 10 10 10 10 10 10 10 10 10 10 10 1	4 4400 d

ontinued...

Ecology & Environment

Project: T109210031 Lab No. 28636 Page 56 of 94 December 21, 1992

Lab No. 28636-10

Client ID: T2100120 (water)

Compound	Concentration ug/l	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 U 10 10 10 10 10 10 10 10 10 10 10 10 10

Ecology & Environment Project: T109210031 Lab No. 28636 Page 61 of 94 December 21, 1992

Lab No. 28636-11

Client ID: T2100121 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-25-92

Compound	Concentration ug/l	
Chloromethane		200 3
Bromomethane	1	200
Vinyl Chloride	18	J
Chloroethane		- 20U
Methylene Chloride	16 0) - [
Acetone		100UR
Carbon Disulfide		101
1,1-Dichloroethene		10
1,1-Dichloroethane		10
1,2-Dichloroethene (Total)		10 [
Chloroform		10 リナ
1,2-Dichloroethane		10 🗸
2-Butanone	110	· 15
1,1,1-Trichlorcethane		10 0 7
Carbon Tetrachloride		10 ブ
Vinyl Acetate		50
Bromodichloromethane		10 1
1,2-Dichloropropane		10
Cis-1,3-Dichloropropene		10 V
Trichloroethene	42	
Dibromochloromethane	.~	100
1,1,2-Trichlorcethane		101

MW F26-9:

Ecology & Environment Project: T109210031 Lab No. 28636 Page 62 of 94 December 21, 1992

Lab No. 28636-11

Client ID: T2100121 (water)

Compound	Concentration ug/l	·	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes	33	10 U 10 10 50 10 V	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2

Ecology & Environment Project: T109210031 Lab No. 28636

Lab No. 28636 Page 63 of 94 December 21, 1992

Lab No. 28636-12

Client ID: T2100122 (water)

Volatile Organics by Method 8240 Date Analyzed: 12-1-92

Compound	Concentration ug/1		
Chloromethane Bromomethane		1 .00	J _
Vinyl Chloride	1,000	400 <i>U</i>	
Chloroethane		4000	
Methylene Chloride	160 U	12	
Acetone			R
Carbon Disulfide		200	•
1,1-Dichloroethene 1,1-Dichloroethane		200	•
1,2-Dichloroethene (Total)		200 200	
Chloroform		200	J -
1,2-Dichloroethane		200	~-
2-Butanone	2,000		.)
1,1,1-Trichlorcethane			J
Carbon Tetrachloride		1 1 1	1
Vinyl Acetate Bromodichloromethane		1,000	ナ
1,2-Dichloropropane		200	J
Cis-1,3-Dichloropropene		200	
Trichloroethene	1,100	200 4	
Dibromochloromethane		200 V	
1,1,2-Trichloroethane		200 U	

mr 1-26-9.

Ecclogy & Environment Project: T109210031 Lab No. 28636

Lab No. 28636 Page 64 of 94 December 21, 1992

Lab No. 28636-12

Client ID: T2100122 (water)

Compound	Concentration ug/l		
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes	6,200	200 V 200 200 1,000 200 V 200 200 200 200 200 200	J MY 725-93

Ecology & Environment Project: T109210031 Lab No. 28636 Page 65 of 94 December 21, 1992

Lab No. 28636-13

Client ID: T2100123 (water)

Volatile Organics by Method 8240 Date Analyzed: 12-1-92

Compound	Concentration ug/l	
Chloromethane		20 V J
Bromomethane	66	20 <i>U</i>
Vinyl Chloride Chloroethane		200
Methylene Chloride	16 UJ	_ 200
Acetone		100VR
Carbon Disulfide		10 1
1,1-Dichloroethene		10
1,1-Dichloroethane		10
1,2-Dichloroethene (Total)		10 11
Chloroform 1,2-Dichloroethane		10 1
2-Butanone	120	10 4
1,1,1-Trichloroethane	120	101/15
Carbon Tetrachloride		10 15
Vinyl Acetate	Ĭ	50 \
Bromodichloromethane		10 5
1,2-Dichloropropane		10
Cis-1,3-Dichloropropene	1.2	10 🗸
Trichloroethene Dibromochloromethane	4 2	10:1
1,1,2-Trichloroethane		10 <i>U</i> 10 <i>U</i>
		1001

MW 92

Continued . .

Ecology & Environment Project: T109210031 Lab No. 28636 Page 66 of 94 December 21, 1992

Lab No. 28636-13

Client ID: T2100123 (water)

8240 Continued . . .

Compound	Concentration ug/1	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes	5.8	10 U J J J J J J J J J J J J J J J J J J

Ecology & Environment Project: T109210031

Lab No. 28636 Page 67 of 94 December 21, 1992

Lab No. 28636-14

Client ID: T2100124 (water)

Volatile Organics by Method 8240 Date Analyzed: 12-1-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	110 U	J .	20 V P P P P P P P P P P P P P P P P P P

MM 2693

Continued

his report is visual solely for the use of the person or company to whom it is addressed. This like

Ecology & Environment Project: T109210031 Lab No. 28636 Page 68 of 94 December 21, 1992

Lab No. 28636-14

Client ID: T2100124 (water)

8240 Continued

Compound	Concentration ug/l	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Kylenes		10 V 10 10 10 10 10 10 10 10 10 10 10 10 10

Ecology & Environment Project: T109210031 Lab No. 28636

Page 69 of 94 December 21, 1992

Lab No. 28636-15

Client ID: T2100115 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-25-92

Compound	Concentration ug/1	<u> </u>	
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	18 V	J	20 U 20 V J 10 10 10 10 10 10 10 10 10 10 10 10 10

2MM 1-26-93

Continued . . .

Ecology & Environment Project: T109210031 Lab No. 28636

Lab No. 28636
Page 70 of 94
December 21, 1992

Lab No. 28636-15

Client ID: T2100115 (water)

8240 Continued . . .

Compound	Concentration ug/l		
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 U 10 10 50 10 10 10 10 10 10	 Mm +26-

Ecology & Environment Project: T109210031 Lab No. 28636 Page 75 of 94

December 21, 1992

Lab No. 28636-16

Client ID: T2100116 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-25-92

Compound	Concentration ug/l	
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	20 U	20V 20V 20V 20V 20V 10 10 10 10 10 10 10 10 10 10 10 10 10

MW-26-93

Continued

Ecology & Environment
Project: T109210031
Lab No. 28636
Page 76 of 94
December 21, 1992

Lab No. 28636-15

Client ID: T2100116 (water)

8240 Continued . . .

Compound	Concentration ug/l	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 U 10 10 10 10 10 10 10 10 10 10 10 10 10

Ecology & Environment

Project: T109210031 Lab No. 28636 Page 81 of 94 December 21, 1992

Lab No. 28636-17

Client ID: T2100110 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-25-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethane 1,2-Dichloroethane 1,2-Dichloroethane 2-Butanone 1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropane Cis-1,3-Dichloropropane Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	18 V 6.6	10 U 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10	h 1 4 4 4 4 4

Continued . .

Ecology & Environment Project: T109210031

Lab No. 28636 Page 82 of 94 December 21, 1992

Lab No. 28636-17

Client ID: T2100110 (water)

8240 Continued . . .

Compound	Concentration ug/l	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 V 10 V 10 V 50 V 10 V

Ecology & Environment Project: T109210031 Lab No. 28636

Lab No. 28636 Page 87 of 94 December 21, 1992

Lab No. 28636-18

Client ID: T2100111 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-25-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethane 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	19 U 9.0	J 20 U 20 V	प प प प प प प प

MW F2693

Continued

Ecology & Environment Project: T109210031 Lab No. 28636 Page 88 of 94 December 21, 1992

Lab No. 28636-18

Client ID: T2100111 (water)

8240 Continued .

Compound	Concentration ug/l	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 D J 10 D MM 10 D D MM 10 D D MM 10 D D D MM 10 D D D D D D D D D D D D D D D D D D D

Ecology & Environment Project: T109210031 Lab No. 28636

Lab No. 28636 Page 93 of 94 December 21, 1992

Lab No. 28636-19

Client ID: T2100125 (water)

Volatile Organics by Method 8240 Date Analyzed: 11-25-92

Compound	Concentration ug/l		
Chloromethane Bromomethane Vinyl Chloride Chloroethane Methylene Chloride Acetone Carbon Disulfide 1,1-Dichloroethene 1,1-Dichloroethene 1,2-Dichloroethene (Total) Chloroform 1,2-Dichloroethane 2-Butanone 1,1,1-Trichloroethane Carbon Tetrachloride Vinyl Acetate Bromodichloromethane 1,2-Dichloropropane Cis-1,3-Dichloropropene Trichloroethene Dibromochloromethane 1,1,2-Trichloroethane	74 <i>U</i> 18	J	20 V J 10 10 10 10 10 10 10 10 10 10 10 10 10

Mr +2693

Continued

Ecology & Environment Project: T109210031

Lab No. 28636 Page 94 of 94 December 21, 1992

Lab No. 28636-19

Client ID: T2100125 (water)

8240 Continued . . .

Compound	Concentration ug/l	
Benzene Trans-1,3-Dichloropropene Bromoform 4-Methyl-2-Pentanone 2-Hexanone Tetrachloroethene 1,1,2,2-Tetrachloroethane Toluene Chlorobenzene Ethyl Benzene Styrene Total Xylenes		10 V 10 D 10 D 10 10 D 10 10 D 10 10 D 10 D



ecology and environment, inc.

1500 FIRST INTERSTATE BUILDING, 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

MEMORANDUM

DATE: January 26, 1993

TO: Dawn Hartley, Project Manager, E & E, Seattle, WA

FROM: Mark Woodke, TAT-Chemist, E & E, Seattle, WA ////

THRU: David Byers, TAT-Chemist, E & E, Seattle, WA

SUBJ: Inorganic Data Quality Assurance Review, Northwest Pipe and

Casing, Clackamas, Oregon

REF: Project TDD: T10-9210-031 Analytical TDD: T10-9210-058

Project PAN: EOR-0201-SC Analytical PAN: EOR-0202-AB

The data quality assurance review of 12 water and 2 soil samples collected from the Northwest Pipe and Casing site in Clackamas, Oregon, has been completed. Analysis for Priority Pollutant Metals (EPA 6000 and 7000 series methods) was performed by Sound Analytical Services, Tacoma, Washington.

The 14 samples were numbered:

T2100104	T2100105	T2100106	T2100110	T2100111
T2100112	T2100113	T2100114	T2100115	T2100116
T2100117	T2100118(soil)	T2100119(soil)	T2100120	

Data Qualifications:

I Holding Time: Acceptable.

Samples T2100104, T2100105, and T2100106 were collected 11-18-92. Samples T2100110 through sample T2100117 were collected on 11-19-92. Samples T2100118, T2100119, and T2100120 were collected 11-20-92. All analyses were performed on or before 12-08-92, therefore meeting QC criteria of less than 28 days between sampling and mercury analysis and less than 6 months between sampling and analysis for all other metals.

II Calibration

A. Initial Calibration and Calibration Verification: Acceptable.

All mercury results were within the control limits of 80 to 120 percent of the true values. All ICP results were within the 90 to 110 percent control limits.

B. Spike Sample Analysis: Satisfactory.

All Matrix Spike recoveries for the elements analyzed were within QC limits, except:

Sample	Element	Recovery	QC Limits
T2100119S	Thallium	71.5 %	75% - 125%

Positive results and sample quantitation limits for thallium in the soil samples were flagged as estimated quantities (J).

C. Serial Dilution Analysis: Satisfactory.

All Serial Dilution results for the elements analyzed were within QC limits, except:

Sample	Element	Difference	QC Limits
T2100119L	Arsenic	273.9 %	< 10 %
	Cadmium	37.4 %	< 10 %
	Chromium	28.9 %	< 10 %
	Copper	17.9 %	< 10 %
	Lead	98.6 %	< 10 %
	Zinc	25.5 %	< 10 %

Positive arsenic, cadmium, chromium, copper, lead, and zinc results were flagged as estimated quantities (J) in the soil samples.

VII Overall Assessment of Data for Use

The overall usefulness of the data is based on the criteria outlined in "Laboratory Data Validation Functional Guidelines for Evaluating Inorganic Analyses".

Based upon the information provided, the data are acceptable for use with the above stated data qualifications.

Data Qualifiers and Definitions

- J The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

	INORGANIC A	NALYSES DATA SHEET	EPA SAMPLE NO.
Lab Name: SOUND_ANA	ALYTICAL SERVICES	Contract: T109210031	100104
Lab Code:	Case No.:		
Matrix (soil/water): WATER	Lab Samp	ole ID: 28636-4
Level low/med):	LOW	Date Rec	eived: 12/09/92

% Solids: __0.0

CAS No.	Analyte	Concentration	С	5	М
7429-90-5	Aluminum_		<u> </u>		NR
7440-36-0	Antimony_	60.0	U		P_
7440-38-2	Arsenic	14.7	1_		F_
7440-39-3	Barium		_		NR
7440-41-7	Beryllium	5.0	U		P_
7440-43-9	Cadmium	5.0	١		P_
7440-70-2	Calcium				NR
7440-47-3	Chromium_	76.4			P_{-}
7440-48-4	Cobalt		[NR
7440-50-8	Copper				P_
7439-89-6	Iron				NR
7439-92-1	Lead	23.4	Ι_		F_
7439-95-4	Magnesium		!_		NR
7439-96-5	Manganese		· -		NR
7439-97-6	Mercury				AV
7440-02-0	Nickel	·			P
7440-09-7	Potassium		-		NR
7782-49-2	Selenium_	5.0	U		F_
7440-22-4	Silver		U		P_
7440-23-5	Sodium	· · · · · · · · · · · · · · · · · · ·			NR
7440-28-0	Thallium_	10.0	าบ		F_
7440-62-2	Vanadium_				NR
7440-66-6	Zinc		-		P
5955-70-0	Cyanide		-		NR

COIOI Selore.	 clarity before.		rexture:	-
Color After:	 Clarity After:	_ 	Artifacts:	_
Comments:	 	-7117	-26-93	

1 INORGANIC ANALYSES DATA SHEET

EPA	SAMPLE	NΩ
LFA	JAMELLE	110

Lab	Name:	SOUND_ANALYTI	CAL_SERVICES	Contract:	T109210031	10010	05
			Case No.:				

Matrix (soil/water): WATER

Lab Sample ID: 28636-5___

Level (low/med): LOW__

Date Received: 12/09/92

% Solids:

__0.0

CAS No.	Analyte	Concentration	С	Q	М
7429-90-5	Aluminum_				NR
7440- 36-0	Antimony_	81.3	_		P_
7440-38-2	Arsenic	1	U		F_
7440-39-3	Barium		_		NR
7440-41-7	Beryllium	5.0	Ū		P_
7440-43-9	Cadmium	5.0	U	5	P
7440- 70 - 2	Calcium		_		NR
7440- 47-3	Chromium_	29.4			P_
7440-48-4	Cobalt				NR
7440-50-8	Copper	46.4			P
7439-89-6	Iron				NR
7439-92-1	Lead	9.4	_		F_
7439-95-4	['] Magnesium		_		NR
7439-96-5	Manganese		_		NR
7439-97-6	Mercury	0.20	U		AV
7440-02-0	Nickel	40.0	U		P_
7440-09-7	Potassium	<u> </u>	_		NR
7782-49-2	Selenium_				F_
7440-22-4	Silver	10.0	U		P_
7440-23-5		.	1_		NR
7440-28-0			U	l	F_
7440-62-2	!Vanadium_		_		NR
7440-66-6	Zinc	277	_	.	P_
5955-70-0	'Cyanide	+	-	.	NR

color selore.	 ciditey before.	· · ·	lexture.	
Color After:	 Clarity After:		Artifacts:	
Comments:	 	Mr	1-26-43	

·	INORGANIC A	1 ANALYSES DATA		EPA	SAMPLE	NO.
Tah Name:	SOUND_ANALYTICAL_SERVICES	Contract: 1	T109210031		100106	

Matrix (soil/water): WATER Lab Sample ID: 28636-6___

Level (low/med): LOW__ Date Received: 12/09/92

% Solids: ___0.0

CAS No.	Analyte	Concentration	С	Q	М
7429-90-5	Aluminum_		_		NR
7440- 36-0	Antimony_	60.0	U		P_
7440-38-2	Arsenic	10.0	U		F_
7440-39-3	Barium		_		NR
7440-41-7	Beryllium	5.0	U	i	P_
7440-43-9	Cadmium	5.0	U	J	P_
7440-70-2	Calcium		l_		NR
7440-47-3	Chromium_	10.0	U		P_
7440-48-4	Cobalt		_		NR
7440- 50-8	Copper	25.0	U		P_
7439-89-6	Iron		1_		NR
7439-92-1	Lead	3.0	Ū		F_
7439-95-4	Magnesium		_		NR
7439-96-5	Manganese				NR
7439-97-6	Mercury	0.20	įŪ		ΑV
7440-02-0	Nickel		U		P_
7440-09-7	Potassium]_		NR
7782-49-2	Selenium_	5.0	์เบิ		F_
7440-22-4	Silver	10.0	Ìυ		P_
7440-23-5	Sodium			1	NR
7440-28-0	Thallium_	10.0	U		F_
7440-62-2	Vanadium_		. ! _		NR
7440-66-6		21.3			P_
5955-70-0	Cyanide_			i	NR

Color Eefore:		Clarity	Before:		Texture:	
Color After:	· · · · · · · · · · · · · · · · · · ·	Clarity	After:		Artifacts:	
Comments:				mm	1-21-93	

1 INORGANIC ANALYSES DATA SHEET

EPA	C	3.74	TOT	r	MO
LPA	\supset	Αľ	בעו	ıĿ	NO

	INONGANIC AN	While Dair 2	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Lab Name: SOUND_ANALY	TICAL_SERVICES	Contract: T1	109210031	100110
Lab Code:	Case No.:	SAS No.:	: 28636_	SDG No.: E&E
<pre>Matrix (soil/water):</pre>	WATER		Lab Sample	ID: 28636-17
Level (low/med):	LOW		Date Recei	ved: 12/09/92
% Solids:	0.0		·	

CAS No.	Analyte	Concentration	С	Q	M
7429-90-5	Aluminum_		_		NR
7440-36-0	Antimony_	60.0	Ū		P_
7440- 38 - 2	Arsenic	10.0	U		\mathbf{F}_{-}^{-1}
7440-39-3	Barium				NR
7440-41-7	Beryllium	5.0	Ū		P_
7440-43-9	Cadmium	5.0	U	2	P_
7440-70-2	Calcium		l _		NR
7440-47-3	Chromium_	69.4			P_
7440-48-4	Cobalt				NR
7440-50-8	Copper	25.0	U		P_
7439-89-6	Iron		l_		NR
7439-92-1	Lead	3.1			F_
7439-95-4	Magnesium				NR
7439-96-5	Manganese	l			NR
7439-97-6	Mercury	0.20	U		AV
7440-02-0	Nickel		U		P_
7440-09-7	Potassium				NR
7782-49-2	Selenium_	5.0	Ū		F_
7440-22-4	Silver	10.0	U		P_
7440-23-5	Sodium		1_		NR
7440-28-0	Thallium_	10.0	U		F_
7440-62-2	Vanadium_		1_		NR
7440-66-6	Zinc	20.0	U		P_
5955- 70-0	Cyanide		. _		NR

Color Before:	Clarity	Before:		Texture:
Color After:	Clarity	After:		Artifacts:
Comments:			J.W. H.	1-26-93
	.			

	I	NORGANIC A	l NALYSES DATA S	HEET	ŗ.	EPA	SAMPLE NO.
Lab Name: SOUND	_ANALYTICAL	_SERVICES	Contract: T1	092	10031		100111
Lab Code:	_ Cas	se No.:	SAS No.:	28	636_	SDG	No.: E&E
Matrix (soil/wa	ter): WATER	₹		Lab	Sampl	e ID	: 28636-18
Level low/med)	: LOW_	_		Dat	e Rece	ived	: 12/09/92
% Solids:	0.0)					
Cor	ncentration	Units (ug/	'L or mg/kg dry	we	ight):	UG/	L_
		:	1				
	CAS No.	Analyte	Concentration	С	Q	M	
	7429-90-5	Aluminum_		- -		NR	
		Antimony_	60.0	- -		P_	
		Arsenic _	10.0	, –			
		Barium				F_ NR	
		Beryllium	5.0	- -			
	7440-43-9	i =	5.0			P	
	7440-70-2	Calcium_		, , ,		P_ NR	
	7440-47-3		10.0	- -		l I	
	7440-48-4	_				P_ NR	
	7440-50-8	Copper	25.0	- -		1 ,	
	7439-89-6	Iron	25.0			P_ NR	
	7439-93-0		3.0			F_	
	1	Magnesium				NR	
	1	Manganese	1	- -		NR	
		Mercury	0.20	-		AV	
	7440-02-0		40.0			P_	
	•	Potassium		-		NR	
	j.	Selenium_	5.0	- -		F_	
		Silver	10.0	: -		P_	
	7440-23-5		1			NR	
	· ·	Thallium_	10.0	111		F_	
		Vanadium_	10.0			NR	
	7440-66-6	———	20.0	ן טו		P_	
	1	!Cyanide_				NR	
		-·		1=1			
Color Before:		Clari	ty Before:			Tex	ture:
Color After:		Clari	ty After:	 -		Art	ifacts:
Comments:					~h	7v. 1	-71-92

		U.S. I	EPA - CLP		
)	I	NORGANIC A	1 NALYSES DATA S	HEET	EPA SAMPLE NO.
Lab Name: SOUND	_ANALYTICAL	_SERVICES	Contract: T1	09210031	100112
Lab Code:	_ Cas	e No.:	SAS No.:	28636_	SDG No.: E&E
Matrix (soil/wa	ter): WATER	}		Lab Sampl	e ID: 28636-2
Level low/med)	: LOW	_		Date Rece	eived: 12/09/92
% Solids:	0.0)			
		•	L or mg/kg dry	weight):	ug/L
C 0 1					
	CAS No.	Analyte	Concentration	C Q	М
	7429-90-5	Aluminum_			NR
		Antimony_		ש	P_
	7440-38-2		11.1	-	F_
	7440-39-3		5.0		NR
	7440-41-7 7440-43-9		5.0	U .5	P_
	7440-70-2	Calcium		0 -2	P_ NR
	7440-47-3	Chromium_	41.0	-	P_
	7440-48-4		1	1-1	NR NR
	7440-50-8	1	71.8		P_
	7439-89-6		· ———		NR
	7439-92-1	1	23.2		F_{
	7439-95-4	;		-	NR
		Manganese		-	NR
	i	Mercury	0.20		AV
	7440-02-0		44.8	-	P_
	7782-49-2	Potassium Selenium_		-	NR F_
		Silver	10.0		P_
	7440-23-5		1		NR
		Thallium_	10.0	<u> </u>	F_
	7440-62-2	Vanadium_		. _	NR
	7440-66-6		110		_! P!
	5955- 70 - 0	Cyanide		. _	NR
		- · 		.!_!	
Color Before:		Clari	ty Before:		Texture:
Color After:		Clari	ty After:	 	Artifacts:
Comments:				200	1-26-93

		U.S. 1	EPA - CLP				
	I	NORGANIC A	l NALYSES DATA SI	HE:	ET	EPA SAMPLE NO	•
Lab Name: SOUND	_AN A LYTICAL	_SERVICES	Contract: T1	09	210031	100113	
Lab Code:			SAS No.:			SDG No. F&E	
	_						
Matrix (soil/wa	ter): WATER	•		La	D Sampı	le ID: 28636-3_	
Level (low/med)	: LOW	-		Da	te Rece	eived: 12/09/92	!
% Solids:	0.0)					
Cor	centration	Units (ug/	L or mg/kg dry	. M	eight):	: UG/I.	
							
	CAS No.	Analyte	Concentration	С	Q	м	
	7429-90-5	Aluminum		-		NR	
	7440-36-0	Antimony_				P_	
	7440-38-2	Arsenic	10.0	ָט		F_	
	7440-39-3	Barium		=	- -	NR	
•	7440-41-7	Beryllium Cadmium	5.0 5.0			P_	
	7440-43-9 7440-70-2	Calcium_	3.0	٦		P_ NR	
	7440-47-3	Chromium_	10.0	Ū		P_	
	7440-48-4	Cobalt		_		NR	
	7440-50-8	Copper	25.0	Ū		P_	
	7439-89-6	Iron		_		NR	
	7439-92-1	Lead	3.0	U		F_	
	7439-95-4	Magnesium		-		NR	
	7439-96-5	Manganese Mercury	0.20	1		NR	
	7440-02-0	Nickel	40.0	1		P_	
	7440-09-7				\	NR	
	7782-49-2	Selenium_	5.0	Ū		F_	
	7440-22-4	Silver	10.0	Ų	Í	_ P_	
	7440-23-5	Sodium				_ NR	
	7440-28-0 7440-62-2	Thallium_ Vanadium	10.0	U		- F_	
	7440-62-2	Zinc	20.0		:	NR P	
	5955-70-0	Cyanide		"		NR	
		_					
Color Eefore:		Clari	ty Before:			Texture:	
Color After:		Clari	ty After:		_	Artifacts:	
Comments:					MAY	V 1-26-93	

	1		
TNORGANIC	ANALVSES	ከልሞል	SHEET

EPA	SAMPLE	NO.
-----	--------	-----

Lab Name: SOUND_ANALY	TICAL SERVICES	Contract: T1	L09210031	100114
•	Case No.:			SDG No.: E&E
Lab Code:	case no	SAS NO.	. 20050_	SDG NO., Edb
<pre>Matrix (soil/water):</pre>	WATER		Lab Sample	e ID: 28636-1
Level 'low/med):	LOW		Date Rece	ived: 12/09/92
% Solids:	0.0			

CAS No.	Analyte	Concentration	С	Q	М
7429-90-5	Aluminum_				NR
7440- 36 - 0	Antimony_	60.0	U		P_
7440-38-2	Arsenic	10.0	U		F_
7440-39-3	Barium		_		NR
7440-41-7	Beryllium	5.0	U		P_
7440-43-9	Cadmium	5.0	U	1	P_
7440-70-2	Calcium		_		NR
7440-47-3	Chromium_	80.1			P_
7440-48-4	Cobalt				NR
7440-50-8	Copper	25.0	Ū		P_
7439-89-6	Iron		<u> </u>		NR
7439-92-1	Lead	3.0	Ū		F_
7439-95-4	Magnesium		_		NR
7439-96-5	Manganese		<u> </u>		NR
7439-97-6	Mercury	0.20	Ū		AV
7440-02-0	Nickel	1	_		P_
7440-09-7	Potassium		_		NR
7782-49-2	Selenium_	5.0	U		F_
7440-22-4	Silver	10.0	U		P_
7440-23-5	Sodium				NR
7440-28-0	Thallium_	10.0	U		F_
7440-62-2	Vanadium_		.		NR
7440-66-6		106	-		P_
5955-70-0	Cyanide		. [_		NR
İ	:				_

Color Before:	Clarity Before:	Texture:
Color After:	Clarity After:	Artifacts:
Comments:		MY -4-93

		U.S.	EPA - CLP			
1 INORGANIC ANALYSES DATA SHEET						EPA SAMPLE NO.
Lab Name: SOUND	_ANALYTICAI	L_SERVICES	Contract: T1	09	210031	100115
Lab Code:	Cas	se No.:	SAS No.:	2	8636	SDG No.: E&E
			<u>.</u>			
Matrix (soil/wa	ter): WATE	3		La	b Sampl	le ID: 28636-15
Level (low/med)	: LOW_	-		Da	te Rece	eived: 12/09/92
% Solids:	0.0					
_			/ -			
Cor	ncentration	Units (ug/	L or mg/kg dry	, w	eight)	: UG/L_
		<u> </u>		1	·	
	CAS No.	Analyte	Concentration	С	Q ·	М
	7429-90-5	Aluminum		-		NR
	7440-36-0	Antimony_	60.0	- i		P_
	7440-38-2	Arsenic _	10.0	1 1		F_ F_
	7440-39-3	Barium				NR
	7440-41-7	Beryllium	5.0	U		P_
	7440-43-9	Cadmium	5.0			P_
	7440-70-2	Calcium_				NR
	7440-47-3	Chromium_	10.0	Ū		P_
	7440-48-4	Cobalt		_		NR
	7440-50-8	Copper	29.0			P_
	7439-89-6	Iron				NR
	7439-92-1	Lead	5.8	[_	l ————	F_
	7439-95-4	Magnesium		1		NR
	7439-96-5			-	[NR
	7439-97-6		0.20			AV
	7440-02-0	Nickel	40.0	U	!	_ P
	7440-09-7	Potassium		.	ļ ———	NR NR
	7782-49-2	Selenium_	***			_ F
	7440-22-4	Silver	10.0	10		- P_
	7440-23-5	Sodium	10.0	-	ļ	NR
	7440-28-0 7440-62-2	· · · · · · · · · · · · · · · · · · ·	· ·	JU		_ F_
	7440-62-2	Vanadium_ Zinc	43.2	- —		NR D
	5955-70-0		43.2	-	i ——	P_ NR
	3333 70 0	cyaniue		- -	i ———	- 100
Color Before:		Clari	ty Before:		_	Texture:
Color After:		Clari	ty After:		_	Artifacts:
Comments:					M. M.	1-26-93

1 INORGANIC ANALYSES DATA SHEET

גמים	SAMPL	r	MO
LPA	SAMPL	ᆫ	NO.

Lab 1	Name:	SOUND_ANALYTICAL_SERVICES Contract: T1092100	100116
		Case No.: SAS No.: 28636	
Matr	ix (so	oil/water): WATER Lab Sa	ample ID: 28636-16

Level low/med): LOW___

Date Received: 12/09/92

% Solids:

__0.0

CAS No.	Analyte	Concentration	С	Q	М
7429-90-5	Aluminum_		_		NR
7440- 36 - 0	Antimony_	60.0	U		P_
7440-38-2	Arsenic	10.0	ַ ע		F_
7440-39-3	Barium		_		NR
7440-41-7	Beryllium		U		P_
7440-43-9	Cadmium	5.0	U	<u>J</u>	P_
7440-70-2	Calcium		_		NR
7440-47-3	Chromium_	11.6	_		P_
7440-48-4	Cobalt		_		NR
7440-50-8	Copper	25.0	U		P_
7439-89-6	Iron		_	ļ	NR
7439-92-1	Lead	5.3	_	ļ	F_
7439-95-4	Magnesium		_		NR
7439- 96-5	Manganese		_	l	NR
7439-97-6	Mercury	0.20	U	İ	AV
7440-02-0	Nickel	40.0	U		P_
7440-09-7	!Potassium		1_	l	NR
7782- 49 - 2	Selenium_			l	F_
7440-22-4	Silver	10.0	U	Ì	P_
7440-23-5			_		NR
7440-28-0	Thallium_		U	l— —	F_
7440-62-2	Vanadium_		. _		NR
7440-66-6		22.9	1_		P_
5955- 70-0	'Cyanide		. _		NR

Color Before:	 Clarity	Before:		Texture:
Color After:	 Clarity	After:		Artifacts:
Comments:			MM	1-26-93
				. ,

	1		
INORGANIC	ANALYSES	DATA	SHEET

EDX	SAMPLE	MO
LPA	SAMPLE	NO.

Lab Name: SOUND_ANALY	TTCAL SERVICES	Contract: T	109210031	100117
Lab Name: Sconz_imiz				
Lab Code:	Case No.:	SAS No.	: 28636_	SDG No.: E&E
<pre>Matrix (soil/water):</pre>	WATER		Lab Sampl	e ID: 28636-7
Level (low/med):	LOW		Date Rece	ived: 12/09/92
% Solids:	0 0			

	3 1 4 -				
CAS No.	Analyte	Concentration	C	Q	M
7429-90-5	Aluminum_		-		NR
7440-36-0	Antimony_	60.0	11		P_
7440-38-2	Arsenic	10.0	U		F
7440-39-3	Barium		Ĭ		NR
7440-41-7	Beryllium	5.0	11		P
7440-43-9	Cadmium	5.0	U		P
7440-70-2	Calcium		-		NR
7440-47-3	Chromium	980	-	I ——	P
7440-48-4	Cobalt		-		NR
7440-50-8	Copper	46.6	-		Р
7439-89-6	Iron		{-		NR
7439-92-1	Lead	4.7	-		F
7439-95-4	Magnesium		-		NR
7439-96-5	Manganese		-		NR
7439-97-6	Mercury		ΙŪ		ΑV
7440-02-0	Nickel	597	i i		P_
7440-09-7	Potassium		1-		NR
7782-49-2	Selenium_		U		F_
7440-22-4	Silver	10.0			P
7440-23-5	Sodium				NR
7440-28-0	Thallium_	10.0	U		F
7440-62-2	Vanadium				NR
7440-66-6	Zinc	25.9	-		P
5955-70-0	Cyanide_		-		NR
	1		1_		

Color Before:	 Clarity	Before:		Texture:
Color After:	 Clarity	After:		Artifacts:
Comments:	 		My	1-26-93

		0.5.	CPA - CLP					
	I	NORGANIC A	1 NALYSES DA	ra si	HEE	ET	EPA	SAMPLE NO.
Lab Name: SOUND	_ANALYTICAI	_SERVICES	Contract	: Tl	092	210031		100118
Lab Code:	Cas	se No.:	SAS	No.:	28	3636_	SDG	No.: E&E
Matrix (soil/wa	ter): SOIL_	_			Lai	o Sampl	e ID:	28636-8
Level (low/med)	: LOW_	_			Dat	te Rece	eived	: 12/09/92
% Solids:	_68.8	3						
Cor	ncentration	Units (ug/	L or mg/kg	dry	w	eight)	MG/	KG
	CAS No	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Concentrat					
	CAS No.	Analyte		101		Q ————————————————————————————————————	M	
	7429-90-5	Aluminum_					NR	
	7440-36-0	Antimony_		2.1	<u></u>		P_	
	7440-38-2	Arsenic		3.9	<u>J</u>]		P_	
	7440-39-3	Barium			_		NR	
	7440-41-7	Beryllium					P_	
	7440-43-9			1.7	II.		P_	
•	7440-70-2				_		NR	
	7440-47-3	Chromium_	1	12.3	I		P_	
	7440-48-4		l		-		NR	
	7440-50-8			19.4	I		P_	
	7439-89-6	Iron			_		NR	
	7439-92-1	Lead		_2.8	$ \mathcal{I} $		P_	
	7439-95-4	1 -			-		NR	
	7439-96-5 7439-97-6	_		0.12			NR	,
	7440-02-0			18.8			AV	
	7440-02-0			10.0	-		P_	
	7782-49-2	1		_3.5	 		NR	
	7440-22-4	Silver		0.72			P_ P_	
	7440-23-5	Sodium _	· · · · · · · · · · · · · · · · · · ·	0.72	1-1		NR	
	7440-28-0	Thallium_		5.3	Ū		P_	
	7440-62-2	· -				<u> </u>	NR	
	7440-66-6	_		33.8	1	·	P_	
	5955-70-0	Cyanide_			-		NR	
		_			_			
Color Before:		Clari	ty Before:			_	Text	ure:
Color After:		Clari	ty After:			_	Art	facts:
Comments:						m m	-U-	-93
					_			

		U.S. 1	EPA - CLP				
	I	NORGANIC A	1 NALYSES DATA	SHEET		EPA SAMPL	E NO.
Lab Name: SOUND	_ANALYTICAL	_SERVICES	Contract: T	10921	0031	10011	.9
Lab Code:	_ Cas	se No.:	SAS No.	: 286	36_	SDG No.:	E&E
Matrix (soil/wa	ter): SOIL_	-		Lab	Sampl	e ID: 2863	86-9
Level (low/med)	: LOW	_		Date	Rece	ived: 12/0	9/92
% Solids:	_75.2	2					
Cor	ncentration	Units (ug/	'L or mg/kg dr	v wei	aht):	MG/KG	
						 ,	
	CAS No.	Analyte	Concentration	C	Q	М	
•	7429-90-5	Aluminum		- - -		NR	
	1	Antimony_	1.7	7 0		P_	
		Arsenic		3 1 1		P_	
	7440-39-3	Barium		_ _ _		NR	
		Beryllium				P_	
	L	Cadmium	2.0	이피_		P	
		Calcium		_ _]_		NR	
	7440-47-3	Chromium_	13.9	9 🎞 –		P_	
	7440-48-4			_ _ -		NR	
	7440-50-8	Copper	19.	3 7 _		P_	
		Iron Lead	4.	7 5-		NR	
		Magnesium		/ ユ ー		P_ NR	
		Manganese		- - -		NR	
		Mercury		<u> </u>		AV	
	7440-02-0			1 1		P_	
	7440-09-7	Potassium		_!=!=		NR	
	7782-49-2	Selenium_	2.	9 0 _		P_	
	7440-22-4	Silver	0.6	6		P_	
	7440-23-5	Sodium	· 	_ _ _		NR	
	7440-28-0	Thallium_	1 =	3 0 2		P_	
	7440-62-2	Vanadium_				NR	
	7440-66-6	Zinc	35.	9 1 -		P_	
	5955-70-0	Cyanide	· 	- - -		NR	
		- i <u> </u>	-			·	
Color Before:		Clari	ty Before:			Texture:	
Color After:		Clari	ty After:			Artifacts	s:
Comments:					MY	1-26-9	

	1		
INORGANIC	ANALYSES	DATA	SHEET

EPA	SAMPLE.	NO.
-----	---------	-----

100120	
--------	--

Lab Name: SOUND_ANALYTICAL_SERVICES Contract:	T109210031	- 1
---	------------	-----

Lab Code: ____ Case No.: ___ SAS No.: 28636_ SDG No.: E&E___

Matrix (soil/water): WATER Lab Sample ID: 28636-10___

Level (low/med): LOW__ Date Received: 12/09/92

% Solids: __0.0

			ļ		
CAS No.	Analyte	Concentration	С	Q	M
7429-90-5	Aluminum_				NR
7440-36-0	Antimony_	60.0	U		P_
7440-38-2	Arsenic	10.0	U		\mathbf{F}_{-}^{-}
7440-39-3	Barium				NR
7440-41-7	Beryllium	5.0	Ū		P_
7440-43-9	Cadmium		U	7	P
7440-70-2	Calcium		_		NR
7440-47-3	Chromium_	_10.0	Ū		P
7440-48-4	Cobalt		1_		NR
7440-50-8	Copper	25.0	U		P
7439-89-6	Iron				NR
7439-92-1	Lead	3.0	Ū		$ \mathbf{F}_{\perp} $
7439-95-4	Magnesium		_		NR
7439-96-5	Manganese		[NR
7439-97-6	Mercury		Ū		AV
7440-02-0	Nickel	40.0	U		P
7440-09-7	Potassium		1_		NR
7782-49-2	Selenium_	5.0	ĺΰ		F_
7440-22-4	Silver	10.0	U	i —	P
7440-23-5	Sodium				NR
7440-28-0	Thallium_		U		F_
7440-62-2	Vanadium				NR
7440-66-6	Zinc	20.0	U		P
5955-70-0	Cyanide_		. _		NR
l	-		. _		11

Color Before:	 Clarity	Before:		Texture:	
Color After:	 Clarity	After:		Artifacts:	
Comments:			M.W.	1-26-93	
	 				<u>-</u>



ecology and environment, inc.

1500 FIRST INTERSTATE BUILDING, 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

MEMORANDUM

DATE: January 26, 1993

TO: Dawn Hartley, Project Manager, E & E, Seattle, WA

FROM: Mark Woodke, TAT-Chemist, E & E, Seattle, WA

THRU: David Byers, TAT-Chemist, E & E, Seattle, WA $\bigcirc \ell / \bigcirc$

SUBJ: Chlorinated Pesticide/PCB Data Quality Assurance Review,

Northwest Pipe and Casing, Clackamas, Oregon

REF: Project TDD: T10-9210-031 Analytical TDD: T10-9210-058

Project PAN: EOR-0201-SC Analytical PAN: EOR-0201-AB

The data quality assurance review of one soil sample collected from the Northwest Pipe and Casing site in Clackamas, Oregon, has been completed. Analysis for Chlorinated Pesticides/Polychlorinated Biphenyls (EPA method 8080) was performed by Sound Analytical Services. Tacoma, Washington.

The sample was numbered: T2100100

Data Qualifications:

I Sample Holding Time: Acceptable.

Sample T2100100 was collected 10-28-92, extracted on 11-10-92, and analyzed on 11-13-92. The sample was within QC holding time criteria of 14 days between collection and extraction and 40 days between extraction and analysis.

II Instrument Performance: Acceptable.

Peak resolution for all compounds was acceptable. The surrogate retention time shift was within QC limits.

.-<u>cycięd pape</u>

III Calibration

A. Initial Calibration: Satisfactory.

A six-point initial calibration was performed for each pesticide of interest, with all % Relative Standard Deviation (%RSDs) within QC limits of < 20 %, except:

Date	Column	Compound	% RSD	QC Limits
11-12-92	DB-5	delta-BHC	23 %	< 20 %
11-12-92	DB-608	alpha-BHC	27 %	< 20 %
11-12-92	DB-608	delta-BHC	27 %	< 20 %
11-12-92	DB-608	Heptachlor	37 %	< 20 %
11-12-92	DB-608	4,4'-DDT	22 %	< 20 %

Positive results and sample quantitation limits for the initial calibration QC outliers were flagged as estimated quantities (J).

A 1-point calibration for each PCB of interest was performed.

B. Continuing Calibration: Not Performed.

A continuing calibration was not necessary as all analyses were performed within 12 hours of the initial calibration, except the method blank. No action was taken based on method blank analysis after the 12 hour time limit as no compounds were detected in the sample.

IV Method Blank: Acceptable.

No contaminants were detected in any method blanks.

V Surrogate Recoveries: Acceptable.

All recoveries for decachlorobiphenyl and tetrachloro-meta-xylene were within QC criteria.

VI Matrix Spike/Matrix Spike Duplicate: Satisfactory.

All matrix spike/matrix spike duplicate percent recoveries were within QC limits, except:

Sample	Compound	Recovery	QC Limits
T2100100S	4,4'-DDT	141 %	23 % - 134 %

VII Field Duplicates: Not Applicable.

VIII Compound Identification: Acceptable.

Compound identification, including dual column confirmation, was acceptable.

IX Compound Quantitation and Reported Detection Limits: Acceptable.

Compound quantitation was acceptable.

X Overall Assessment of Data for Use

The overall usefulness of the data is based on the criteria outlined in the OSWER Directive "National Functional Guidelines For Organic Data Review" (June 1991).

Based upon the information provided, the data are acceptable for use with the above stated data qualifications.

Data Qualifiers and Definitions

- J The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

Ecology & Environment Project: T109210031 Lab No. 28231

Page 3 of 5

December 31, 1992

Lab No. 28231-1

Client ID: T2100100

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-10-92 Date Analyzed: 11-13-92

Compound Concentration, mq/kq

Aldrin	0.001
a-BHC	0.001 げ
b-BHC	0.001
g-BHC	0.001
y-BHC (Lindane)	0.001 J
Chlordane (technical)	0.01
4,4'-DDD	0.001
4,4'-DDE	0.001
4,4'-DDT	0.001 J
Dieldrin	0.001
Endosulfan I	0.001
Endosulfan II	0.001
Endosulfan sulfate	0.001
Endrin	0.001
Endrin aldehyde	0.001
Heptachlor	0.001 J
Heptachlor epoxide	0.001
Endrin Ketone	0.001
Methoxychlor	0.002
Toxaphene	0.01
Aroclor 1016	0.001
Aroclor 1221	0.001
Aroclor, 1232	0.001
Aroclor 1242	0.001
Aroclor 1248	0.001
Aroclor 1254	0.001
Aroclor 1260	0.001
Aroclor 1262	0.001
Aroclor 1268	0.001

MW 1-7-6-93



ecology and environment, inc.

1500 FIRST INTERSTATE BUILDING, 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

MEMORANDUM

DATE:

January 26, 1993

TO:

Dawn Hartley, Project Manager, E & E, Seattle, WA

FROM:

Mark Woodke, TAT-Chemist, E & E, Seattle, WA &

THRU:

David Byers. TAT-Chemist, E & E, Seattle, WA

SUBJ:

Organic Data Quality Assurance Review, Northwest Pipe and

Casing, Clackamas, Oregon

REF:

Project TDD: T10-9210-031

Analytical TDD:

T10-921.0-058

Project PAN:

EOR-0201-SC

Analytical PAN:

EOR-0202-AB

The data quality assurance review of 2 soil samples collected from the Northwest Pipe and Casing site in Clackamas, Oregon, has been completed. Analysis for Semivolatile Organic Compounds (EPA method 8270) was performed by Sound Analytical Services, Tacoma, Washington.

The 2 samples were numbered:

T2100100

T2100101

Data Qualifications:

I Holding Time: Acceptable.

Sample T2100100 was collected 10-28-92. Sample T2100101 was collected on 11-03-92. All samples were extracted on 11-11-92. All samples were analyzed on 11-14-92. All samples were analyzed within QC criteria of 14 days from collection to extraction and 40 days from extraction to analysis.

II GC/MS Tuning: Acceptable.

All tuning check compound mass abundances and ratios were within contract-required limits for semivolatile analysis.

III Calibration

A. Initial Calibration: Satisfactory.

All System Performance Check Compounds (SPCCs) were within contract-required limits for the initial calibration with average Relative Response Factors (RRFs) above 0.05 for semivolatiles. All Calibration Check Compounds (CCCs) and non-CCCs were within contract-required limits for the initial calibration with % Relative Standard Deviations (RSDs) below 30 percent, except:

Date	Compound	%RSDs	Associated Samples
11-13-92	Benzoic Acid	36.8	All
	2,4-Dinitrophenol	37.2	All

No action was taken by the data reviewer as benzoic acid and 2,4-dinitrophenol were not detected in any sample.

B. Continuing Calibration: Satisfactory.

All CCCs were at or below the contract-required Relative Percent Difference (RPD) limits of 25 for the semivolatile continuing calibration. All compounds were at or above the contract-required Relative Response Factor (RRF(50)) QC criteria. All non-CCCs had percent difference (%D) values for the continuing calibration of less than or equal to 25 percent, except:

Date	Time	Compound	%D	QC Limits	Assoc. Samples
11-14-92	0831	Benzoic acid	48.3	< 25	All
		Pentachlorophenol	28.0	< 25	
		4-Nitrophenol	25.5	< 25	

Positive results and sample quantitation limits for the continuing calibration QC outliers were flagged as estimated quantities (J) in the associated samples.

IV Method Blank: Satisfactory.

The following compound was detected in a method blank:

		Concentration	Associated
Blank	Compound	ug/Kg	Samples_
M. Blank	Di-n-butylphthalate	190	All

Results for the compound detected in the blanks were flagged as not detected (U) in the associated samples if the amount detected in the samples was less than 5 times the amount detected in the blank (10 times for common contaminants).

V Surrogate Recovery: Satisfactory.

All surrogate results met QC criteria, except:

Sample	Surrogate	Recovery	QC Limits
T2100101	Nitrobenzene	17 %	23 % - 110 %
	2-Fluorobiphenyl	20 %	30 % - 115 %

Base/neutral positive results and sample quantitation limits for sample T2100101 were flagged as estimated quantities (J).

VI Matrix Spike/Matrix Spike Duplicates: Acceptable.

All matrix spike/matrix spike duplicate (MS/MSD) results were within QC limits. Sample T2100103, analyzed 12-14-92 and reported in a different data validation package, was used as the MS/MSD sample for this data group.

VII Internal Standards: Acceptable.

All internal standard results were within QC limits.

VIII Field Duplicates: Not Applicable.

IX Overall Assessment of Data for Use

The overall usefulness of the data is based on the criteria outlined in the OSWER Directive "National Functional Guideline for Organic Data Review" (June 1991).

Based upon the information provided, the data are acceptable for use with the above stated data qualifications.

Data Qualifiers and Definitions

- J The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

1B SEMIVOLATILE ORGANICS ANALYSIS DATA SHEET

EPA SAMPLE NO.

231-1

ab Name: Sound Analytical Services Contract: T109210031

Lab Code:-

Case No.:-

SAS No.:-

SDG No.:28231

Matrix: (soil/water) SOIL

Lab Sample ID:28231-1

Sample wt/vol: 30.1 (g/ml) G

Lab File ID: S6777

Level: (low/med) LOW

Date Received: 11/04/92

% Moisture: 15 decanted: (Y/N) N

Date Extracted: 11/11/92

Concentrated Extract Volume: 1000.0 (uL) Date Analyzed:11/14/92

Injection Volume: 1.0 (uL)

Dilution Factor:

GPC Cleanup: (Y/N) N

pH: 0.0

CONCENTRATION UNITS:

CAS NO.

COMPOUND

(ug/L or ug/Kg) UG/KG

Q

	T	
108-95-2Phenol	390.	U
111-44-4Bis(2-chloroathyl)ether	390.	<u></u>
95-57-82-Chlorophenol	390.	<u></u>
541-73-11,3-Dichlorobenzene	390.	Ŭ
106-46-71,4-Dichlorobenzene	390.	Ū
100-51-6Benzyl alcohol	780.	Ü
95-50-11,2-Dichlorobenzene	390.	Ū
95-48-72-Methylphenol	390.	Ü
108-60-12,2'-oxybis(1-Chloropropane)	390.	Ü
106-44-54-Methylphenol	390.	Ū
621-64-7N-Nitroso-di-n-propylamine	390.	<u>U</u>
67-72-1Hexachloroethane	390.	Ū l
98-95-3Nitrobenzene	390.	U
78-59-1Isophorone	390.	Ū
88-75-52-Nitrophenol	390.	Ū
105-67-92,4-Dimethylphenol	390.	Ū
65-85-0Benzoic acid	2000.	UJ
111-91-1bis(2-Chloroethoxy)methane	390.	Ŭ
120-83-22,4-Dichlorophenol	390.	Ū
120-82-11,2,4-Trichlorobenzene	390.	Ū
91-20-3Naphthalene	390.	Ū
106-47-84-Chloroaniline	780.	Ŭ
87-68-3Hexachlorobutadiene	390.	Ŭ
59-50-74-Chloro-3-methylphenol	780.	Ü
91-57-62-Methylnaphthalene	390.	Ū
77-47-4Hexachlorocyclopentadiene	390.	Ü
88-06-22,4,6-Trichlorophenol	390.	Ü
95-95-42,4,5-Trichlorophenol	390.	Ü
91-58-72-Chloronaphthalene 88-74-42-Nitroaniline	390.	<u>U</u>
131-11-3Dimethylphthalate	2000.	<u>U</u>
208-96-8Acenaphthylene	390.	Ū
606-20-22,6-Dinitrotoluene	390. 390.	U
2,0 Diniciocoldene	·\	
	1	1

MW 1-26-93

SEMIVOLATILE ORGANICS ANALYSIS DATA SHEET

EPA SAMPLE NO.

ab Name:Sound Analytical Services Contract:T109210031

Lab Code:- Case No.:- SAS No.:- SDG No.:28231

Matrix: (soil/water) SOIL Lab Sample ID:28231-1

Sample wt/vol: 30.1 (g/ml) G Lab File ID: S6777

Level: (low/med) LOW Date Received:11/04/92

% Moisture: 15 decanted: (Y/N) N Date Extracted:11/11/92

Concentrated Extract Volume: 1000.0 (uL) Date Analyzed:11/14/92

Injection Volume: 1.0 (uL) Dilution Factor: 1.0

GPC Cleanup: (Y/N) N pH: 0.0

CONCENTRATION UNITS:
CAS NO. COMPOUND (ug/L or ug/Kg) UG/KG Q

2000. U 390. U 2000. U 2000. U 7 99-09-2----3-Nitroaniline 83-32-9-----Acenaphthene 51-28-5-----2,4-Dinitrophenol 100-02-7----4-Nitrophenol <u>390.</u> 132-64-9-----Dibenzofuran 121-14-2-----2,4-Dinitrotoluene 84-66-2-----Diethylphthalate <u>390.</u> 390. U 390. U 7005-72-3----4-Chlorophenyl-phenylether 86-73-7-----Fluorene 390. U 100-01-6-----4-Nitroaniline 2000. U 534-52-1----4,6-Dinitro-2-methylphenol 2000. U 86-30-6----N-Nitrosodiphenylamine(1) 390. U 390. U 101-55-3----4-Bromophenyl-phenylether 390. U 2000. U 390. U 118-74-1-----Hexachlorobenzene 87-86-5-----Pentachlorophenol 85-01-8----Phenanthrene 120-12-7-----Anthracene 84-74-2-----Di-n-butylphthalate 130. U J <u>390. | ប្</u> 390. U 390. U 91-94-1----3,3'-Dichlorobenzidine 780. U 56-55-3-----Benzo(a)anthracene 390. U 218-01-9-----Chrysene 160. 390. <u>U</u> 117-81-7-----bis(2-Ethylhexyl)phthalate 117-84-0-----Di-n-octylphthalate <u>390.</u>| 205-99-2----Benzo(b)fluoranthene 207-08-9-----Benzo(k)fluoranthene <u>390. U</u> 50-32-8-----Benzo(a)pyrene 390. U 193-39-5----Indeno(1,2,3-cd)pyrene 390. U 53-70-3-----Dibenz(a,h)anthracene <u> 390.</u> บิ 191-24-2----Benzo(q,h,i)pervlene 3**90.** U

(1) - Cannot be separated from Diphenylamine

MW 1-26-93

1B SEMIVOLATILE ORGANICS ANALYSIS DATA SHEET

EPA SAMPLE NO.

231-2

Q

Lab Sample ID:28231-2

ab Name: Sound Analytical Services Contract: T109210031

Case No.:- SAS No.:- SDG No.:28231 Lab Code:-

Lab File ID: S6779 Sample wt/vol: 30.3 (g/ml) G

Date Received: 11/04/92 Level: (low/med) LOW

Date Extracted: 11/11/92 % Moisture: 28 decanted: (Y/N) N

Concentrated Extract Volume: 1000.0 (uL) Date Analyzed:11/14/92

Injection Volume: 1.0 (uL) Dilution Factor: 1.0

GPC Cleanup: (Y/N) N pH: 0.0

Matrix: (soil/water) SOIL

CONCENTRATION UNITS: CAS NO. COMPOUND (ug/L or ug/Kg) UG/KG

		
100 05 0 51 1	4.50	
108-95-2Phenol		<u>U</u>
111-44-4Bis(2-chloroethyl)ether	460.	บร
95-57-82-Chlorophenol	460.	U
541-73-11,3-Dichlorobenzene		UJ
106-46-71,4-Dichlorobenzene		<u>U</u> 5
100-51-6Benzyl alcohol	920.	U
95-50-11,2-Dichlorobenzene	460.	<u> </u>
95-48-72-Methylphenol	460.	Ū
108-60-12,2'-oxybis(1-Chloropropane)	460.	<u>U </u>
106-44-54-Methylphenol	460.	Ū
621-64-7N-Nitroso-di-n-propylamine	460.	บี่
67-72-1Hexachloroethane	460.	ר ע
98-95-3Nitrobenzene	460.	UJ
78-59-1Isophorone	460.	UJ
88-75-52-Nitrophenol	460.	Ū
105-67-92,4-Dimethylphenol	460.	Ū
65-85-0Benzoic acid	2300.	UJ
111-91-1bis(2-Chloroethoxy)methane		UJ
120-83-22,4-Dichlorophenol	460.	Ū
120-82-11,2,4-Trichlorobenzene	460.	ਹੁਤ
91-20-3Naphthalene	460.	UT
106-47-84-Chloroaniline	920.	UT
87-68-3Hexachlorobutadiene	460.	<u>U 7</u>
59-50-74-Chloro-3-methylphenol	920.	U
91-57-62-Methylnaphthalene	460.	UJ
77-47-4Hexachlorocyclopentadiene	460.	UJ
88-06-22,4,6-Trichlorophenol	460.	Ū
95-95-42,4,5-Trichlorophenol	460.	Ū
91-58-72-Chloronaphthalene	460.	ডিক্ত
88-74-42-Nitroaniline	2300.	U
131-11-3Dimethylphthalate	460.	U
208-96-8Acenaphthylene	460.	Ū,
606-20-22,6-Dinitrotoluene	460.	ŪΨ
	· · _	

1C SEMIVOLATILE ORGANICS ANALYSIS DATA SHEET

EPA SAMPLE NO.

231-2

ab Name: Sound Analytical Services Contract: T109210031

SDG No.:28231

Matrix: (soil/water) SOIL

Lab Sample ID:28231-2

Sample wt/vol:

Case No.:-

Lab File ID: S6779

SAS No.:-

Level:

Lab Code:-

(low/med) LOW

Date Received: 11/04/92

% Moisture:

28 decanted: (Y/N) N

Date Extracted: 11/11/92

Concentrated Extract Volume: 1000.0 (uL) Date Analyzed:11/14/92

Injection Volume:

1.0 (uL)

30.3 (q/ml) G

Dilution Factor:

GPC Cleanup: (Y/N) N

pH: 0.0

CAS NO.

COMPOUND

CONCENTRATION UNITS:

(ug/L or ug/Kg) UG/KG

Q

		·
99-09-23-Nitroaniline	2300.	սշ
83-32-9Acenaphthene	460.	03-
51-28-52,4-Dinitrophenol	2300.	<u> </u>
100-02-74-Nitrophenol	2300.	Ŭ 5
132-64-9Dibenzofuran	460.	Ŭ Ť
121-14-22,4-Dinitrotoluene	460.	Ü
84-66-2Diethylphthalate	460.	Ü
7005-72-34-Chlorophenyl-phenylether	460.	Ŭ
86-73-7Fluorene	460.	<u></u> U
100-01-64-Nitroaniline	2300.	<u></u> <u> </u>
534-52-14,6-Dinitro-2-methylphenol	2300.	Ü
86-30-6N-Nitrosodiphenylamine(1)	460.	ਹਰ
101-55-34-Bromophenyl-phenylether	460.	บัง
118-74-1Hexachlorobenzene	460.	05
87-86-5Pentachlorophenol	2300.	ਹੱਤੋਂ
85-01-8Phenanthrene	460.	บ้า
120-12-7Anthracene		บัว
84-74-2Di-n-butylphthalate	440.	VJ
206-44-0Fluoranthene	460.	UJ
129-00-0Pyrene	460.	0
85-68-7Butylbenzylphthalate	460.	U
91-94-13,3'-Dichlorobenzidine	920.	। ਹ
56-55-3Benzo(a)anthracene	460.	UV
218-01-9Chrysene	460.	UV
117-81-7bis(2-Ethylhexyl)phthalate	640.	1 3
117-84-0Di-n-octylphthalate	460.	UJ
205-99-2Benzo(b)fluoranthene	460.	U
207-08-9Benzo(k)fluoranthene	460.	U U
50-32-8Benzo(a)pyrene	460.	U
193-39-5Indeno(1,2,3-cd)pyrene	460.	Ū
53-70-3Dibenz(a,h)anthracene	460.	Ū,
191-24-2Benzo(g,h,i)perylene	460.	UV

(1) - Cannot be separated from Diphenylamine

MIN 1-26-93



ecology and environment, inc.

1500 FIRST INTERSTATE BUILDING, 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

MEMORANDUM

DATE: January 19, 1993

TO: Dawn Hartley, Project Manager, E & E, Seattle, WA

FROM: Mark Woodke, TAT-Chemist, E & E, Seattle, WA MW

THRU: David Byers, TAT-Chemist, E & E, Seattle, WA

SUBJ: Inorganic Data Quality Assurance Review, Northwest Pipe and

Casing, Clackamas, Oregon

REF: Project TDD: T10-9210-031 Analytical TDD: T10-9210-058

Project PAN: EOR-0201-SC Analytical PAN: EOR-0202-AB

The data quality assurance review of 2 soil samples collected from the Northwest Pipe and Casing site in Clackamas, Oregon, has been completed. Analysis for Priority Pollutant Metals (EPA 6000 and 7000 series methods) was performed by Sound Analytical Services, Tacoma, Washington.

The 2 samples were numbered: T2100102 T2100103

Data Qualifications:

I Sample Holding Time: Acceptable.

The samples met QC holding time criteria. Sample T2100102 was collected 11-08-92. Sample T2100103 was collected 11-13-92. All analyses were performed on or before 12-01-92, therefore meeting QC criteria of less than 28 days between sampling and mercury analysis and less than 6 months between sampling and analysis for all other metals.

II Calibration

A. Initial Calibration and Calibration Verification: Acceptable.

All mercury results were within the control limits of 80 to 120 percent of the true values. All ICP results were within the 90 to 110 percent control limits.

B. Continuing Calibration: Acceptable.

All mercury results were within the control limits of 80 to 120 percent of the true values. All ICP results were within the control limits of 90 to 110 percent of the true values.

III Blanks: Satisfactory.

The following blanks contained elemental contamination above the Instrument Detection Limit (IDL):

Blank	Element	Concentration	IDL
ICB	Manganese	17.9 ug/L	15 ug/L
CCB6	Barium	5.3 ug/L	5 ug/L

ICB = Initial Calibration Blank

CCB = Continuing Calibration Blank

Manganese and barium results were flagged as not detected (U) in all samples if the amount detected in the samples was less than five times the amount detected in the blanks.

IV Interference Check Sample Analysis: Satisfactory.

All parameters for the Interference Check Sample (ICS) were within the control limit of 80 to 120 percent of the true values. Aluminum, calcium, cobalt, iron, and magnesium results were not provided for the ICSABF analysis. No action was taken based on ICS results as samples results for the interferents (aluminum, calcium, iron, and magnesium) were not provided for comparison with the ICS results.

V Laboratory Control Sample Analysis: Acceptable.

All Laboratory Control Sample results were within QC limits of 80 - 120 percent.

VI Specific Sample Results

A. Duplicate Sample Analysis: Acceptable.

For all sample values less than five times the CRDL, the duplicate sample values were within 2 times the CRDL. The Relative Percent Difference (RPD) values for the duplicate sample analysis were within QC criteria of less than 20 percent for sample values greater than five times the CRDL.

B. Spike Sample Analysis: Satisfactory.

All Matrix Spike recoveries for the elements analyzed were within QC limits, except:

Sample	Element	Recovery	QC Limits
T2100103S	Arsenic	71.3 %	75% - 125%
T2100103S	Lead	71.3 %	75% - 125%
T2100103S	Selenium	71.3 %	75% - 125%
T2100103S	Thallium	72.9 %	75% - 125%

Positive results and sample quantitation limits for arsenic, lead, selenium, and thallium were flagged as estimated quantities (J) in all samples.

C. Serial Dilution Analysis: Satisfactory.

All Serial Dilution results for the elements analyzed were within QC limits, except:

Sample	Element	Difference	QC Limits
T2100103L	Barium	11.0 %	< 10 %
T2100103L	Chromium	13.5 %	< 10 %
T2100103L	Zinc	12.1 %	< 10 %

Positive barium, chromium, and zinc results were flagged as estimated quantities (J) in all samples.

VII Overall Assessment of Data for Use

The overall usefulness of the data is based on the criteria outlined in "Laboratory Data Validation Functional Guidelines for Evaluating Inorganic Analyses".

Based upon the information provided, the data are acceptable for use with the above stated data qualifications.

Data Qualifiers and Definitions

- J The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

	I	NORGANIC A	1 NALYSES DATA S	HE	ET	EPA SAMPLE NO.
Lab Name: SOUND						100102
						CDC No . ECE
Lab Code:	Cas	e No.:	SAS NO.:	2	8462_	SDG No.: E&E
Matrix (soil/wa	ter): SOIL_	-	•	La	b Sampl	le ID: 28462-1
Level (low/med)	: LOW_	_		Da	te Rec	11/13/92
% Solids:	_69.8	3				11/13/92
Con	centration	Units (ug/	L or mg/kg dry	, w	eight)	: MG/KG
١				11		
	CAS No.	Analyte	Concentration	С	Q	М
	7429-90-5	Aluminum		-		NR
.	7440-36-0		1.5	וּט		P_
	7440-38-2					P_
	7440-39-3		82.5	宁		P_
ļ	7440-41-7					P_
· ·	7440-43-9	_	1.8		**	P_
	7440-70-2			-		NR
	7440-47-3		18.1	15		P_
1	7440-48-4	_				NR
	7440-50-8	Copper	41.9	-		P_
	7439-89-6	Iron				NR
	7439-92-1	Lead	2.5	I		P_
	7439-95-4	Magnesium				NR
	7439-96-5	Manganese	\	1_1	·	NR
	7439-97-6			_		NR
	7440-02-0		18.1	_		P_
	7440-09-7			1-		NR
	7782-49-2		2.6	1 - 1	I	. P_
	7440-22-4	Silver	0.26	ע		P_
	7440-23-5	Sodium		-		NR
	7440-28-0	Thallium_	3.8	U	Ţ	. P_
	7440-62-2	Vanadium_		_		NR
	7440-66-6	Zinc	40.1	T	<u>·</u>	P_ (199
•	5955-70-0	Cyanide		-		NR P NR MW 1-19-9
Color Before:		Clari	ty Before:		<u>.</u>	Texture:
Color After:		Clari	ty After:		_	Artifacts:
Comments:					· · · · · · · · · · · · · · · · · · ·	

		NORGANIC A	1 NALYSES DATA S	HE	ET	EPA	SAMPLE	NO.
Lab Name: SOUNI)_ANALYTICAI	_SERVICES	Contract: T1	.09	210031		100103	
Lab Code:			SAS No.:			SDG	No.: E	&E
Matrix (soil/wa	ater): SOIL	_		La	b Sampl	le ID	: 28462	!-2
Level (low/med)): LOW	_		Da	te Rece	eived	: 12/03	1920 P
% Solids:	_67.2	2					11/13	192
Cor	ncentration	Units (ug/	/L or mg/kg dry	Z W	reight):	: MG/	KG	
	CAS No.	Analyte	Concentration	c	Q	М		
	7429-90-5 7440-36-0 7440-38-2 7440-39-3 7440-41-7 7440-43-9 7440-47-3 7440-47-3 7440-48-4 7440-50-8 7439-95-4 7439-95-4 7439-96-5 7439-97-6 7440-02-0 7440-09-7 7782-49-2 7440-23-5 7440-23-5 7440-66-6 5955-70-0	Aluminum_ Antimony_ Arsenic_ Barium_ Beryllium Cadmium_ Calcium_ Chromium_ Cobalt_ Copper_ Iron_ Lead_ Magnesium Manganese Mercury_ Nickel_ Potassium Selenium_ Silver_ Sodium_ Thallium_ Vanadium_ Zinc_ Cyanide_	1.6 4.7 77.4 0.28 1.1 17.0 34.6 2.9 24.9 2.7 0.27	HH - 1 H - 1 H - 1 H	<u></u>	NR P_P_P_NR P_NR P_NR P_NR P_NR P_NR P_N	Mr	H9-92
Color Before:		Clari	ty Before:		_	Text	ture:	
Color After:		Clari	ty After:		_	Art:	ifacts:	
Comments:								
								

INORGANIC ANALYSES DATA SHEET

גמים	SAMPLE	NIO
CFA	SAMPLIC	140-

	1	NORGANIC A	NALYSES DATA S	neer		,
Lab Name: SOUNI	D_ANALYTICAL	_SERVICES	Contract: T1	.0921	.0031	100102
Lab Code:	Case No.: SAS No.: 284			62_	SDG No.: E&E	
Matrix (soil/wa	ater): SOIL_	-		Lab	Sampl	e ID: 28462-1
Level (low/med): LOW	_		Date	e Rece	eived: 12/03/92
% Solids:	_69.8	3				
Cor	ncentration	Units (ug/	L or mg/kg dry	y wei	ight):	MG/KG
	CAS No.	Analyte	Concentration	С	Q	М
	7429-90-5 7440-36-0 7440-38-2 7440-39-3 7440-41-7 7440-43-9 7440-47-3 7440-48-4 7440-50-8 7439-95-4 7439-95-4 7439-95-4 7439-96-5 7439-97-6 7440-02-0 7440-09-7 7782-49-2 7440-23-5 7440-28-0 7440-66-6 5955-70-0	Aluminum_Antimony_Arsenic_Barium_Beryllium Cadmium_Calcium_Chromium_Cobalt_Copper_Iron_Lead_Magnesium Manganese Mercury_Nickel_Potassium Selenium_Silver_Sodium Thallium_Vanadium_Zinc_Cyanide_C	0.11			NR NR NR NR NR NR NR NR NR NR NR NR NR N
Color Before:		Clari	ty Before:			Texture:
Color After:		Clari	ty After:			Artifacts:

	I	NORGANIC A	l NALYSES DATA S	HEET	EPA SAMPLE NO.
Lab Name: SOUNI	_ANALYTICAI	_services	Contract: T1	.09210031	100103
Lab Code:					SDG No.: E&E
Matrix (soil/wa	ater): SOIL	_		Lab Samp	le ID: 28462-2
Level (low/med)): LOW			Date Rec	eived: 12/03/92
					22,000,00
% Solids:	_67.	2			
Cor	ncentration	Units (ug,	L or mg/kg dry	y weight)	: MG/KG
	CAS No.	Analyte	Concentration		M
	CAS NO.	Analyce	Concentration	C Q	<u></u>
		Aluminum_		-	NR
	T .	Antimony_		-	NR
	7440-38-2	Arsenic		-	_ NR
	ľ	Barium		\-\- <u></u>	NR
		Beryllium		-	_ NR
	7440-43-9	Cadmium		\-\- 	_ NR
	7440-70-2	Calcium		-	_ NR
	7440-47-3	Chromium_		-	_ NR
	7440-48-4	Cobalt		-	_ NR
•	7440-50-8	Copper		-	_ NR
	7439-89-6	Iron		-	_ NR
	7439-92-1	Lead		-	_ NR
	7439-95-4	Magnesium		-	_ NR
	7439-96-5 7439-97-6	Manganese	0.11	0	_ NR
	7440-02-0	Mercury Nickel	⁰ •±±		_ AV NR
	7440-02-0	Potassium	\ 	-	NR NR
	7782-49-2	Selenium_		-	NR
	7440-22-4		.	-	NR
	7440-23-5	Sodium		-	NR
	7440-28-0	Thallium	·	-	NR
	7440-62-2			-	NR
	7440-66-6			1-1	NR OM CIVO
	5955-70-0	Cyanide_			NR // Y
Color Before:		Clari	ty Before:		Texture:
Color After:		Clari	ty After:		Artifacts:
Comments:					



ecology and environment, inc.

1500 FIRST INTERSTATE BUILDING, 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

MEMORANDUM

DATE: January 19, 1993

TO: Dawn Hartley, Project Manager, E & E, Seattle, WA

FROM: Mark Woodke, TAT-Chemist, E & E. Seattle, WAM W

THRU: David Byers, TAT-Chemist, E & E. Seattle, WA

SUBJ: Organic Data Quality Assurance Review, Northwest Pipe and

Casing, Clackamas, Oregon

REF: Project TDD: T10-9210-031 Analytical TDD: T10-9210-058

Project PAN: EOR-0201-SC Analytical PAN: EOR-0202-AB

The data quality assurance review of 2 soil samples collected from the Northwest Pipe and Casing site in Clackamas, Oregon, has been completed. Analysis for Semivolatile Organic Compounds (EPA method 8270) was performed by Sound Analytical Services, Tacoma, Washington.

The 2 samples were numbered: T2100102 T2100103

Data Qualifications:

I Holding Time: Acceptable.

Sample T2100102 was collected 11-08-92 and sample T2100103 was collected on 11-13-92. Both samples were extracted on 11-18-92. and analyzed on 12-01-92. Both samples met QC criteria of 14 days from collection to extraction and 40 days from extraction to analysis.

II GC/MS Tuning: Acceptable.

All tuning check compound mass abundances and ratios were within contract-required limits for semivolatile analysis.

III Calibration

A. Initial Calibration: Satisfactory.

All System Performance Check Compounds (SPCCs) were within contract-required limits for the initial calibration with average Relative Response Factors (RRFs) above 0.05 for semivolatiles. All Calibration Check Compounds (CCCs) and non-CCCs were within contract-required limits for the initial calibration with % Relative Standard Deviations (RSDs) below 30 percent, except:

Date	Compound	%RSDs	Associated Samples
11-18-92	Benzoic Acid	36.9	A11
	2,4-Dinitrophenol	37.2	All

No action was taken by the data reviewer as benzoic acid and 2,4-dinitrophenol were not detected in any sample.

B. Continuing Calibration: Satisfactory.

All CCCs were at or below the contract-required Relative Percent Difference (RPD) limits of 25 for the semivolatile continuing calibration. All compounds were at or above the contract-required Relative Response Factor (RRF(50)) QC criteria. All non-CCCs had percent difference (%D) values for the continuing calibration of less than or equal to 25 percent, except:

Date	Time	Compound	%D	QC Limits	Assoc. Samples
12-01-92	1921	1,4-Dichlorobenzene	67.5	< 25	All
•	1921	Nitrobenzene	36.6	< 25	
	1921	bis(2-chloroethoxy)methane	62.7	< 25	

Sample quantitation limits for the continuing calibration QC outliers were flagged as estimated quantities (J) in the associated samples.

IV Method Blank: Satisfactory.

The following compound was detected in a method blank:

		Concentration	Associated
Blank	Compound	ug/Kg	Samples
M. Blank	Di-n-butylphthalate	810	All

Results for the compound detected in the blanks were flagged as not detected (U) in the associated samples if the amount detected in the samples was less than 5 times the amount detected in the blank (10 times for common contaminants).

V Surrogate Recovery: Acceptable.

All surrogate results met QC criteria.

VI Matrix Spike/Matrix Spike Duplicates: Acceptable.

All matrix spike/matrix spike duplicate results were within QC limits.

VII Internal Standards: Acceptable.

All internal standard results were within QC limits.

VIII Field Duplicates: Not Applicable.

IX Overall Assessment of Data for Use

The overall usefulness of the data is based on the criteria outlined in the OSWER Directive "National Functional Guideline for Organic Data Review" (June 1991).

Based upon the information provided, the data are acceptable for use with the above stated data qualifications.

Data Qualifiers and Definitions

- J The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

Ecology & Environment Project: T109210031

Lab No. 28462 Page 3 of 13

December 14, 1992

Lab No. 28462-1

Semivolatile Organics Per EPA SW-846 Method 8270 Date Extracted: 11-18-92

Date Analyzed: 12-1-92

Compound	Concentration ug/kg		
Phenol bis(2-Chloroethyl) ether 2-Chlorophenol 1,3-Dichlorobenzene 1,4-Dichlorobenzene Benzyl Alcohol 1,2-Dichlorobenzene 2-Methylphenol bis(2-Chloroisopropyl)ether 4-Methylphenol N-Nitroso-Di-N-propylamine Hexachloroethane Nitrobenzene Isophorone 2-Nitrophenol 2,4-Dimethylphenol Benzoic Acid bis(2-Chloroethoxy)methane 2,4-Dichlorophenol 1,2,4-Trichlorobenzene Naphthalene 4-Chloroaniline Hexachlorobutadiene 4-Chloro-3-methylphenol		460 460 460 460 460 460 460 460 460 460	

MW 1-19-93

Client ID: T2100102

Ecology & Environment Project: T109210031 Page 4 of 13

Page 4 of 13 Lab No. 28462 December 14, 1992

Lab No. 28462-1

Client ID: T2100102

EPA Method 8270 Continued

Compound	Concentration ug/kg		
2-Methylnaphthalene Hexachlorocyclopentadiene 2,4,6-Trichlorophenol 2,4,5-Trichlorophenol 2-Chloronaphthalene 2-Nitroaniline Dimethyl phthalate Acenaphthylene 2,6-Dinitrotoluene 3-Nitroaniline Acenaphthene 2,4-Dinitrophenol 4-Nitrophenol Dibenzofuran 2,4-Dinitrotoluene Diethylphthalate 4-Chlorophenyl phenyl ether Fluorene 4-Nitroaniline 4,6-Dinitro-2-methylphenol N-Nitrosodiphenylamine 4-Bromophenyl phenyl ether Hexachlorobenzene Pentachlorophenol Phenanthrene Anthracene Di-n-butylphthalate	1 100 11	460 U 460 460 46	
DI W. Duckibucuarace	1,400 U	1	

mr 1-19-93

Ecology & Environment Project: T109210031

Page 5 of 13 Lab No. 28462 December 14, 1992

Lab No. 28462-1

Client ID: T2100102

EPA Method 8270 Continued

Compound	Concentration ug/kg		
Fluoranthene Pyrene Butyl benzyl phthalate 3,3'-Dichlorobenzidine Benzo(a)anthracene Chrysene bis(2-ethylhexyl)phthalate Di-n-octyl phthalate Benzo(b)fluoranthene Benzo(k)fluoranthene Benzo(a)pyrene Indeno(1,2,3-cd)pyrene Dibenz(a,h)anthracene Benzo(g,h,i)perylene	600	460 U 460 930 460 460 460 460 460 460 460 460 460	MM 19-92

Ecology & Environment Project: T109210031

Lab No. 28462 Page 9 of 13 December 14, 1992

Lab No. 28462-2

T2100103

Client ID:

Semivolatile Organics Per EPA SW-846 Method 8270

Date Extracted: 11-18-92 Date Analyzed: 12-1-92

Compound	Concentration ug/kg		
Phenol bis(2-Chloroethyl) ether 2-Chlorophenol 1,3-Dichlorobenzene 1,4-Dichlorobenzene Benzyl Alcohol 1,2-Dichlorobenzene 2-Methylphenol bis(2-Chloroisopropyl)ether 4-Methylphenol N-Nitroso-Di-N-propylamine Hexachloroethane Nitrobenzene Isophorone 2-Nitrophenol 2,4-Dimethylphenol Benzoic Acid bis(2-Chloroethoxy)methane 2,4-Dichlorophenol 1,2,4-Trichlorobenzene Naphthalene 4-Chloroaniline Hexachlorobutadiene 4-Chloro-3-methylphenol		490 490 490 490 490 490 490 490 490 490	

MW 1-19-93

Continued

Ecology & Environment Project: T109210031

Page 10 of 13 Lab No. 28462 December 14, 1992

Lab No. 28462-2

Client ID: T2100103

EPA Method 8270 Continued

	San annua 1		
Compound	Concentration ug/kg		
2-Methylnaphthalene		490U	
Hexachlorocyclopentadiene	\	490	
2,4,6-Trichlorophenol		490	
2,4,5-Trichlorophenol		490	
2-Chloronaphthalene		490	
2-Nitroaniline	i	2,500	
Dimethyl phthalate	}	490	
Acenaphthylene		490	
2,6-Dinitrotoluene)	490	
3-Nitroaniline	ļ	2,500	
Acenaphthene	1	490	
2,4-Dinitrophenol		2,500	
4-Nitrophenol	Ì	2,500	
Dibenzofuran	1	490	
2,4-Dinitrotoluene		490	
Diethylphthalate		490	
4-Chlorophenyl phenyl ether		490	
Fluorene		490	
4-Nitroaniline		2,500	
4,6-Dinitro-2-methylphenol		2,500	ı
N-Nitrosodiphenylamine		490	
4-Bromophenyl phenyl ether		490	
Hexachlorobenzene		490	
Pentachlorophenol		2,500	
Phenanthrene		490	
Anthracene		490₩	
Di-n-butylphthalate	1,400 U		

MW 1-9-93

Ecology & Environment Project: T109210031

Page 11 of 13 Lab No. 28462 December 14, 1992

Lab No. 28462-2

Client ID: T2100103

EPA Method 8270 Continued	- 		
Compound	Concentration ug/kg		
Fluoranthene Pyrene Butyl benzyl phthalate 3,3'-Dichlorobenzidine Benzo(a)anthracene Chrysene bis(2-ethylhexyl)phthalate Di-n-octyl phthalate Benzo(b)fluoranthene Benzo(k)fluoranthene Benzo(a)pyrene Indeno(1,2,3-cd)pyrene Dibenz(a,h)anthracene Benzo(g,h,i)perylene	540	490 U 490 490 490 490 490 490 490 490 490 490	MN 1-9-9



ecology and environment, inc.

1500 FIRST INTERSTATE BUILDING, 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

MEMORANDUM

DATE: February 4, 1993

TO: Dawn Hartley, Project Manager, E & E, Seattle, WA

FROM: Mark Woodke, TAT-Chemist, E & E. Seattle. WA

THRU: David Byers. TAT-Chemist, E & E. Seattle, WA

SUBJ: Organic Data Quality Assurance Review, Northwest Pipe and

Casing, Clackamas, Oregon

REF: Project TDD: T10-9210-031 Analytical TDD: T10-9210-058

Project PAN: EOR-0201-SC Analytical PAN: EOR-0202-AB

The data quality assurance review of 1 water sample collected from the Northwest Pipe and Casing site in Clackamas, Oregon, has been completed. Analysis for Total Organic Carbon (EPA method 415.1) was performed by Sound Analytical Services, Tacoma. Washington.

The sample was numbered: T2100120

Data_Qualifications:

I Holding Time: Acceptable.

Sample T2100120 was collected 11-20-92, and was extracted and analyzed on 12-02-92. The method states to analyze the sample as soon as possible after collection. No action was taken based on the 12 days between collection and analysis as the sample was preserved properly and was kept at 4 degrees celsius from collection until analysis.

II Calibration: Acceptable.

A two-point calibration was performed prior to sample analysis, with all results acceptable in the reviewers' professional judgment.

III Method Blank: Acceptable.

No organic carbon was detected in the method blank.

IV Matrix Spike/Matrix Spike Duplicates: Acceptable.

The matrix spike/matrix spike duplicate recoveries were both 90 %, which is acceptable in the reviewers' professional judgment.

V Duplicates: Acceptable.

The duplicate Relative Percent Difference was 11 %, which is acceptable in the reviewers' professional judgment.

VI Overall Assessment of Data for Use

The overall usefulness of the data is based on the criteria outlined in the OSWER Directive "National Functional Guidelines for Organic Data Review" (June 1991) and EPA Method 415.1.

Based upon the information provided, the data are acceptable for use with the above stated data qualifications.

Data Qualifiers and Definitions

- J The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

Ecology & Environment Project: T109210031 Lab No. 28636

Lab No. 28636 Page 56 of 94 December 21, 1992

Lab No. 28636-10

Client ID: T2100120 (water)

Total Organic Carbon Per EPA Method 415.1

Date Extracted: 12-2-92 Date Analyzed: 12-2-92

TOC

9 mg/L



ecology and environment, inc.

1500 FIRST INTERSTATE BUILDING. 999 THIRD AVENUE, SEATTLE, WASHINGTON 98104, TEL. (206) 624-9537 International Specialists in the Environment

MEHORANDUM

DATE:

February 11, 1993

TO:

Dawn Hartley, Project Manager, E & E. Seattle, WA

FROM:

Mark Woodke, TAT-Chemist, E & E, Seattle. WA M

THRU:

David Byers, TAT-Chemist, E & E, Seattle, WA 1.

SUBJ:

Chlorinated Pesticide/PCB Data Quality Assurance Review,

Northwest Pipe and Casing, Clackamas, Oregon

REF:

Project TDD: T10-9210-031

Analytical TDD:

T10-9210-058

Project PAN: EOR-0201-SC

Analytical PAN: EOR-0201-AB

The data quality assurance review of sixteen water and two soil samples collected from the Northwest Pipe and Casing site in Clackamas, Oregon, has been completed. Analysis for Chlorinated

Pesticides/Polychlorinated Biphenyls (EPA method 8080) was performed by Sound Analytical Services, Tacoma, Washington.

The samples were numbered:

T2100104	T2100105	T2100106	T2100110
T2100111	T2100112	T2100113	T2100114
T2100115	T2100116	T2100117	T2100118(soil)
T2100119(soil)	T2100120	T2100121	T2100122
T2100123	T2100124		

Data Qualifications:

Ι Sample Holding Time: Acceptable.

Samples T2100104 through T2100106 were collected 11-18-92. Samples T2100110 through T2100117 were collected 11-19-92. Samples T2100118 through T2100120 and T2100124 were collected 11-20-92. Samples T2100121 through T2100123 were collected 11-14-92. All extractions were performed on or before 11-25-92. All analyses were performed on or before 12-02-92. The samples were within QC holding time criteria of 14 days between collection and extraction and 40 days between extraction and analysis.

TT Instrument Performance: Acceptable.

Peak resolution for all compounds was acceptable. The surrogate retention time shift was within QC limits on at least one column for each sample.

recycled paper

III Calibration

A. Initial Calibration: Acceptable.

A three-point initial calibration was performed for each pesticide of interest, with all % Relative Standard Deviation (%RSDs) within QC limits of < 15 %. A one-point initial calibration was performed for each PCB of interest.

B. Continuing Calibration: Satisfactory.

All continuing calibration results were within QC limits, except:

Compound	Column	% Difference	QC Limits
Methoxychlor	DB-608	16 %	₹ 15 %

No action was taken by the data reviewer as the methoxychlor difference on the DB-5 column was within QC limits and methoxychlor was not detected in any of the samples.

IV Method Blank: Acceptable.

No contaminants were detected in any method blanks.

V Surrogate Recoveries: Satisfactory.

All recoveries for decachlorobiphenyl(DCB) and tetrachloro-meta-xylene(TCMX) were within QC criteria, except:

Sample	Column	Surrogate	Recovery	QC Limits
T2100104	DB-608	TCMX	44 %	60 % - 150 %
	DB-608	DCB	55 %	60 % - 150 %

No action was taken by the data reviewer as the surrogate results on the DB-5 column were within OC limits.

VI Matrix Spike/Matrix Spike Duplicate: Acceptable.

The matrix spike/matrix spike duplicate percent recoveries were within OC limits.

VII Field Duplicates: Not Applicable.

VIII Compound Identification: Acceptable.

Compound identification, including dual column confirmation, was acceptable.

- IX Compound Quantitation and Reported Detection Limits: Acceptable.
 - Compound quantitation was acceptable.
- X Overall Assessment of Data for Use

The overall usefulness of the data is based on the criteria outlined in the OSWER Directive "National Functional Guidelines For Organic Data Review" (June 1991).

Based upon the information provided, the data are acceptable for use with the above stated data qualifications.

Data Qualifiers and Definitions

- J The associated numerical value is an estimated quantity because the reported concentrations were less than the contract required detection limits or quality control criteria were not met.
- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.

Ecology & Environment Project: T109210031

Lab No. 28636 Page 6 of 94

December 21, 1992

Lab No. 28635-1

Client ID: T2100114 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

<u>Concentration</u>, ug/l

Aldrin	0.01 U
a-BHC	0.01
b-BHC	0.01
g-BHC	0.01
y-BHC (Lindane)	0.01
Chlordane (technical)	0.10
4,4'-DDD	0.01
4,4'-DDE	0.01
4,4'-DDT	0.01
Dieldrin	0.01
Endosulfan I	0.01:
Endosulfan II	0.01
Endosulfan suifate	0.01
Endrin	0.01
Endrin aldehyde	0.01
Heptachlor	0.01
Heptachlor epoxide	0.01
Endrin Ketone	0.01
Methoxychlor	0.02
Toxaphene	0.10
Aroclor 1015	3.10
Aroclor 1221	0.10
Aroclor 1232	0.10
Aroclor 1242	0.10
Aroclor 1248	0.10
Aroclor 1254	3.10
Aroclor 1260	0.10
Aroclor 1262	0.10
Aroclor 1268	0.10 \/

Ecology & Environment Project: T109210031 Lab No. 28636

Lab No. 28636 Page 12 of 94 December 21, 1992

Lab No. 28636-2

Client ID: T2100112 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Sampound	Concentration, ug/l	POL	
Aldrin a-BHC		0.01 /	
D-BHC		0.01	
a-BHC		0.01	
y-BHC (Lindane)		0.01	
Chlordane (technical)		0.10	
4,4'-DDD		0.01	
÷,4'-DDE		0.01	
4,4'-DDT	•	0.01	
Dieldrin		0.01	
Endosulfan I		0.01	
Endosulfan II	'	0.01	
Endosulfan sulfate		0.01	
Endrin		0.01	
Endrin aldehyde	•	0.01	
Heptachlor Heptachlor epoxide		0.01	
Endrin Ketone		0.01	
Methoxychlor		0.01:	A C
Toxaphene		0.10	$\mathcal{M}_{\mathcal{M}}$
Aroclor 1016	·	0.10	1-11-93
Aroclor 1221	•	0.10	17/-9/2
Aroclor 1232	•	0.10	- CU 1/
Aroclor 1242		3.10	1
Aroclor 1248		0.10	
Arocior 1254		C.10	·
Aroclor 1260		0.10	
Aroclor 1262	•	0.10,/	
Aroclor 1258		2.10 /	

Ecology & Environment Project: T109210031

Lab No. 28635 Page 18 of 94 December 21, 1992

Lab No. 28636-3

Client ID: T2100113 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

<u>Compound</u> <u>Concentration, ug/l</u>

Aldrin a-BHC b-BHC g-BHC y-BHC (Lindane) Chlordane (technical) 4,4'-DDD 4,4'-DDE 4,4'-DDT Dieldrin Endosulfan II Endosulfan III Endosulfan sulfate Endrin Endrin aldehyde Heptachlor Heptachlor epoxide Endrin Ketone Methoxychlor Toxaphene Aroclor 1016 Aroclor 1221 Aroclor 1248 Aroclor 1254 Aroclor 1254 Aroclor 1250 Aroclor 1262 Aroclor 1268	0.01 0.10 0.10
Arocior 1258	0.10

Ecology & Environment Project: T109210031 Lab No. 28636

Page 24 of 94 December 21, 1992

Lab No. 28635-4

Client ID: T2100104 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Compound Concentration, ug/1

a-BHC b-BHC g-BHC y-BHC (Lindane) Chlordane (technical) 4,4'-DDD 4,4'-DDE 4,4'-DDT Dieldrin Endosulfan I Endosulfan II Endosulfan sulfate Endrin Endrin aldehyde Heptachlor Heptachlor epoxide Endrin Ketone Methoxychlor Toxaphene Aroclor 1016 Aroclor 1221 Aroclor 1232 Aroclor 1242 Aroclor 1248 Aroclor 1254 Aroclor 1254 Aroclor 12560 Aroclor 1260	0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01	
Aroclor 1268	0.1	$\sqrt{}$

Ecology & Environment Project: T109210031

Lab No. 28636 Fage 30 of 94 December 21, 1992

Lab No. 28636-5 Client ID: T2100105 (water)

Organochlorine Pesticides and PCB's Per EPA Method 80.80

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Sampound	Concentration, ug/l	POL
Aldrin a-BHC b-BHC g-BHC y-BHC (Lindane) Chlordane (technical) 4,4'-DDD 4,4'-DDT Dieldrin Endosulfan II Endosulfan II Endosulfan sulfate Endrin Endrin aldehyde Heptachlor Heptachlor Heptachlor Heptachlor Toxaphene Aroclor 1016 Aroclor 1221 Aroclor 1232 Aroclor 1242 Aroclor 1254 Aroclor 1254 Aroclor 1256 Aroclor 1260 Aroclor 1262 Aroclor 1262 Aroclor 1263		3.01 0.10 0.10

Ecology & Environment Project: T109210031

Lab No. 28636 Page 36 of 94 December 21, 1992

Lab No. 28636-6 Client ID: T2100106 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Compound	Concentration, us/1	POL
Aldrin a-BHC b-BHC g-BHC (Lindane) Chlordane (technical) 4,4'-DDD 4,4'-DDE 4,4'-DDT Dieldrin Endosulfan II Endosulfan II Endosulfan sulfate Endrin Endrin aldehyde Heptachlor Heptachlor Heptachlor Heptachlor Toxaphene Aroclor 1016 Aroclor 1221 Aroclor 1232 Aroclor 1242 Aroclor 1254 Aroclor 1254 Aroclor 1250 Aroclor 1260 Aroclor 1262 Aroclor 1262 Aroclor 1268		0.01 0.01
		V

Continued .

Ecology & Environment Project: T109210031 Lab No. 28636

Page 42 of 94
December 21, 1992

Lab No. 28636-7

Client ID: T2100117 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Compound

Concentration, ug/1

Aldrin a-BHC b-BHC g-BHC y-BHC (Lindane) Chlordane (technical) 4,4'-DDD 4,4'-DDE 4,4'-DDT Dieldrin Endosulfan I Endosulfan II Endosulfan sulfate Endrin Endrin aldehyde Heptachlor Heptachlor epoxide Endrin Ketone Methoxychlor Toxaphene Aroclor 1016 Aroclor 1221 Aroclor 1232 Aroclor 1242 Aroclor 1254 Aroclor 1254 Aroclor 1260	0.01 0.10 0.10	
	0.10	
	0.10	V

Ecology & Environment Project: T109210031 Lab No. 28636 Page 48 of 94

Lab No. 28636-8

December 21, 1992

Client ID: T2100118 (soil)

Organochlorine Pesticides and PCB's Per EPA Method 8080 Date Extracted: 11-25-92

Date Analyzed: 12-2-92

Compound Concentration, mg/kg

Aldrin a-BHC b-BHC g-BHC Y-BHC (Lindane) Chlordane (technical) 4,4'-DDD 4,4'-DDE 4,4'-DDT Dieldrin Endosulfan II Endosulfan II Endosulfan sulfate Endrin Endrin aldehyde Heptachlor Heptachlor Heptachlor Heptachlor Toxaphene Aroclor 1016 Aroclor 1221 Aroclor 1232 Aroclor 1242 Aroclor 1248 Aroclor 1254 Aroclor 1260 Aroclor 1260 Aroclor 1262	0.001 0.001
Aroclor 1268	2.010

Ecology & Environment Project: T109210031

Lab No. 28635 Page 54 of 94 December 21, 1992

Lab No. 28636-9

Compound

Client ID: T2100119 (soil)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Concentration, mg/kg

Aroclor 1248 Aroclor 1254 Aroclor 1260 Aroclor 1262 Aroclor 1268
--

Continued .

Ecology & Environment Project: T109210031

Lab No. 28636 Page 60 of 94 December 21, 1992

Lab No. 28635-10 Client ID: T2100120 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Compound

Concentration, us/1

Aldrin a-BHC b-BHC g-BHC y-BHC (Lindane) Chlordane (technical)	0.01 0.01 0.01 0.01 0.01 0.10
4,4'-DDD	0.01
4,4'-DDE	0.01
4,4'-DDT Dieldrin	0.01
Endosulfan I	0.01
Endosulfan II	0.01
Endosulfan sulfate	0.01
Endrin	0.01
Endrin aldehyde	0.01
Heptachlor	0.01
Heptachlor epoxide	0.01
Endrin Ketone	0.01
Methoxychlor	0.02
Toxaphene	0.10
Aroclor 1016	0.10
Aroclor 1221	0.10
Aroclor 1232	0.10
Aroclor 1242	0.10
Aroclor 1248	0.10
Aroclor 1254	0.10
Aroclor 1260	0.10
Aroclor 1262	0.10 /
Aroclor 1268	0.10

Ecology & Environment Project: T109210031 Lab No. 28636

Page 74 of 94 December 21, 1992

Lab No. 28636-15

Client ID: T2100115 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Aldrin a-BHC b-BHC c-BHC g-BHC (Lindane) Chlordane (technical) 4,4'-DDD 4,4'-DDT 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.0

Ecclogy & Environment Project: T109210031

Lab No. 28636 Page 80 of 94 December 21, 1992

Compound

Lab No. 28636-15 Client ID: T2100116 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Concentration, ug/l

Aldrin	0.01 V
a-BHC	0.01;
b-BHC	0.01
g-BHC	0.01
ý-BHC (Lindane)	0.01
Chlordane (technical)	0.10
4,4'-DDD	0.01
4,4'-DDE	0.01
4,4'-DDT	0.01
Dieldrin	0.01
Endosulfan I	0.01
Endosulfan II	0.01
Endosulfan sulfate	0.01
Endrin	0.01
Endrin aldehyde	0.01
Heptachlor	0.01
Heptachlor epoxide	0.01
Endrin Ketone	0.01
Methoxychlor	0.02
Toxaphene	0.10
Aroclor 1016	0.10 ;
Aroclor 1221	0.10
Aroclor 1232	0.10
Aroclor 1242	0.10
Aroclor 1248	0.10
Aroclor 1254	0.10
Aroclor 1260	0.10
Aroclor 1262	0.10 /
Aroclor 1268	0.10 \ /
	V

Continued .

Ecology & Environment Project: T109210031

Lab No. 28636 Page 86 of 94

December 21, 1992

Lab No. 28636-17

Client ID: T2100110 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Concentration, ug/l

Aldrin a-BHC b-BHC g-BHC y-BHC (Lindane) Chlordane (technical) 4,4'-DDD 4,4'-DDE 4,4'-DDT Dieldrin Endosulfan II Endosulfan II Endosulfan sulfate Endrin Endrin aldehyde Heptachlor Heptachlor Heptachlor epoxide Endrin Ketone Methoxychlor Toxaphene Aroclor 1016 Aroclor 1221 Aroclor 1232 Aroclor 1242 Aroclor 1248 Aroclor 1254 Aroclor 12560 Aroclor 1260 Aroclor 1262	0.01 0.01
Aroclor 1262	0.10/
Aroclor 1268	0.10V

(MW) 1-26-93

Ecology & Environment Project: T109210031

Lab No. 28636 Page 92 of 94 December 21, 1992

Compound

Lab No. 28636-19 Client ID: T2100111 (water)

Organochlorine Pesticides and PCB's Per EPA Method 8080

Date Extracted: 11-25-92 Date Analyzed: 12-2-92

Concentration, ug/l

Aldrin	0.01
a-BHC	0.01
b-BHC	0.01
g-BHC	0.01
y-BHC (Lindane)	0.10
Chlordane (technical)	1
4,4'-DDD	0.01
4,4'-DDE	0.01
4,4'-DDT	0.01
Dieldrin	0.01
Endosulfan I	0.01
Endosulfan II	0.01
Endosulfan sulfate	0.01
Endrin	0.01
Endrin aldehyde	0.01
Heptachlor	0.01
Heptachlor epoxide	0.01
Endrin Ketone	0.01
Methoxychlor	0.02
Toxaphene	0.10
Aroclor 1016	0.10
Aroclor 1221	0.10
Aroclor 1232	0.10
Aroclor 1242	0.10
Aroclor 1248	0.10
Aroclor 1254	0.10
Arecier 1260	0.10 ·
Aroclor 1262	0.10
Aroclor 1268	0.10 V